MATERIAL SAFETY DATA SHEET **PA12 150 GREEN**

Version Number 1.0 Revision Date 07/13/2013

Page 1 of 6 Print Date 7/17/2013

POLYONE CORPORATI 33587 Walker Road, Avor		OH 44012
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PA12 150 GREEN
Product code	:	CC10183896
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

Components CAS No Weight percent

Components	CAS-No.	Weight percent
Rutile, antimony chromium buff	68186-90-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact				
Acute exposure					
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.				
Ingestion	: May be harmful if swallowed.				
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.				
Skin	: Experience shows no unusual dermatitis hazard from routine handling.				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				

PolyOne.

MATERIAL SAFETY DATA SHEET **PA12 150 GREEN**

Version Number 1.0 Revision Date 07/13/2013 Page 2 of 6 Print Date 7/17/2013

Medical Conditions Aggravated by Exposure:	: None known.		
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIREFIGHTING MEASURES		
Flash point	: not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.		
	7. HANDLING AND STORAGE		
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.		

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **PA12 150 GREEN**

Version Number 1.0							
Revision Date 07/13/2013							

_

Page 3 of 6 Print Date 7/17/2013

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.					
8. EXPOSURE CONTROLS/PERSONAL PROTECTION					
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields			
Hand protection	:	Protective gloves			
Skin and body protection	:	Long sleeved clothing			
Additional Protective Measures	:	Safety shoes			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid
 : pellets
 : GREEN
 : very faint
 : Not determined
 : not applicable
 : insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

10. STABILITY AND REACTIVITY

PolyOne

MATERIAL SAFETY DATA SHEET **PA12 150 GREEN**

Version Number 1.0 Revision Date 07/13/2013 Page 4 of 6 Print Date 7/17/2013

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	0	Themical Name	Effect	Target Organ		
68186-90-3	Rutile, antimony chromium buff		Irritant	Eyes, Skin, Respiratory system.		
			CAL INFORMATIO)N		
		12. ECOLOGIC				
Persistence and degra	dability	: Not readily b	iodegradable.			
Environmental Toxic	ity	: Chemicals ar polymer matr	•	e as they are bound within the		
Bioaccumulation Pot	ential	: Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice		: no data availa	: no data available			
		13. DISPOSAL	CONSIDERATION	NS		
Product		possible recy generator of classification	cling is preferred to d waste material has the , transportation and d	he product can be recycled. Where lisposal or incineration. The e responsibility for proper waste isposal in accordance with and local regulations.		
Contaminated packaging		material has t transportation	he responsibility for	ble. The generator of waste proper waste classification, ordance with applicable federal, ons.		

PolyOne.

MATERIAL SAFETY DATA SHEET **PA12 150 GREEN**

Version Number 1.0 Revision Date 07/13/2013 Page 5 of 6 Print Date 7/17/2013

	1	4. TRANSPOR	F INFOR	MATION				
U.S. DOT Classification	:	Not regulated for	or transpo	rtation.				
ICAO/IATA	:	Refer to specifi	c regulation	on.				
IMO/IMDG (maritime)	:	Refer to specifi	c regulation	on.				
	15	. REGULATOR	RY INFO	RMATION	N			
US Regulations:								
OSHA Status	:	Classified as ha	zardous b	ased on co	mponent	ts.		
TSCA Status	:	All component TSCA Inventor		roduct are	listed on	or exer	npt from th	e
US. EPA CERCLA Hazardo	us Sub	stances (40 CFR	302)					
not applicable								
SARA Title III Section 302		-						
Unless specific chemicals are	e identi	fied under this se	ection, this	s product is	Not Ap	plicable	under this	regul
SARA Title III Section 313	Foxic C	Chemicals:						
	e identi	fied under this se	ection, this					regul
Unless specific chemicals are				CAS-No.		Weight 5.00 -	percent	
Chemical Name			r		-)	5.00 -	10.00	
Chemical Name CHROMIUM III COMPO		CHROMIUM III	[68186-90-				
Chemical Name	NY		[
Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMON	NY		[1314-98-3		1.00 -	5.00	
Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMOI COMPOUNDSCHROMI	NY		[1.00 -	5.00	
Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMOI COMPOUNDSCHROMIU ZINC COMPOUNDS	NY UM CO	OMPOUNDS	[1.00 -	5.00	
Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMON COMPOUNDSCHROMIU ZINC COMPOUNDS Canadian Regulations:	NY UM CO	OMPOUNDS	CAS-N	1314-98-3		t	5.00 NPRI ID	#

PolyOne

MATERIAL SAFETY DATA SHEET **PA12 150 GREEN**

Version Number 1.0 Revision Date 07/13/2013

Page 6 of 6 Print Date 7/17/2013

Rutile, antimony chromium buff 68186-	90-3 5.00 - 10.00
Zinc sulfide 1314-9	8-3 1.00 - 5.00

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
1328-53-6	
68186-90-3	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.