PolyOne.

MATERIAL SAFETY DATA SHEET GREY 552 ABS

Version Number 1.0 Revision Date 08/05/2013

Product Use

Page 1 of 7 Print Date 8/5/2013

1.	PROD	UCT AND COMPANY IDENTIFICATION
POLYONE CORPORAT 33587 Walker Road, Avo		OH 44012
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREY 552 ABS
Product code	:	CC10185353
Chemical Name	:	Mixture
CAS-No.	:	Mixture

2. COMPOSITION/INFORMATION ON INGREDIENTS

: Industrial Applications

Components	CAS-No.	Weight percent
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-	52829-07-9	1 - 5
piperidinyl) ester		
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **GREY 552 ABS**

Version Number 1.0 Revision Date 08/05/2013 Page 2 of 7 Print Date 8/5/2013

Medical Conditions	: None known.	
Aggravated by Exposure:		
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptom persist or in all cases of doubt seek medical advice.	3
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	r at
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
	5. FIREFIGHTING MEASURES	
Flash point	: not applicable	
Flammable Limits		
Upper explosion limit	: not applicable	
Lower explosion limit	: not applicable	
Auto-ignition temperature	: not applicable	
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroger (NOx), other hazardous materials, and smoke are all possible. 	l
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal.	in
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. He	at



MATERIAL SAFETY DATA SHEET **GREY 552 ABS**

			Prir	nt Date 8/5/2
	0	nly in areas with appropriate	exhaust ventilation.	
Storage		Leep containers dry and tightl nd contamination. Keep in a		re absorption
8.1	EXPOSURE	C CONTROLS/PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protec	tive equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shield	s	
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		Iandle in accordance with goo ractice. Wash hands before b		
Engineering measures		leat only in areas with approp ppropriate exhaust ventilation		. Provide
Exposure limit(s)				
-	Value	Exposure time	Exposure type	List:
Exposure limit(s) Components Titanium dioxide	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type	List: ACGIH
Components		Time Weighted Average	Exposure type Total dust.	ACGIH
Components	10 mg/m3	Time Weighted Average (TWA):		ACGIH OSHA Z
Components	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Total dust. Total dust. as Ti	ACGIH OSHA ZI OSHA ZI MX OEL
Components	10 mg/m3 15 mg/m3 10 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average	Total dust. Total dust. as Ti	
Components	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit	Total dust. Total dust. as Ti as Ti	ACGIH OSHA ZI OSHA ZI MX OEL
Components Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	Total dust. Total dust. as Ti as Ti OPERTIES	ACGIH OSHA ZI OSHA ZI MX OEL MX OEL
Components	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : solid	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR	Total dust. Total dust. as Ti as Ti OPERTIES ouration rate : No	ACGIH OSHA ZI OSHA ZI MX OEL
Components Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : solid : pelle : GRE	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR Evap ts Specie CY Bulk	Total dust. Total dust. as Ti as Ti OPERTIES ouration rate : No ific Gravity : No	ACGIH OSHA ZI OSHA ZI MX OEL MX OEL
Components Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : solid : pelle : GRE : very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR Evap ets Speci EVA Bulk faint	Total dust. Total dust. Total dust. as Ti as Ti OPERTIES OUTATION TATE : No ific Gravity : No density : No	ACGIH OSHA ZI OSHA ZI MX OEL MX OEL
Components Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : solid : pelle : GRE : very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR Evap ets Speci Speci EVA Bulk faint Vapo	Total dust. Total dust. as Ti as Ti OPERTIES ouration rate : No offic Gravity : No density : No our pressure : not	ACGIH OSHA ZI OSHA ZI MX OEL MX OEL MX OEL
Components Titanium dioxide Image: Colour of the second s	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIO : solid : pelle : GRE : very : Not a : not a	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR L Evap Ets Species EY Bulk faint Vapor determined Vapor upplicable pH	Total dust. Total dust. as Ti as Ti OPERTIES ouration rate : No offic Gravity : No density : No our pressure : not our density : not	ACGIH OSHA ZI OSHA ZI MX OEL MX OEL MX OEL
Components Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIO : solid : pelle : GRE : very : Not of	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR L Evap Ets Species EY Bulk faint Vapor determined Vapor upplicable pH	Total dust. Total dust. as Ti as Ti OPERTIES ouration rate : No offic Gravity : No density : No our pressure : not our density : not	ACGIH OSHA ZI OSHA ZI MX OEL MX OEL MX OEL



MATERIAL SAFETY DATA SHEET **GREY 552 ABS**

Version Number 1.0 Revision Date 08/05/2013 Page 4 of 7 Print Date 8/5/2013

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
52829-07-9	Decanedioic acid, bis(2,2,6,6-tetramethyl-4- piperidinyl) ester	Irritant	Eyes.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
52829-07-9	Decanedioic acid, bis(2,2,6,6-tetramethyl-4- piperidinyl) ester	Oral LD50 Dermal LD50	3,700 mg/kg > 3,100 mg/kg	rat rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

MATERIAL SAFETY DATA SHEET **GREY 552 ABS**

Version Number 1.0 Revision Date 08/05/2013 Page 5 of 7 Print Date 8/5/2013

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	

blvUn<u>e</u>

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET **GREY 552 ABS**

Version Number 1.0 Revision Date 08/05/2013 Page 6 of 7 Print Date 8/5/2013

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulationChemical NameCAS-No.Weight percentZINC COMPOUNDS68187-51-91.00 - 5.00

Canadian Regulations:

Chemical Name			CAS-No.	Weight percent	NPRI ID#
Zinc ferrite brown spinel (C.I. 119)	. Pig	gment Yellow	68187-51-9	1.00 - 5.00	
WHMIS Classification	:	D2A			
DSL	:	All components	s of this product a	re on the Canadia	n Domestic
	:		s of this product a (DSL) or are exer		n Domestic
	:				n Domestic
ational Inventories:		Substances List			n Domestic

Korea KECI : Listed

Japan ENCS

Philippines PICCS : Listed

16. OTHER INFORMATION

: Not determined

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

MATERIAL SAFETY DATA SHEET **GREY 552 ABS**

Version Number 1.0 Revision Date 08/05/2013 Page 7 of 7 Print Date 8/5/2013

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.