SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023



Page 1 of 19 Print Date 08/30/2023

SAFETY DATA SHEET

SHELL WHITE 85835

Section 1. Identification		
GHS product identifier Chemical name CAS number Other means of identification Product type	:	SHELL WHITE 85835 Mixture Mixture CC10186546 solid
<u>Relevant identified uses of the subst</u> Product use	ance :	or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION 33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. Some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	CARCINOGENICITY - Category 1A
GHS label elements		
Hazard pictograms	:	
Signal word	:	Danger

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023



Page 2 of 19 Print Date 08/30/2023

Hazard statements	:	May cause cancer.
Precautionary statements		
Prevention	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	:	IF exposed or concerned: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10186546

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	>= 10 - <= 25	13463-67-7
Silica, amorphous	>= 1 - <= 3	7631-86-9
Chrome yellow (Lead chromate pigment)	>= 0.3 - <= 1	1344-37-2
Ethyl benzene	> 0 - <= 0.3	100-41-4
Styrene	> 0 - <= 0.3	100-42-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

AVIENT

Page 3 of 19 Print Date 08/30/2023

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	:	No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact Inhalation	:	No specific data. No specific data.

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023



Page 4 of 19 Print Date 08/30/2023

Skin contact Ingestion	: :	No specific data. No specific data.	
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	:	No specific treatment.	
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

SHELL WHITE 85835

ÀVIENT

/ersion Number 1.6	Page 5 of 19
Revision Date 08/26/2023	Print Date 08/30/2023

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containn	nent a	nd cleaning up
Small spill	:	Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

AVIENT

Page 6 of 19 Print Date 08/30/2023

Conditions for safe storage, including any incompatibilities
 Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01)
	TWA 10 mg/m3 Form: Total dust
	OSHA PEL (1993-06-30)
	TWA 15 mg/m3 Form: Total dust
	ACGIH TLV (2022-01-06)
	TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles
	TWA 2.5 mg/m3 Form: respirable fraction, finescale particles
Silica, amorphous	NIOSH REL (1994-06-01)
	TWA 6 mg/m3
Chrome yellow (Lead chromate pigment)	ACGIH TLV (2018-03-20)
	TWA 0.0002 mg/m3 (as Cr) Form: Inhalable fraction
	STEL 0.0005 mg/m3 (as Cr) Form: Inhalable fraction
	NIOSH REL (2010-09-01)
	TWA 0.0002 mg/m3
	OSHA PEL 1989 (1989-03-01)
	CEIL 0.1 mg/m3 (as CrO3)
	OSHA PEL 1989 (1989-03-01)
	TWA 0.05 mg/m3 (calculated as Pb)
	OSHA PEL (2006-11-27)
	TWA 0.005 mg/m3 (as Cr)
	OSHA PEL (1993-06-30)
	TWA 0.05 mg/m3 (calculated as Pb)
	OSHA PEL Z2 (2006-11-27)

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

ÀVIENT

Page 7 of 19 Print Date 08/30/2023

	CEIL 0.001 mg/m3
Ethyl benzene	OSHA PEL 1989 (1989-03-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm OSHA PEL (1993-06-30) TWA 435 mg/m3 100 ppm NIOSH REL (1994-06-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm ACGIH TLV (2010-12-06) Ototoxicant TWA 20 ppm
Styrene	ACGIH TLV (2020-03-01) Ototoxicant TWA 10 ppm STEL 20 ppm NIOSH REL (1994-06-01) TWA 215 mg/m3 50 ppm STEL 425 mg/m3 100 ppm OSHA PEL 1989 (1989-03-01) TWA 215 mg/m3 50 ppm STEL 425 mg/m3 100 ppm OSHA PEL 72 (1993-06-30) TWA 100 ppm CEIL 200 ppm AMP 600 ppm
Appropriate engineering controls Environmental exposure controls	 If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

ÀVIENT

Page 8 of 19
Print Date 08/30/2023

Eye/face protection	:	clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
<u>Skii protection</u>		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Pellets.]
Color	:	WHITE
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not applicable.
Burning time	:	Not available.
		0/40

Burning rate

SAFETY DATA SHEET

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

ÀVIENT

Page 9 of 19 Print Date 08/30/2023

Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not applicable.
(flammable) limits		Upper: Not applicable.
Vapor pressure	:	Not available.
Vapor density	:	Not applicable.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not applicable.
octanol/water		11
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not applicable.
Aerosol product		
Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time	:	Not available.
equivalent		
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid Incompatible materials	:	Keep away from extreme heat and oxidizing agents. Keep away from strong acids. Oxidizer.



SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

Page 10 of 19 Print Date 08/30/2023

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

:

:

Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide (TiO2)				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists		-	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Benzene, ethyl-				
	LD50 Oral	Rat	3,500 mg/kg	-
	LD50 Dermal	Rabbit	5,000 mg/kg	-
Styrene				
	LD50 Oral	Rat	2,650 mg/kg	-
	LC50 Inhalation	Rat	2,770 ppm	4 h
	Gas.			
	LC50 Inhalation	Rat	11.8 Mg/l	4 h
	Vapor			

Conclusion/Summary

Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Silica	Eyes - Mild irritant	Rabbit	-	24 hrs	-
Benzene, ethyl-	Skin - Mild irritant	Rabbit	-	24 hrs	-
	Eyes - Severe irritant	Rabbit	-		-
Styrene	Eyes - Mild irritant	Human	-		-
	Skin - Mild irritant	Rabbit	-		-
	Skin - Moderate irritant	Rabbit	-		-
	Eyes - Severe irritant	Rabbit	-		-
	Eyes - Moderate irritant	Rabbit	-	24 hrs	-

Conclusion/Summary		
Skin	:	Mixture.Not fully tested.
Eyes	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

AVIENT

Page 11 of 19)
Print Date 08/30/2023	3

Sensitization

Conclusion/Summary Skin Respiratory	:	Mixture.Not fully tested. Mixture.Not fully tested.
Mutagenicity		
Conclusion/Summary	:	Mixture.Not fully tested.
Carcinogenicity		
Conclusion/Summary	:	Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide (TiO2)	-	2B	-
Silica	-	3	-
C.I. Pigment Yellow 34	+	12A	Known to be a human carcinogen.Reasonably anticipated to be a human carcinogen.
Benzene, ethyl-	-	2B	-
Styrene	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Teratogenicity

Conclusion/Summary	:	Mixture.Not fully tested
--------------------	---	--------------------------

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure) Not available.

Not available.

Aspiration hazard

Name	Result
Benzene, ethyl-	ASPIRATION HAZARD - Category 1

Information on the likely routes of : Not available. exposure

Potential acute health effects

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023



	Pa	ge	12	of	19
Print	Date	08/	/30/	/20	23

Eye contact Inhalation Skin contact Ingestion	 No known significant effects or critical hazards.
Symptoms related to the physical, o	chemical and toxicological characteristics
Eye contact Inhalation Skin contact Ingestion <u>Delayed and immediate effects and</u>	 No specific data. No specific data. No specific data. No specific data. also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects Potential delayed effects	Not available.Not available.
Long term exposure	
Potential immediate effects Potential delayed effects	Not available.Not available.
Potential chronic health effects	
Conclusion/Summary	: Mixture.Not fully tested.
General Carcinogenicity	 No known significant effects or critical hazards. May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity Teratogenicity Developmental effects Fertility effects	 No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.
Numerical measures of toxicity	
<u>Acute toxicity estimates</u> N/A	
Other information	: This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.
	12/19

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023



Page 13 of 19 Print Date 08/30/2023

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
		dubia	
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water		
Benzene, ethyl-			
	Acute LC50 4.2 Mg/l Fresh	Fish - Oncorhynchus mykiss	96 h
	water		
	Acute EC50 6.53 Mg/l Marine	Crustaceans - Artemia sp.	48 h
	water		
	Acute EC50 2.93 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	Acute EC50 4.9 Mg/l Marine	Algae - Skeletonema costatum	72 h
	water		
	Acute EC50 7.7 Mg/l Marine	Algae - Skeletonema costatum	96 h
	water		
Styrene			
	Acute LC50 4.02 Mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Acute EC50 0.0047 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	Acute LC50 52 Mg/l Marine	Crustaceans - Artemia salina	48 h
	water		
	Acute EC50 78 Mg/l Marine	Algae - Skeletonema costatum	96 h
	water		

Conclusion/Summary

: Not available.

Persistence and degradability

Conclusion/Summary

: Not available.

Bioaccumulative potential

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

AVIENT

Page 14 of 19
Print Date 08/30/2023

Product/ingredient name	LogPow	BCF	Potential
C.I. Pigment Yellow 34	-	3,600.00	high
Benzene, ethyl-	3.6	-	low
Styrene	0.35	13.49	low

Mobility in soil

Soil/water partition coefficient (KOC)	:	Not available.
Other adverse effects	:	No known significant effects or critical hazards.

:

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water	:	Consult mode specific transport rules

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

AVIENT

Page 15 of 19 Print Date 08/30/2023

IMO/IMDG

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: The following components are listed: Chrome yellow (Lead chromate pigment)
		United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed
		United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not listed
		United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		United States - TSCA 6 - Final risk management: Listed Chrome
		yellow (Lead chromate pigment)
		United States - TSCA 6 - Proposed risk management: Not listed
		United States - TSCA 8(a) - Chemical risk rules: Not listed
		United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
		United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
		United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed
		United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
		United States - TSCA 8(d) - Health and safety studies: Not listed
		United States - EPA Clean water act (CWA) section 307 - Priority
		pollutants: Listed Chrome yellow (Lead chromate pigment) Zinc ferrite brown spinel (C.I. Pigment Yellow 119) Ethyl benzene
		United States - EPA Clean water act (CWA) section 311 -
		Hazardous substances: Listed
		United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed
		United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed
		United States - Department of commerce - Precursor chemical:
		Not listed
Clean Air Act Section 112(b)	:	Listed

Clean Air Act Section 112(b)

15/19

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023



Page 16 of 19 Print Date 08/30/2023

Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		
DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

SARA 311/312

Classification

CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
Titanium oxide (TiO2)	>= 10 - <= 25	CARCINOGENICITY - Category 2
Silica	>= 1 - <= 3	EYE IRRITATION - Category 2B
C.I. Pigment Yellow 34	>= 0.3 - <= 1	CARCINOGENICITY - Category 1B
Benzene, ethyl-	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1
Styrene	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

<u>SARA 313</u>

Form R - Reporting requirements

Product name	CAS number	%
Chrome yellow (Lead chromate pigment)	1344-37-2	>= 0.1 - < 1

ÄVIENT

SAFETY DATA SHEET

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

Page 17 of 19 Print Date 08/30/2023

Ethyl benzene	100-41-4	>= 0.1 - < 1
Styrene	100-42-5	>= 0.1 - < 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts :	The following components are listed:
	Titanium dioxide
	Silica, amorphous
New York :	None of the components are listed.
New Jersey :	The following components are listed:
	Titanium dioxide
	Chrome yellow (Lead chromate pigment)
	Ethyl benzene
Pennsylvania :	The following components are listed:
	Titanium dioxide
	Silica, amorphous

California Prop. 65

WARNING: This product can expose you to chemicals including Chrome yellow (Lead chromate pigment), which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Chrome yellow (Lead chromate pigment)	Yes.	Yes.
Ethyl benzene	Yes.	-
Styrene	Yes.	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations Inventory list		
Australia	:	All components are listed or exempted.
		17/19

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

ÀVIENT

Page 18 of 19
Print Date 08/30/2023

Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): All components are listed or exempted.
		Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted. All components are listed or exempted.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. <u>History</u>

Date of printing	:	08/30/2023
Date of issue/Date of revision	:	08/26/2023
Date of previous issue	:	03/14/2022
Version	:	1.6
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From

SHELL WHITE 85835

Version Number 1.6 Revision Date 08/26/2023

ÀVIENT

Page 19 of 19 Print Date 08/30/2023

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Not available.

References

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.