PolvOne.

MATERIAL SAFETY DATA SHEET ROSEMARY MINT MID

Version Number 1.1 Revision Date 09/19/2013

Page 1 of 8 Print Date 9/19/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ROSEMARY MINT MID
Product code	:	CC10187399
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Chromium (III) oxide	1308-38-9	5 - 10
Rutile, antimony chromium buff	68186-90-3	5 - 10
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne

MATERIAL SAFETY DATA SHEET **ROSEMARY MINT MID**

Version Number 1.1 Revision Date 09/19/2013 Page 2 of 8 Print Date 9/19/2013

Medical Conditions			
Aggravated by Exposure:			
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIREFIGHTING MEASURES		
Flash point	: not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 		
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.		
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.		
	7. HANDLING AND STORAGE		

PolyOne.

MATERIAL SAFETY DATA SHEET **ROSEMARY MINT MID**

Version Number 1.1 Revision Date 09/19/2013		Page 3 of 8 Print Date 9/19/2013
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	'OSU I	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET ROSEMARY MINT MID

Version Number 1.1 Revision Date 09/19/2013 Page 4 of 8 Print Date 9/19/2013

Components	Value	Exposure time	Exposure type	List:
Chromium (III) oxide	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Evapouration rate

Specific Gravity

Vapour pressure

Vapour density

Bulk density

pН

:

:

Not applicable

Not determined

: Not established

: not applicable

: not applicable

: not applicable

: solid

:

pellets

: GREEN

: very faint

: Not determined

: not applicable

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

: insoluble 10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

MATERIAL SAFETY DATA SHEET ROSEMARY MINT MID

Version Number 1.1 Revision Date 09/19/2013

Page 5 of 8 Print Date 9/19/2013

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

12. ECOLOGICAL INFORMATION			
Persistence and degradability	:	Not readily biodegradable.	
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Additional advice	:	no data available	

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET ROSEMARY MINT MID

Version Number 1.1 Revision Date 09/19/2013 Page 6 of 8 Print Date 9/19/2013

	13. DISPOSAL CONSIDERATIONS	
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Not regulated for transportation.	
ICAO/IATA	: Refer to specific regulation.	
IMO/IMDG (maritime)	e) : Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.	

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for
			Mixture/Product
Chromium (III)	1308-38-9	010 lbs	134 LB
oxide			

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

PolyOne.

MATERIAL SAFETY DATA SHEET ROSEMARY MINT MID

Version Number 1.1 Revision Date 09/19/2013 Page 7 of 8 Print Date 9/19/2013

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
CHROMIUM III COMPOUNDSCHROMIUM	1308-38-9	5.00 - 10.00
COMPOUNDS		
CHROMIUM III COMPOUNDSCHROMIUM III	68186-90-3	5.00 - 10.00
COMPOUNDSANTIMONY		
COMPOUNDSCHROMIUM COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Aluminum oxide	1344-28-1	0.10 - 1.00	
Chromium (III) oxide	1308-38-9	5.00 - 10.00	
Rutile, antimony chromium buff	68186-90-3	5.00 - 10.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1308-38-9	
68186-90-3	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed

:

•	Linter

- Europe EINECS : Listed
- Japan ENCS : Listed
- Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET ROSEMARY MINT MID

Version Number 1.1 Revision Date 09/19/2013

Page 8 of 8 Print Date 9/19/2013

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.