PolvOne

## MATERIAL SAFETY DATA SHEET BEIGE CTR/UV/AS CMPD

Version Number 1.0 Revision Date 02/26/2014

Page 1 of 7 Print Date 3/3/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BEIGE CTR/UV/AS CMPD
Product code	:	CC10195208
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium stearate	1592-23-0	1 - 5
Zinc stearate	557-05-1	1 - 5
Silica, amorphous	7631-86-9	30 - 60

## 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne

# MATERIAL SAFETY DATA SHEET **BEIGE CTR/UV/AS CMPD**

Version Number 1.0 Revision Date 02/26/2014 Page 2 of 7 Print Date 3/3/2014

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Graben disside blanket Weter energy Drugender From</li> </ul>
Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	<ul> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen</li> </ul>
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE

PolyOne.

# MATERIAL SAFETY DATA SHEET BEIGE CTR/UV/AS CMPD

rsion Number 1.0 vision Date 02/26/2014		Page 3 of Print Date 3/3/201
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

P<u>olyOne</u>

# MATERIAL SAFETY DATA SHEET **BEIGE CTR/UV/AS CMPD**

Version Number 1.0 Revision Date 02/26/2014 Page 4 of 7 Print Date 3/3/2014

Components	Value	Exposure time	Exposure type	List:
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Zinc stearate	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	10 mg/m3	Time Weighted Average (TWA):		ACGIH

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Evapouration rate

Specific Gravity

Vapour pressure

Vapour density

Bulk density

pН

: Not applicable

: Not determined

: Not established

: not applicable

: not applicable

: not applicable

: solid

: pellets

: very faint

: insoluble

: Not determined

: not applicable

: TAN

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

## **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.

## MATERIAL SAFETY DATA SHEET BEIGE CTR/UV/AS CMPD

#### Version Number 1.0 Revision Date 02/26/2014

Page 5 of 7 Print Date 3/3/2014

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
557-05-1	Zinc stearate	Systemic effects	Eyes, Skin, Respiratory
			system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.

## LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	>10 gm/kg	rat
557-05-1	Zinc stearate	Oral LD50	> 10 gm/kg	rat

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. When possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION

5/7

PolyOne.

# MATERIAL SAFETY DATA SHEET **BEIGE CTR/UV/AS CMPD**

Version Number 1.0 Revision Date 02/26/2014 Page 6 of 7 Print Date 3/3/2014

U.S. DOT Classification	: Not regulated for	r transportation.		
ICAO/IATA	: Refer to specific	regulation.		
IMO/IMDG (maritime)	: Refer to specific	regulation.		
	15. REGULATOR	Y INFORMATI	ON	
US Regulations:				
OSHA Status	: Classified as haz	zardous based on	components.	
TSCA Status	: All components TSCA Inventory	s of this product a	re listed on or e	exempt from the
US. EPA CERCLA Hazardous	Substances (40 CFR 3	302)		
not applicable				
California Proposition 65	: Not applicable			
SARA Title III Section 302 Ex	tremely Hazardous Su	bstance		
Unless specific chemicals are i	dentified under this see	ction, this produc	t is Not Applica	ble under this regul
SARA Title III Section 313 To				
Unless specific chemicals are i Chemical Name	dentified under this see	ction, this produc		ble under this regulation ight percent
ZINC COMPOUNDS		557-05-		) - 5.00
Canadian Regulations: National Pollutant Relea	ase Inventory (NPRI)	CAS-No.	Weight	NPRI ID#
Zinc stearate		557-05-1	percent 1.00 - 5.00	
WHMIS Classification	: Not controlled.			

PolyOne

# **MATERIAL SAFETY DATA SHEET BEIGE CTR/UV/AS CMPD**

Version Number 1.0 Revision Date 02/26/2014

/ersion Number 1.0 Revision Date 02/26/2014		Page 7 of 7 Print Date <i>3/3/2014</i>
	Substances List (DSL) or are exempt.	
National Inventories:		
Australia AICS	Listed	
China IECS	Not determined	
Europe EINECS	Listed	
Japan ENCS	Not determined	
Korea KECI	Not determined	
Philippines PICCS	Not determined	
	16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.