UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 1 of 17 Print Date 08/12/2023

SAFETY DATA SHEET

UV CHARCOAL PVC V2

Section 1. Identification		
GHS product identifier Chemical name	:	UV CHARCOAL PVC V2 Mixture
CAS number Other means of identification	:	Mixture CC10381993
	ance	solid or mixture and uses advised against
Product use Supplier's details	:	Industrial applications. Plastics. AVIENT CORPORATION
	-	33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. All ingredients are bound in a PVC polymer matrix and potential for hazardous exposure as shipped is minimal. PVC resin is manufactured from Vinyl Chloride Monomer (VCM). PVC resin manufacturers take special efforts to strip residual VCM from their resins. Residual VCM in the resin is typically below 8.5 ppm. However, VCM is a known carcinogen. The end-user (fabricator) should take necessary precautions (mechanical ventilation, local exhaust, respiratory protection, etc.) to protect employees from exposure to any vapors or dusts that may be released during heating or fabrication. See Sections 8 and 11 for special precautions.After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	:	Not classified.
GHS label elements		

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023

ÀVIENT

Page 2 of 17 Print Date 08/12/2023

Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Not available.

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10381993

CAS number/other identifiers

Ingredient name	%	CAS number
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	>= 10 - <= 25	68515-48-0
C9-rich		
Titanium dioxide	>= 10 - <= 25	13463-67-7
2-Benzotriazolyl-4-methylphenol	>= 10 - <= 25	2440-22-4
Carbon black	>= 3 - <= 5	1333-86-4
Silica, amorphous	>= 1 - <= 3	7631-86-9
Quartz	> 0 - <= 0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 3 of 17 Print Date 08/12/2023

Section 4. First aid measures

Description of necessary first aid measur	es
---	----

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	:	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Specific treatments	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 4 of 17 Print Date 08/12/2023

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal	:	May emit Hydrogen Chloride (HCl).
decomposition products		Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : For emergency responders :	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions :	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill :	Move containers from spill area.	Vacuum or sweep up material and

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 5 of 17 Print Date 08/12/2023

Large spillplace in a designated, labeled waste container. Dispose of via a
licensed waste disposal contractor.Large spill:Move containers from spill area. Prevent entry into sewers, water
courses, basements or confined areas. Vacuum or sweep up material
and place in a designated, labeled waste container. Dispose of via a
licensed waste disposal contractor. Note: see Section 1 for emergency
contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
1,2-Benzenedicarboxylic acid, di-C8-10- branched alkyl esters, C9-rich	None.
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023




Page 6 of 17 Print Date 08/12/2023

2-Benzotriazolyl-4-methylphenol	None.
Carbon black	OSHA PEL 1989 (1989-03-01)
	TWA 3.5 mg/m3
	OSHA PEL (1993-06-30)
	TWA 3.5 mg/m3
	NIOSH REL (1994-06-01)
	TWA 3.5 mg/m3
	NIOSH REL (1994-06-01)
	TWA 0.1 mgPAH/m ³
	ACGIH TLV (2010-12-06)
	TWA 3 mg/m3 Form: Inhalable fraction
Silica, amorphous	NIOSH REL (1994-06-01)
I I I I I I I I I I I I I I I I I I I	TWA 6 mg/m3
Ouartz	OSHA PEL 1989 (1989-03-01)
Qualiz	TWA 0.1 mg/m3 (Calculated as Quartz) Form: Respirable dust
	OSHA PEL Z3 (1997-09-03)
	TWA 250 MPPCF / (%SiO2+5) Form: Respirable
	TWA 10 MG /M3 / ($\%$ SiO2+2) Form: Respirable
	OSHA PEL Z3 (1997-09-03)
	TWA 30 MG /M3 / ($\%$ SiO2+2) Form: Total dust
	NIOSH REL (1994-06-01)
	TWA 0.05 mg/m3 Form: Respirable dust
	ACGIH TLV (2005-12-09)
	TWA 0.025 mg/m3 Form: Respirable fraction
	OSHA PEL (2016-06-23)
	TWA 0.05 mg/m3 Form: Respirable dust

Appropriate engineering controls Environmental exposure controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end

UV CHARCOAL PVC V2



ÀVIENT

Page 7 of 17	
Print Date 08/12/2023	

Eye/face protection	:	of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Pellets.]
Color	:	GREY
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not applicable.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not applicable.

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023

ÀVIENT

Page 8 of 17 Print Date 08/12/2023

(flammable) limits		Upper: Not applicable.
Vapor pressure	:	Not available.
Vapor density	:	Not applicable.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not applicable.
Decomposition tomporotume		Not available.
Decomposition temperature		
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not applicable.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or
Chemical stability	:	its ingredients. Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure			
1,2-Benzenedicarboxylic acid,	di-C8-10-branched a	lkyl esters, C9-rich					
	LD50 Oral	Rat	10,000 mg/kg	-			
Titanium oxide (TiO2)							
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h			
	Dusts and mists						
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-			



UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023

Page 9 of 17 Print Date 08/12/2023

Phenol, 2-(2H-benzotriazol-2-yl)-4-methyl-									
	LD50 Oral	Rat	10,000 mg/kg	-					
Carbon black									
	LD50 Oral	Rat	15,400 mg/kg	-					

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Eyes - Mild irritant	Rabbit	-		-
Phenol, 2-(2H-benzotriazol- 2-yl)-4-methyl-	Eyes - Mild irritant	Rabbit	-	24 hrs	-
Silica	Eyes - Mild irritant	Rabbit	-	24 hrs	-

Conclusion/Summary Skin Eyes Respiratory	:	Mixture.Not fully tested. Mixture.Not fully tested. Mixture.Not fully tested.
Sensitization		
Conclusion/Summary Skin Respiratory	:	Mixture.Not fully tested. Mixture.Not fully tested.
Mutagenicity		
Conclusion/Summary	:	Mixture.Not fully tested.
Carcinogenicity		

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide (TiO2)	-	2B	-
Carbon black	-	2B	-
Silica	-	3	-
Quartz (SiO2)	-	1	Known to be a human carcinogen.

Reproductive toxicity

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 10 of 17 Print Date 08/12/2023

Conclusion/Summary	:	Mixture.Not fully	tested.	
Teratogenicity				
Conclusion/Summary	:	Mixture.Not fully	tested.	
Specific target organ toxicity (single Not available.	e expo	osure)		
Specific target organ toxicity (repe	ated e	exposure)		
Name	Cate	egory	Route of exposure	Target organs
Quartz (SiO2)	Cate	gory 1	-	-
Aspiration hazard Not available.				
Information on the likely routes of exposure	:	Not available.		
Potential acute health effects				
Eye contact	:		cant effects or critical ha	
Inhalation Skin contact	:		cant effects or critical ha	
Skin contact Ingestion	:		ant effects or critical ha	
ingestion	•	i to known signifie	and effects of efficient he	izur ub.
Symptoms related to the physical,	chemi	cal and toxicologica	al characteristics	
Eye contact	:	No specific data.		
Inhalation	:	No specific data.		
Skin contact		No specific data.		
Ingestion	:	No specific data.		
Delayed and immediate effects and	also c	chronic effects from	n short and long term	exposure_
Short term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Long term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 11 of 17 Print Date 08/12/2023

Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	Not available.
Developmental effects	:	Not available.
Fertility effects	:	No known significant effects or critical hazards.
Numerical measures of toxicity		
<u>Acute toxicity estimates</u> N/A		
Other information	:	This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	
Titanium oxide (TiO2)				
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h	
	Marine water			
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h	
		dubia		
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h	
	water			
Carbon black				
	Acute EC50 37.563 Mg/l Fresh	Daphnia - Daphnia magna	48 h	
	water			
UV CHARCOAL PVC V2				
Remarks - Acute - Aquatic invertebrates.:	Chemicals are not readily available as they are bound within the polymer matrix.			
Conclusion/Summary	: Chemicals are not readily available as they are bound within the polymer matrix.			

Persistence and degradability

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 12 of 17
Print Date 08/12/2023

Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			
Phenol, 2-(2H-benzotriazol-2-yl)-4-	4.2	-	high
methyl-			

<u>Mobility in soil</u>

Soil/water partition coefficient (KOC)	:	Not available.
Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

12/17

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 13 of 17 Print Date 08/12/2023

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	:	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Listed 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich
		United States - TSCA 4(a) - ITC Priority list: Not listed
		United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not listed
		United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		United States - TSCA 6 - Final risk management: Not listed
		United States - TSCA 6 - Proposed risk management: Not listed
		United States - TSCA 8(a) - Chemical risk rules: Not listed
		United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
		United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
		United States - TSCA 8(a) - Preliminary assessment report
		(PAIR): Not listed
		United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
		United States - TSCA 8(d) - Health and safety studies: Not listed
		United States - EPA Clean water act (CWA) section 307 - Priority
		pollutants: Listed Zinc ferrite brown spinel (C.I. Pigment
		Yellow 119)
		Zinc dilaurate
		Phenol
		Nickel
		Chromium
		Arsenic

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



Page 14 of 17 Print Date 08/12/2023

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II		Not listed
Substances	•	i tot listed
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		Not listed
DEA List II Chemicals (Essential Chemicals)	•	Not listed
Chemiculy,		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

Not applicable.

:

Composition/information on ingredients

No products were found.

Name	%	Classification
1,2-Benzenedicarboxylic	>= 10 - <= 25	EYE IRRITATION - Category 2B
acid, di-C8-10-branched		
alkyl esters, C9-rich		
Titanium oxide (TiO2)	>= 10 - <= 25	CARCINOGENICITY - Category 2
Phenol, 2-(2H-benzotriazol-	>= 10 - <= 25	EYE IRRITATION - Category 2B
2-yl)-4-methyl-		
Carbon black	>= 3 - <= 5	CARCINOGENICITY - Category 2
Silica	>= 1 - <= 3	EYE IRRITATION - Category 2B
Quartz (SiO2)	> 0 - <= 0.3	CARCINOGENICITY - inhalation - Category 1A

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023

ÀVIENT

Page 15 of 17 Print Date 08/12/2023

	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

<u>SARA 313</u>

Form R - Reporting requirements

Product name	CAS number	%
Zinc ferrite brown spinel (C.I. Pigment Yellow 119)	68187-51-9	>= 1 - < 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

<u>State regulations</u> Massachusetts	:	The following components are listed: Titanium dioxide Calcium carbonate Carbon black
New York New Jersey	:	Silica, amorphous None of the components are listed. The following components are listed:
	•	Titanium dioxide Ethene, chloro-, homopolymer Calcium carbonate Zinc ferrite brown spinel (C.I. Pigment Yellow 119) Carbon black Quartz
Pennsylvania	:	The following components are listed: Titanium dioxide Calcium carbonate
		Zinc ferrite brown spinel (C.I. Pigment Yellow 119)
		Carbon black
		Silica, amorphous

California Prop. 65

WARNING: This product can expose you to chemicals including 1,2-Benzenedicarboxylic acid, di-C8-10branched alkyl esters, C9-rich, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023



	Page 16 of 17	
Print	Date 08/12/2023	

Ingredient name	No significant risk level	Maximum acceptable dosage level
1,2-Benzenedicarboxylic acid, di-C8-10-	Yes.	-
branched alkyl esters, C9-rich		
Titanium dioxide	-	-
Carbon black	-	-
Quartz	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations Inventory list		
Australia	:	Not determined.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	Not determined.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined.
_		Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark

ÄVIENT

UV CHARCOAL PVC V2

Version Number 1.0 Revision Date 08/11/2023 Page 17 of 17 Print Date 08/12/2023

and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>IIIStol y</u>		
Date of printing	:	08/12/2023
Date of issue/Date of revision	:	08/11/2023
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.