PolvOne.

### MATERIAL SAFETY DATA SHEET LC 386-154

Version Number 1.2 Revision Date 12/26/2012

Product Use

Page 1 of 7 Print Date 12/26/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LC 386-154
Product code	:	EM01046070
Chemical Name	:	Mixture
CAS-No.	:	Mixture

## : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Talc	14807-96-6	0.1 - 1
Kaolin	1332-58-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

#### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.



# MATERIAL SAFETY DATA SHEET *LC 386-154*

Version Number 1.2 Revision Date 12/26/2012 Page 2 of 7 Print Date 12/26/2012

Medical Conditions Aggravated by Exposure:	None known.	
	4. FIRST AID MEASURES	
Inhalation		idental inhalation of fumes from hen symptoms persist or in all cases of
Ingestion	Do not induce vomiting withou persist or in all cases of doubt s	t medical advice. When symptoms eek medical advice.
Eyes		of water, also under the eyelids, for at on persists, seek medical attention.
Skin	Wash off with soap and plenty seek medical attention.	of water. If skin irritation persists
	5. FIREFIGHTING MEASUR	ES
Flash point	not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	pressure mode should be worn to contaminants.	ng apparatus (SCBA) used in positive to prevent inhalation of airborne monoxide (CO), oxides of nitrogen
	CCIDENTAL RELEASE MEA	SURES
Personal precautions	Wear appropriate personal prote impervious gloves, boots and co	
Environmental precautions	Should not be released into the be allowed to enter drains, wate	environment. The product should not er courses or the soil.
Methods for cleaning up	Clean up promptly by sweeping plastic, cardboard or metal cont	g or vacuum. Package all material in tainers for disposal.
	7. HANDLING AND STORA	GE
Handling	Take measures to prevent the bionly in areas with appropriate e	uild up of electrostatic charge. Heat exhaust ventilation.



## MATERIAL SAFETY DATA SHEET *LC 386-154*

Version Number	er 1.2
Revision Date	12/26/2012

Storage

Page 3 of 7 Print Date 12/26/2012

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	No personal respiratory protective equipment	nt normally required.
Eye/Face Protection	Safety glasses with side-shields	
Hand protection	Protective gloves	
Skin and body protection	Long sleeved clothing	
Additional Protective Measures	Safety shoes	
General Hygiene Considerations	Handle in accordance with good industrial h practice. Wash hands before breaks and at t	
Engineering measures	Heat only in areas with appropriate exhaust appropriate exhaust ventilation at machiner	
Europeuro limit(a)		

Exposure limit(s)

PolyOne

### MATERIAL SAFETY DATA SHEET LC 386-154

Version Number 1.2 Revision Date 12/26/2012 Page 4 of 7 Print Date 12/26/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
	20 mg/m3	(TWA): Short Term Exposure Limit (STEL):		MX OEL
Kaolin	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	2 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	2 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

#### : Not determined : not applicable : insoluble

: solid

: very faint

:

:

pellets, Slabs

NOT APPLICABLE

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

: Not applicable Not determined Not established : : not applicable

:

: not applicable

: not applicable

#### **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

## MATERIAL SAFETY DATA SHEET *LC 386-154*

#### Version Number 1.2 Revision Date 12/26/2012

Page 5 of 7 Print Date 12/26/2012

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.
1332-58-7	Kaolin	Systemic effects	Respiratory system, digestive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1332-58-7	Kaolin	Oral LD50	5,000 mg/kg	rat
		Dermal LD50	5,000 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14807-96-6	Talc	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### 12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.



# MATERIAL SAFETY DATA SHEET *LC 386-154*

Version Number 1.2 Revision Date 12/26/2012 Page 6 of 7 Print Date 12/26/2012

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : Not applicable
SARA Title III Section 302 l	Extremely Hazardous Substance
	e identified under this section, this product is Not Applicable under this regula

PolyOne.

## MATERIAL SAFETY DATA SHEET *LC 386-154*

ersion Number 1.2		Page 7 of
evision Date 12/26/2012		Print Date 12/26/2012
SARA Title III Section 313 To	xic Chemicals:	
Unless specific chemicals are id	lentified under this section, this produc	ct is Not Applicable under this regulation
Canadian Regulations:		
National Pollutant Relea	se Inventory (NPRI)	
not applicable		
WHMIS Classification	: D2A	
DSL	: DSL status has not been determine restricted by regulations.	ined. Quantity use in Canada may be
National Inventories:		
Australia AICS	: Not determined	
China IECS	: Not determined	
Europe EINECS	: Listed	
Japan ENCS	: Not determined	
Korea KECI	: Not determined	
Philippines PICCS	: Not determined	
	16. OTHER INFORMATION	1

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.