

MATERIAL SAFETY DATA SHEET

# GF 1200 A 15 FR BLACK 42

Version Number 1.0 Revision Date 12/22/2001 Page 1 of 7 Print Date 11/2/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GF 1200 A 15 FR BLACK 42
Product code	:	EM0C904315
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Antimony trioxide	1309-64-4	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# GF 1200 A 15 FR BLACK 42

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit	: Not applicable
Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET

# GF 1200 A 15 FR BLACK 42

Version Number 1.0 Revision Date 12/22/2001 Page 3 of 7 Print Date 11/2/2011

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.		
8. EXPOS	SUF	RE CONTROLS / PERSONAL PROTECTION		
Respiratory protection	:	No personal respiratory protective equipment normally required.		
Eye/Face Protection	:	Safety glasses with side-shields.		
Hand protection	:	Protective gloves.		
Skin and body protection	:	Long sleeved clothing.		
Additional Protective Measures	:	Safety shoes.		
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
	-		black	

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>Solid</li> <li>Pellets, slabs</li> <li>BLACK</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul>	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	<ul> <li>Not applicable.</li> <li>Not determined</li> <li>Not established</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>		
10. STABILITY AND REACTIVITY					
Stability	: Stable.				
Hazardous Polymerization	: Will not occur.				
			lame. To avoid thermal		



### MATERIAL SAFETY DATA SHEET

# GF 1200 A 15 FR BLACK 42

Version Number 1.0 Revision Date 12/22/2001 Page 4 of 7 Print Date 11/2/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

decomposition, do not overheat.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

# GF 1200 A 15 FR BLACK 42

Version Number 1.0 Revision Date 12/22/2001 Page 5 of 7 Print Date 11/2/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Persistence and degradability	: Not readily biodegradable.		
Environmental Toxicity	Chemicals are not readily available as they are bound within the mate of the polymer.		
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the ma of the polymer.		
Additional advice	: Not applicable		
	13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastics the product can be recycled. Where possibl recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.		
ICAO/IATA	: Not regulated for transportation.		
IMO / IMDG	: Not regulated for transportation.		



MATERIAL SAFETY DATA SHEET

# GF 1200 A 15 FR BLACK 42

Version Number 1.0 Revision Date 12/22/2001 Page 6 of 7 Print Date 11/2/2011

	15. REGULATO	ORY INFORMATIO	N	
US Regulations:				
OSHA Status	: Classified as	hazardous based on co	omponents.	
TSCA Status	: All component exempt.	All components of this product are listed on the TSCA inventory or are exempt.		
US. EPA CERCLA Hazardou	s Substances (40 CF	TR 302)		
	CAS-No. /440-38-2	•		
California Proposition 65		WARNING! This product contains a chemical known in the State of California to cause cancer.		
SARA Title III Section 313 T	oxic Chemicals:			
Chemical Nam	e	CAS-No.	Weight %	
	COMPOUNDS	1309-64-4	4.37	
CAS-No. 128-37-0 1309-64-4				
7440-38-2 1333-86-4 7440-50-8 57-11-4				
7440-38-2 1333-86-4 7440-50-8 57-11-4 DSL	: Listed.			
7440-38-2 1333-86-4 7440-50-8 57-11-4 DSL National Inventories:		ed		
7440-38-2 1333-86-4 7440-50-8 57-11-4 DSL National Inventories: Australia AICS	: Not determin			
7440-38-2 1333-86-4 7440-50-8 57-11-4 DSL National Inventories: Australia AICS China IECS	: Not determin : Not determin	ed.		
7440-38-2 1333-86-4 7440-50-8 57-11-4 DSL National Inventories: Australia AICS China IECS Europe EINECS	<ul><li>Not determin</li><li>Not determin</li><li>Not determin</li></ul>	ed.		
7440-38-2 1333-86-4 7440-50-8 57-11-4 DSL National Inventories: Australia AICS China IECS	: Not determin : Not determin	ed. ed. ed.		



Page 7 of 7

Print Date 11/2/2011

### MATERIAL SAFETY DATA SHEET

# GF 1200 A 15 FR BLACK 42

Version Number 1.0 Revision Date 12/22/2001

Philippines PICCS

: Not determined.

# **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.