## MATERIAL SAFETY DATA SHEET XL-2175 NATURAL

Version Number 1.7 Revision Date 04/11/2012 Page 1 of 7 Print Date 8/25/2012

POLYONE CORPORATI 33587 Walker Road, Avor		OH 44012
Felephone E <b>mergency telephone</b>	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	XL-2175 NATURAL
Product code	:	EM10000023
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

# ComponentsCAS-No.Weight percentQuartz14808-60-70.1 - 1

components	CHD 110.	weight percent
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET **XL-2175 NATURAL**

Version Number 1.7 Revision Date 04/11/2012 Page 2 of 7 Print Date 8/25/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen</li> </ul>
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

PolyOne

# MATERIAL SAFETY DATA SHEET **XL-2175 NATURAL**

Version Number 1.7 Revision Date 04/11/2012 Page 3 of 7 Print Date 8/25/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Quartz	0.025 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	0.05 mg/m3	Recommended exposure limit (REL):	Respirable dust.	NIOSH
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
	0.1 mg/m3	Time Weighted Average (TWA):		MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : solid: pellets, Slabs

Evaporation rate Specific Gravity Not applicableNot determined

## MATERIAL SAFETY DATA SHEET XL-2175 NATURAL

Version Number 1.7 Revision Date 04/11/2012

Colour

Odour Melting point/range Boiling Point: Water solubility	: :	Not determined not applicable	Vapour pressure Vapour density pH	:	not applicable not applicable not applicable
		10. STABILITY AND R	REACTIVITY		
Stability		: Stable			
Hazardous Polymerization		: Will not occur.			
Conditions to avoid		: To avoid thermal deco	omposition, do not over	heat.	
Incompatible Materials		: Strong acids, oxidizin	g and reducing agents		
	Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization Conditions to avoid	Melting point/range : Boiling Point: : Water solubility : Stability Hazardous Polymerization Conditions to avoid	Melting point/range       : Not determined         Boiling Point:       : not applicable         Water solubility       : insoluble         Image:	Melting point/range       : Not determined       Vapour density         Boiling Point:       : not applicable       pH         Water solubility       : insoluble       Image: Construction of the second	Melting point/range       : Not determined       Vapour density       :         Boiling Point:       : not applicable       pH       :         Water solubility       : insoluble       :       :         Io. STABILITY AND REACTIVITY       :       :       :         Stability       :       :       Stable         Hazardous Polymerization       :       Will not occur.       :         Conditions to avoid       :       To avoid thermal decomposition, do not overheat.

Bulk density

: NO PIGMENT

# Hazardous decomposition<br/>products: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen<br/>(NOx), other hazardous materials, and smoke are all possible.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Page 4 of 7

: Not established

Print Date 8/25/2012

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET **XL-2175 NATURAL**

Version Number 1.7 Revision Date 04/11/2012 Page 5 of 7 Print Date 8/25/2012

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	

PolyOne

# MATERIAL SAFETY DATA SHEET XL-2175 NATURAL

Version Number 1.7 Revision Date 04/11/2012 Page 6 of 7 Print Date 8/25/2012

California Proposition 65	:	Not applicable					
SARA Title III Section 302 Extremely Hazardous Substance							
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation							
SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation							
Canadian Regulations:							
National Pollutant Releas	se Iı	nventory (NPRI)					
not applicable							
WHMIS Classification	:	D2A					
DSL	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.					
National Inventories:							
Australia AICS	:	Not determined					
China IECS	:	Not determined					
Europe EINECS	:	Listed					
Japan ENCS	:	Not determined					
Korea KECI	:	Not determined					
Philippines PICCS	:	Not determined					
		16. OTHER INFORMATION	+				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

PolyOne.

# MATERIAL SAFETY DATA SHEET XL-2175 NATURAL

Version Number 1.7 Revision Date 04/11/2012 Page 7 of 7 Print Date 8/25/2012