

MATERIAL SAFETY DATA SHEET

# IT702 BLUE 6264

Version Number 1.0 Revision Date 03/07/2002 Page 1 of 6 Print Date 11/3/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	IT702 BLUE 6264
Product code	:	EM10000193
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Black 30	71631-15-7	0.1 - 1
C.I. Pigment Blue 28	1345-16-0	0.1 - 1
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	30 - 60

# **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

# POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



# MATERIAL SAFETY DATA SHEET

# IT702 BLUE 6264

Medical Conditions	: None known.
Aggravated by Exposure:	. INDIE KIIOWII.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
Hazards	. 1010
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

# MATERIAL SAFETY DATA SHEET

# IT702 BLUE 6264



Version Number 1.0 Revision Date 03/07/2002		Page 3 of 6 Print Date 11/3/2011			
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXP	8. EXPOSURE CONTROLS / PERSONAL PROTECTION				
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields.			
Hand protection	:	Protective gloves.			
Skin and body protection	:	Long sleeved clothing.			
Additional Protective Measures	:	Safety shoes.			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Black 30	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.2 mg/m3	Time Weighted Average (TWA):	as Ni	ACGIH
	1 mg/m3	PEL:	as Ni	OSHA Z1
C.I. Pigment Blue 28	0.02 mg/m3	Time Weighted Average (TWA):	as Co	ACGIH
	0.10 mg/m3	PEL:	Total dust. as Co	OSHA Z1
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Quartz	0.05 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH
	0.1 mg/m3	PEL:	Respirable dust.	OSHA
	0.3 mg/m3	PEL:	Total dust.	OSHA

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance SolidPellets, slabs

Evaporation rate Specific Gravity

Not applicable.Not determined



#### MATERIAL SAFETY DATA SHEET

# IT702 BLUE 6264

Version Number 1.0 Revision Date 03/07/2002		Page 4 of 6 Print Date <i>11/3/2011</i>
Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>BLUE Bulk density</li> <li>Very faint Vapor pressure</li> <li>Not determined Vapor density</li> <li>Not applicable pH</li> <li>Insoluble</li> </ul>	11
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open fl decomposition, do not overheat.	ame. To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxidizing	agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO (NOx), other hazardous materials, and smoke	, ·

# 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
71631-15-7	C.I. Pigment Black 30	Irritant	Eyes, Skin.
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
71631-15-7	C.I. Pigment Black 30	no	no	2
1345-16-0	C.I. Pigment Blue 28	no	2B	no
14808-60-7	Quartz	no	1	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.



MATERIAL SAFETY DATA SHEET

# IT702 BLUE 6264

Version Number 1.0 Revision Date 03/07/2002 Page 5 of 6 Print Date 11/3/2011

2 - The component is reasonably anticipated to be a human carcinogen.

# Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. Not applicable DISPOSAL CONSIDERATIONS Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, ransportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Chemicals are not readily available as they are bound within the matrix of the polymer. Not applicable DISPOSAL CONSIDERATIONS Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material
of the polymer. Not applicable <b>DISPOSAL CONSIDERATIONS</b> Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material
DISPOSAL CONSIDERATIONS Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, ransportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material
Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material
recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, ransportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material
and disposal in accordance with applicable federal, state/provincial and local regulations.
TRANSPORT INFORMATION
Not regulated for transportation.
Not regulated for transportation.
Not regulated for transportation.
REGULATORY INFORMATION
Classified as hazardous based on components.
All components of this product are listed on the TSCA inventory or are exempt.



#### MATERIAL SAFETY DATA SHEET

# IT702 BLUE 6264

Version Number 1.0 Revision Date 03/07/2002 Page 6 of 6 Print Date 11/3/2011

California Proposition : 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDS	71631-15-7	0.14
NICKEL COMPOUNDS		
COBALT COMPOUNDS	1345-16-0	0.78
COBALT COMPOUNDS	68187-11-1	0.03
CHROMIUM III COMPOUNDS		

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
71631-15-7	
68187-11-1	
123-28-4	
14808-60-7	

DSL

: Listed.

National Inventories:

Australia AICS	: Not determined.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Not determined.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.