

MATERIAL SAFETY DATA SHEET

RT 5145D YELLOW 6397

Version Number 1.0 Revision Date 02/17/2002 Page 1 of 6 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RT 5145D YELLOW 6397
Product code	:	EM10000292
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Decabromodiphenyl oxide	1163-19-5	10 - 30
Antimony trioxide	1309-64-4	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

RT 5145D YELLOW 6397

Version Number 1.0 Revision Date 02/17/2002 Page 2 of 6 Print Date 11/3/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	: :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

RT 5145D YELLOW 6397

NL 1 0 Versio . Revisi

ersion Number 1.0 evision Date 02/17/2002				Print	Page 3 of 6 Date 11/3/2011
	ar	nd contamination.	Keep in a d	ry, cool place.	
8.	EXPOSURE	CONTROLS / PI	ERSONAL	PROTECTION	
Respiratory protection	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: Sa	: Safety glasses with side-shields.			
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothi	ng.		
Additional Protective Measures	: Sa	afety shoes.			
General Hygiene Considerations					afety practice.
Engineering measures	Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				Provide
Exposure limit(s)					
Components	Value	Exposure	time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:		as Sb	OSHA Z1
	9. PHYSIC	CAL AND CHEM	IICAL PRO	PERTIES	
Form:SolidEvaporation rate:Not applicableAppearance:Pellets, slabsSpecific Gravity:Not determineColor:YELLOWBulk density:Not establishedOdor:Very faintVapor pressure:Not applicableMelting point/range:Not determinedVapor density:Not applicableBoiling Point:::Not applicablepH:Not applicableWater solubility:Insoluble:Not applicableinsoluble		determined established applicable applicable			
	10. S	TABILITY AND	REACTIV	TTY	
Stability	: Si	able.			
Hazardous Polymerizatio	Hazardous Polymerization : Will not occur.				
Conditions to avoid	Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.				
Incompatible Materials	: In	compatible with s	trong acids a	and oxidizing agents.	
Hazardous decomposition products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.					



MATERIAL SAFETY DATA SHEET

RT 5145D YELLOW 6397

Version Number 1.0

Page 4 of 6 Print Date 11/3/2011

Revision Date 02/17/2002

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1163-19-5	Decabromodiphenyl oxide	Systemic effects	Liver, Kidney.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1163-19-5	Decabromodiphenyl oxide	Oral LD50	> 5 gm/kg	rat
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Decabromodiphenyl oxide 1163-19-5 A halogenated aromatic with some potential for hazardous exposure via inhalation or ingestion. Acute toxicity is low - oral LD50 in rats >50 mg/L. Animal studies at high feeding levels indicate some potential for liver effects form chronic overexposure.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET

RT 5145D YELLOW 6397

ion Number 1.0 sion Date 02/17/2002	Pag Print Date <i>11,</i>	
Environmental Toxicity	: Chemicals are not readily available as they are bound within the most of the polymer.	atrix
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the most fit polymer.	atriz
Additional advice	: Not applicable	
	13. DISPOSAL CONSIDERATIONS	
Product	: Like most thermoplastics the product can be recycled. Where post recycling is preferred to disposal or incineration. The generator o waste material has the responsibility for proper waste classification transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	of on,
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mat has the responsibility for proper waste classification, transportatio and disposal in accordance with applicable federal, state/provincia and local regulations.	n
	14. TRANSPORT INFORMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.	
ICAO/IATA	: Not regulated for transportation.	
IMO / IMDG	: Not regulated for transportation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on the TSCA inventory o exempt.	r are
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)	
	CAS-No.RQ for Mixture/Product1309-64-413,454 LB	
California Proposition 65	: WARNING! This product contains a chemical known in the State California to cause cancer.	e of
SARA Title III Section 313 T	oxic Chemicals:	



MATERIAL SAFETY DATA SHEET

RT 5145D YELLOW 6397

Version Number 1.0 Revision Date 02/17/2002 Page 6 of 6 Print Date 11/3/2011

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	7.43
DECABROMODIPHENYL OXIDE	1163-19-5	22.29

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1309-64-4
123-28-4

DSL

: Listed.

National Inventories:

Australia AICS	: Not determined.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
Philippines PICCS	: Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.