

MATERIAL SAFETY DATA SHEET

# DP 6474-1000

Version Number 1.0 Revision Date 12/17/2001 Page 1 of 6 Print Date 11/2/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DP 6474-1000
Product code	:	EM10000356
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Decabromodiphenyl oxide	1163-19-5	10 - 30
Antimony trioxide	1309-64-4	1 - 5

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





ion Number 1.0	Page
sion Date 12/17/2001	Print Date 11/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> </ul>
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

# MATERIAL SAFETY DATA SHEET





sion Number 1.0 sion Date 12/17/2001					Print	Page 3 Date 11/2/2
Storage		Leep containers dry an nd contamination. Ke			oisture	absorption
8. E	XPOSURE	CONTROLS / PERS	SONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory	v protecti	ve equipment nor	nally 1	required.
Eye/Face Protection	: S	afety glasses with side	e-shields			
Hand protection	: P	: Protective gloves.				
Skin and body protection	: L	: Long sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		Iandle in accordance v Vash hands before bre				afety practice
Engineering measures		Ieat only in areas with ppropriate exhaust ver			ation.	Provide
Exposure limit(s) Components	Value	Exposure time	e	Exposure typ	)e	List:
Antimony trioxide	0.5 mg/m3	PEL:		as Sb		OSHA Z1
	9. PHYSI	CAL AND CHEMIC	AL PRC	PERTIES		
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: TAN : Very : Not	ets, slabs V faint determined applicable	Specifi Bulk d Vapor	pressure : density :	Not Not Not Not	applicable. determined established applicable applicable applicable
	10. 8	STABILITY AND R	EACTIV	<b>YITY</b>		
Stability	: S	table.				
Stability Hazardous Polymerizatior		table. Vill not occur.				
	n : V : K				. То а	void thermal



### MATERIAL SAFETY DATA SHEET

# DP 6474-1000

# Version Number 1.0

Revision Date 12/17/2001

Page 4 of 6 Print Date 11/2/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1163-19-5	Decabromodiphenyl oxide	Oral LD50	> 5 gm/kg	rat
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Decabromodiphenyl oxide 1163-19-5 A halogenated aromatic with some potential for hazardous exposure via inhalation or ingestion. Acute toxicity is low - oral LD50 in rats >50 mg/L. Animal studies at high feeding levels indicate some potential for liver effects form chronic overexposure.

## Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

## **12. ECOLOGICAL INFORMATION**



# MATERIAL SAFETY DATA SHEET

Page 5 of Print Date 11/2/20 eadily biodegradable. dicals are not readily available as they are bound within the matrix polymer. dicals are not readily available as they are bound within the matrix polymer. pplicable POSAL CONSIDERATIONS most thermoplastics the product can be recycled. Where possible ling is preferred to disposal or incineration. The generator of material has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, provincial and local regulations. cling is preferred when possible. The generator of waste material the responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial actional disposal in accordance with applicable federal, state/provincial and local regulations.
aicals are not readily available as they are bound within the matrix polymer. aicals are not readily available as they are bound within the matrix polymer. pplicable <b>POSAL CONSIDERATIONS</b> most thermoplastics the product can be recycled. Where possible ling is preferred to disposal or incineration. The generator of material has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, provincial and local regulations. cling is preferred when possible. The generator of waste material heresponsibility for proper waste classification, transportation is posal in accordance with applicable federal, provincial and local regulations.
polymer. icals are not readily available as they are bound within the matrix polymer. pplicable <b>POSAL CONSIDERATIONS</b> most thermoplastics the product can be recycled. Where possible ling is preferred to disposal or incineration. The generator of material has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, provincial and local regulations. cling is preferred when possible. The generator of waste material he responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial be responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial be responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial be responsibility for proper waste classification, transportation provincial and local regulations.
polymer. pplicable POSAL CONSIDERATIONS most thermoplastics the product can be recycled. Where possible ling is preferred to disposal or incineration. The generator of material has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, provincial and local regulations. cling is preferred when possible. The generator of waste material he responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial ocal regulations.
POSAL CONSIDERATIONS most thermoplastics the product can be recycled. Where possible ling is preferred to disposal or incineration. The generator of material has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, provincial and local regulations. Cling is preferred when possible. The generator of waste material he responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial ocal regulations.
most thermoplastics the product can be recycled. Where possible ling is preferred to disposal or incineration. The generator of material has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, provincial and local regulations. cling is preferred when possible. The generator of waste material he responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial ocal regulations.
ling is preferred to disposal or incineration. The generator of material has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, provincial and local regulations. cling is preferred when possible. The generator of waste material he responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial ocal regulations.
e responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial ocal regulations.
ANSPORT INFORMATION
egulated for transportation.
egulated for transportation.
egulated for transportation.
ULATORY INFORMATION
ified as hazardous based on components.
omponents of this product are listed on the TSCA inventory or are pt.
(40 CFR 302)
RQ for Mixture/Product
36,364 LB



MATERIAL SAFETY DATA SHEET

# DP 6474-1000

Version Number 1.0 Revision Date 12/17/2001

### Page 6 of 6 Print Date 11/2/2011

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	2.75
DECABROMODIPHENYL OXIDE	1163-19-5	22.00

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
11097-59-9	
1309-64-4	

DSL

: Listed.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.

# **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.