

MATERIAL SAFETY DATA SHEET

IT481 NATURAL

Version Number 1.0 Revision Date 02/15/2002 Page 1 of 6 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	IT481 NATURAL
Product code	:	EM10000417
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

IT481 NATURAL

ion Number 1.0 sion Date 02/15/2002	Page 2 Print Date 11/3/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

IT481 NATURAL

sion Date 02/15/2002			Print	Page 3 Date 11/3/2		
	a	nd contamination. Keep in a d	ry, cool place.			
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection : No personal respiratory protective equipment normally required.						
Eye/Face Protection	: S	afety glasses with side-shields.				
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and a		afety practice		
Engineering measures		eat only in areas with appropri ppropriate exhaust ventilation a		Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH		
	5 mg/m3	PEL:	Respirable dust.	OSHA Z1		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		
0 /	0.05	Time Weighted Average	Respirable dust.	ACGIH		
Quartz	mg/m3	(TWA):				
Quartz	mg/m3 0.1 mg/m3	(TWA): PEL:	Respirable dust.	OSHA		
Quartz			Respirable dust. Total dust.	OSHA OSHA		
Quartz	0.1 mg/m3 0.3 mg/m3	PEL:	Total dust.			
	0.1 mg/m3 0.3 mg/m3 9. PHYSIC	PEL: PEL: CAL AND CHEMICAL PRO	Total dust. PERTIES	OSHA		
Form	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solic	PEL: PEL: CAL AND CHEMICAL PRO	Total dust. PERTIES ration rate : Not	OSHA		
Form Appearance	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solic : Pelle	PEL: PEL: CAL AND CHEMICAL PRO I Evapor ts, slabs Specifi	Total dust. PERTIES ration rate : Not ic Gravity : Not	OSHA applicable. determined		
Form Appearance Color	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solic : Pelle : NO I	PEL: PEL: CAL AND CHEMICAL PRO I Evapor Is, slabs Specifi PIGMENT Bulk d	Total dust. PERTIES ration rate : Not c Gravity : Not ensity : Not	oSHA applicable. determined established		
Form Appearance Color Odor	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solic : Pelle : NO I : Very	PEL: PEL: CAL AND CHEMICAL PRO ts, slabs Specifi PIGMENT Bulk d faint Vapor	Total dust. OPERTIES ration rate:ration rate:Notc Gravity:Notensity:Notpressure:Not	applicable. determined established applicable		
Form Appearance Color Odor Melting point/range	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solid : Pelle : NO I : Very : Not o	PEL: PEL: CAL AND CHEMICAL PRO I Evapor ts, slabs Specifi PIGMENT Bulk d faint Vapor determined Vapor	Total dust. OPERTIES ration rate : Not ac Gravity : Not ensity : Not pressure : Not density : Not	OSHA applicable. determined established applicable applicable		
Form Appearance Color Odor Melting point/range Boiling Point:	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solid : Pelle : NO I : Very : Not o	PEL: PEL: CAL AND CHEMICAL PRO I Evapor ts, slabs Specific PIGMENT Bulk d faint Vapor determined Vapor applicable pH	Total dust. OPERTIES ration rate : Not ac Gravity : Not ensity : Not pressure : Not density : Not	applicable. determined established applicable		
Form Appearance Color Odor Melting point/range Boiling Point:	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solid : Pelle : NO I : Very : Not a : Insol	PEL: PEL: CAL AND CHEMICAL PRO I Evapor ts, slabs Specific PIGMENT Bulk d faint Vapor determined Vapor applicable pH	Total dust. OPERTIES ration rate : Not c Gravity : Not ensity : Not density : Not : Not	OSHA applicable. determined established applicable applicable		
Quartz Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	0.1 mg/m3 0.3 mg/m3 9. PHYSIC : Solid : Pelle : NO I : Very : Not d : Insol 10. S	PEL: PEL: CAL AND CHEMICAL PRO I Evapor ts, slabs Specifi PIGMENT Bulk d faint Vapor determined Vapor applicable pH	Total dust. OPERTIES ration rate : Not c Gravity : Not ensity : Not density : Not : Not	OSHA applicable. determined established applicable applicable		



MATERIAL SAFETY DATA SHEET

IT481 NATURAL

Version Number 1.0 Revision Date 02/15/2002		Page 4 of 6 Print Date <i>11/3/2011</i>
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.

MATERIAL SAFETY DATA SHEET





ersion Number 1.0 evision Date 02/15/2002		Page 5 of Print Date <i>11/3/</i> 201	
Additional advice	:	Not applicable	
	1	3. DISPOSAL CONSIDERATIONS	
Product	:	Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	1	4. TRANSPORT INFORMATION	[
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	:	Not regulated for transportation.	
ICAO/IATA	:	Not regulated for transportation.	
IMO / IMDG	:	Not regulated for transportation.	
	15	. REGULATORY INFORMATION	
US Regulations:			
OSHA Status	:	Classified as hazardous based on components.	
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.	
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.	
Canadian Regulations:			
WHMIS Classification	:	D2A	
WHMIS Ingredient Disc	losu	re List	
CAS-No. 14808-60-7			
DSL	:	Listed.	
National Inventories:			



MATERIAL SAFETY DATA SHEET

IT481 NATURAL

Version Number 1.0 Revision Date 02/15/2002			Page 6 of 6 Print Date <i>11/3/2011</i>
Australia AICS	:	Not determined.	
China IECS	:	Not determined.	
Europe EINECS	:	Not determined.	
Japan ENCS	:	Not determined.	
Korea KECI	:	Not determined.	
Philippines PICCS	:	Not determined.	
		16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.