PolvOne

MATERIAL SAFETY DATA SHEET **PP FR 8-6 NAT-20**

Version Number 1.1 Revision Date 04/14/2008

Page 1 of 7 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	PP FR 8-6 NAT-20
Product code :	EM10001012
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Decabromodiphenyl oxide	1163-19-5	10 - 30
Quartz	14808-60-7	0.1 - 1
Antimony trioxide	1309-64-4	5 - 10
Talc	14807-96-6	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **PP FR 8-6 NAT-20**

Version Number 1.1 Revision Date 04/14/2008 Page 2 of 7 Print Date 1/3/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET **PP FR 8-6 NAT-20**

Version Number 1.1 Revision Date 04/14/2008 Page 3 of 7 Print Date 1/3/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	Time Weighted Average	as Sb	MX OEL
		(TWA):		
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Quartz	0.025	Time Weighted Average	Respirable fraction.	ACGIH
	mg/m3	(TWA):		
	0.1 mg/m3	Time Weighted Average	Respirable.	Z3
		(TWA):		
	0.3 mg/m3	Time Weighted Average	Total dust.	Z3
		(TWA):		
	0.1 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
Talc	2 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
	0.1 mg/m3	Time Weighted Average	Respirable.	Z3
		(TWA):		
	0.3 mg/m3	Time Weighted Average	Total dust.	Z3
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid

Evaporation rate

: Not applicable

MATERIAL SAFETY DATA SHEET **PP FR 8-6 NAT-20**

: pellets, Slabs

: Very faint

: Insoluble

:

·

: NO PIGMENT

: Not determined

: Not applicable

Stable.

Will not occur.

Version Number 1.1 Revision Date 04/14/2008

Revision	Date	04/14/2008

Appearance Color Odour Melting point/range Boiling Point: Water solubility

-	
Hazardous Polymerization	

Stability

Conditions to avoid : Incompatible Materials :

Hazardous decomposition
products: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.

To avoid thermal decomposition, do not overheat.

Strong acids, oxidizing and reducing agents

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1163-19-5	Decabromodiphenyl oxide	Systemic effects	Liver, Kidney.
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1163-19-5	Decabromodiphenyl oxide	Oral LD50	> 5 gm/kg	rat
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	no
1309-64-4	Antimony trioxide	no	2B	no

·

:

Page 4 of 7 Print Date 1/3/2012

Not determined

Not established

: Not applicable

: Not applicable

: Not applicable

Specific Gravity Bulk density Vapour pressure Vapour density pH

MATERIAL SAFETY DATA SHEET **PP FR 8-6 NAT-20**

Version Number 1.1 Revision Date 04/14/2008

Page 5 of 7 Print Date 1/3/2012

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Decabromodiphenyl oxide 1163-19-5 A halogenated aromatic with some potential for hazardous exposure via inhalation or ingestion. Acute toxicity is low - oral LD50 in rats >50 mg/L. Studies on rats at high feeding levels indicate some potential for liver and kidney effects from chronic overexposure as well as thyroid toxicity.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

PolyOne.

MATERIAL SAFETY DATA SHEET **PP FR 8-6 NAT-20**

Version Number 1.1 Revision Date 04/14/2008 Page 6 of 7 Print Date 1/3/2012

.S. DOT Classification CAO/IATA (air) MO / IMDG (maritime) S Regulations:	 Not regulated for tra Refer to specific reg Refer to specific reg 	-	
MO / IMDG (maritime)		ulation.	
	: Refer to specific reg		
S Regulations:		gulation.	
S Regulations:	15. REGULATORY I	NFORMATION	
5 Regulations.			
OSHA Status	: Classified as hazard	ous based on compo	nents.
TSCA Status	: All components of TSCA Inventory.	this product are listed	l on or exempt from the
S. EPA CERCLA Hazardous S	Substances (40 CFR 302)		
Not applicable			
California Proposition 65	: WARNING! This p California to cause of		emical known to the State o
ARA Title III Section 302 Extr	remely Hazardous Substa	nce	
nless specific chemicals are id	entified under this section	n, this product is Not	Applicable under this regul
ARA Title III Section 313 Tox	ic Chemicals:		
nless specific chemicals are id	entified under this section	n, this product is Not	
Chemical Name		CAS-No.	Weight %
ANTIMONY COMPOUNDS		1309-64-4 1163-19-5	5.00 - 10.00 10.00 - 30.00

National Fondular Release Inventory (IN RI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Antimony trioxide	1309-64-4	5.00 - 10.00	17
Decabromodiphenyl oxide	1163-19-5	10.00 - 30.00	

MATERIAL SAFETY DATA SHEET **PP FR 8-6 NAT-20**

Version Number 1.1 Revision Date 04/14/2008 Page 7 of 7 Print Date 1/3/2012

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1309-64-4	
14807-96-6	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined	
China IECS	: Listed	
Europe EINECS	: Listed	
Japan ENCS	: Not determined	
Korea KECI	: Listed	
Philippines PICCS	: Listed	
		_

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.