

MATERIAL SAFETY DATA SHEET

RT3850MS BRIGHT YELLOW 6215

Version Number 1.0 Revision Date 03/07/2002 Page 1 of 5 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RT3850MS BRIGHT YELLOW 6215
Product code	:	EM10001139
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to ever 		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

RT3850MS BRIGHT YELLOW 6215

Version Number 1.0 Revision Date 03/07/2002 Page 2 of 5 Print Date 11/3/2011

	4. FIRST AID MEASUR		
Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all o doubt seek medical advice.			
Ingestion	Do not induce vomiting with persist or in all cases of dou	thout medical advice. When symptoms ubt seek medical advice.	
Eyes		enty of water, also under the eyelids, for at itation persists, seek medical attention.	
Skin	Wash off with soap and ple medical attention.	nty of water. If skin irritation persists seek	
	. FIRE-FIGHTING MEA	SURES	
Flash point	Not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	Not applicable Not applicable Not relevant Carbon dioxide blanket, W	ater spray, dry powder, foam.	
Special Fire Fighting Procedures	pressure mode should be w contaminants.	athing apparatus (SCBA) used in positive orn to prevent inhalation of airborne	
Unusual Fire/Explosion Hazards	None		
	CIDENTAL RELEASE N	IEASURES	
Personal precautions	Wear appropriate personal impervious gloves, boots a	protection during cleanup, such as nd coveralls.	
Environmental precautions	Should not be released into be allowed to enter drains,	the environment. The product should not water courses or the soil.	
Methods for cleaning up		eping or vacuum. Package all material in containers for disposal. Refer to Section 13 sposal methods.	
	7. HANDLING AND STO	RAGE	
Handling	Take measures to prevent the only in areas with appropriate	he build up of electrostatic charge. Heat ate exhaust ventilation.	
Storage	Keep containers dry and tig	shtly closed to avoid moisture absorption	



MATERIAL SAFETY DATA SHEET

RT3850MS BRIGHT YELLOW 6215

Version Number 1.0 Revision Date 03/07/2002 Page 3 of 5 Print Date 11/3/2011

	а	and contamination.	Keep in a d	lry, cool place.	
8. F	XPOSURE	CONTROLS / P	ERSONAL	PROTECTION	
Respiratory protection	: 1	No personal respiratory protective equipment normally required.			
Eye/Face Protection	: \$	Safety glasses with side-shields.			
Hand protection	: F	Protective gloves.			
Skin and body protection	: I	Long sleeved clothing.			
Additional Protective Measures	: 5	Safety shoes.			
General Hygiene Considerations				l industrial hygiene a at the end of workda	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure	time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:		Total dust.	OSHA
	20 mppcf	PEL:		Total dust.	Z3
	9. PHYSI	CAL AND CHEM	/ICAL PRO	OPERTIES	
F	: Soli	d	Evapo	ration rate :	Not applicable.
Form	. 501				
		ets, slabs	Specif	ic Gravity :	Not determined
Appearance	: Pelle	ets, slabs LLOW	Specif Bulk d		Not determined Not established
Form Appearance Color Odor	: Pelle : YEI		Bulk d	lensity :	
Appearance Color Odor	: Pelle : YEI : Very	LLOW	Bulk d Vapor	lensity : pressure :	Not established Not applicable
Appearance Color	: Pelle : YEI : Ver : Not	LLOW y faint	Bulk d Vapor	lensity :	Not established
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : YEI : Ver : Not	LLOW y faint determined applicable	Bulk d Vapor Vapor	lensity : pressure :	Not established Not applicable Not applicable
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : YEI : Ver : Not : Not : Inso	LLOW y faint determined applicable	Bulk d Vapor Vapor pH	lensity : pressure : density :	Not established Not applicable Not applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Pella : YEI : Very : Not : Not : Inso 10.	LLOW y faint determined applicable luble	Bulk d Vapor Vapor pH	lensity : pressure : density :	Not established Not applicable Not applicable
Appearance Color Odor Melting point/range	: Pella : YEI : Very : Not : Not : Inso 10.5	LLOW y faint determined applicable luble STABILITY ANI	Bulk d Vapor Vapor pH	lensity : pressure : density :	Not established Not applicable Not applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	: Pella : YEI : Very : Not : Not : Inso 10.5 : S n : V	LLOW y faint determined applicable sluble STABILITY ANI Stable. Will not occur.	Bulk d Vapor Vapor pH D REACTIV	lensity : pressure : density : : VITY	Not established Not applicable Not applicable Not applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: Pella : YEI : Very : Not : Not : Inso 10.5 n : V : S	LLOW y faint determined applicable sluble STABILITY ANI Stable. Will not occur. Keep away from ox lecomposition, do t	Bulk d Vapor pH DREACTIV	lensity : pressure : density : : VITY	Not established Not applicable Not applicable Not applicable



MATERIAL SAFETY DATA SHEET

RT3850MS BRIGHT YELLOW 6215

Version Number 1.0 Revision Date 03/07/2002

Page 4 of 5 Print Date 11/3/2011

products

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.			
	12. ECOLOGIO	CAL INFORMATIC	N			
Persistence and degrada	bility : Not readily bi	: Not readily biodegradable.				
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Potent		Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: Not applicabl	Not applicable				
	13. DISPOSAL	CONSIDERATION	IS			
Product	recycling is p waste materia transportation	referred to disposal o I has the responsibili	uct can be recycled. Where possible r incineration. The generator of ty for proper waste classification, rdance with applicable federal, ns.			
Contaminated packaging	has the respon- and disposal i	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPO	RT INFORMATIO	N			
U.S. D.O.T. / CA T.D.C Classification (Non-bull ground)	U	for transportation.				
ICAO/IATA	: Not regulated	for transportation.				
IMO / IMDG	: Not regulated	for transportation.				
	15. REGULATO					



MATERIAL SAFETY DATA SHEET

RT3850MS BRIGHT YELLOW 6215

/ersion Number 1.0 Revision Date 03/07/2002		Page 5 of 5 Print Date 11/3/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
Canadian Regulations:		
WHMIS Classification	:	Not controlled.
WHMIS Ingredient Disc	closu	are List
CAS-No. 1344-28-1 71631-15-7 7631-86-9 1314-23-4		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.