

MATERIAL SAFETY DATA SHEET

EXP 15502406701 NAT

Version Number 1.0 Revision Date 02/15/2002 Page 1 of 6 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	EXP 15502406701 NAT
Product code	:	EM10001249
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	471-34-1	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Talc	14807-96-6	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

EXP 15502406701 NAT

Version Number 1.0 Revision Date 02/15/2002 Page 2 of 6 Print Date 11/3/2011

Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	ıt
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.	ek
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None 	•
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	ot
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material ir plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat	



MATERIAL SAFETY DATA SHEET

EXP 15502406701 NAT

Version Number 1.0 Revision Date 02/15/2002		Page 3 of 6 Print Date 11/3/2011
		only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOS	SUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
	_	(TWA):		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Quartz	0.05	Time Weighted Average	Respirable dust.	ACGIH
	mg/m3	(TWA):	_	
	0.1 mg/m3	PEL:	Respirable dust.	OSHA
	0.3 mg/m3	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Talc	2 mg/m3	Time Weighted Average	Respirable dust.	ACGIH
	-	(TWA):	-	
	20 mppcf	Time Weighted Average	Total dust.	OSHA
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Evaporation rate

: Not applicable.



MATERIAL SAFETY DATA SHEET

EXP 15502406701 NAT

Version Number 1.0 Revision Date 02/15/2002		Page 4 of 6 Print Date <i>11/3/2011</i>
Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Pellets, slabs NO PIGMENT Very faint Not determined Not applicable Insoluble 	 Not determined Not established Not applicable Not applicable Not applicable
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open f decomposition, do not overheat.	lame. To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxidizing	agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO (NOx), other hazardous materials, and smoke	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	1



MATERIAL SAFETY DATA SHEET

EXP 15502406701 NAT

Version Number 1.0 Revision Date 02/15/2002 Page 5 of 6 Print Date 11/3/2011

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION



MATERIAL SAFETY DATA SHEET

EXP 15502406701 NAT

Version Number 1.0 Revision Date 02/15/2002		Page 6 of 6 Print Date <i>11/3/2011</i>
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
Canadian Regulations:		
WHMIS Classification	:	D2A
WHMIS Ingredient Discl	osu	ire List
CAS-No. 123-28-4 14808-60-7 7631-86-9 14807-96-6		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Not determined.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.