

MATERIAL SAFETY DATA SHEET

DP-9238-1-1000

Version Number 1.0 Revision Date 08/08/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DP-9238-1-1000
Product code	:	EM10002354
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Talc	14807-96-6	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

DP-9238-1-1000

ion Number 1.0 sion Date 08/08/2002	Page 2 Print Date 11/5/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

DP-9238-1-1000

sion Date 08/08/2002				Print I	Page Date 11/5/
	ar	nd contamination. Kee	ep in a d	ry, cool place.	
8. H	EXPOSURE	CONTROLS / PERS	SONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory	protecti	ve equipment normally r	required.
Eye/Face Protection	: Sa	afety glasses with side	e-shields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	Long sleeved clothing.			
Additional Protective Measures	: Sa	Safety shoes.			
General Hygiene Considerations		andle in accordance w ash hands before brea		industrial hygiene and sa t the end of workday.	afety practic
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s) Components	Value	Exposure time	3	Exposure type	List:
-					
Talc	2 mg/m3	Time Weighted Av (TWA):	erage	Respirable dust.	ACGIH
-	2 mg/m3 20 mppcf	Time Weighted Av	erage		
Talc	20 mppcf	Time Weighted Av (TWA): Time Weighted Av	verage verage	Respirable dust. Total dust.	ACGIH
Talc	20 mppcf 20 mppcf 9. PHYSIC : Solid : Pelle : NO F : Very : Not c	Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMICA ts, slabs PIGMENT faint letermined applicable	erage AL PRO Evapor Specifi Bulk d Vapor	Respirable dust. Total dust. DPERTIES ration rate : Not c Gravity : Not ensity : Not pressure : Not density : Not	ACGIH OSHA applicable.
Talc Talc Talc Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 20 mppcf 9. PHYSIC : Solid : Pelle : NO F : Very : Not c : Not a : Insol	Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMICA ts, slabs PIGMENT faint letermined applicable	erage AL PRO Evapor Specifi Bulk d Vapor Vapor pH	Respirable dust. Total dust. PERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not : Not	ACGIH OSHA applicable. determined established applicable applicable
Talc Talc Talc Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 9. PHYSIC : Solid : Pelle : NO F : Very : Not c : Not a : Insol 10. S	Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMICA I ts, slabs PIGMENT faint determined applicable uble	erage AL PRO Evapor Specifi Bulk d Vapor Vapor pH	Respirable dust. Total dust. PERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not : Not	ACGIH OSHA applicable. determined established applicable applicable
Talc Talc Talc Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	20 mppcf 20 mppcf 9. PHYSIC : Solid : Pelle : NO F : Very : Not c : Not z : Insol 10. S	Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMICA I ts, slabs PIGMENT faint determined applicable uble	erage AL PRO Evapor Specifi Bulk d Vapor Vapor pH	Respirable dust. Total dust. PERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not : Not	ACGIH OSHA applicable. determined established applicable applicable
Talc Talc Talc Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	20 mppcf 20 mppcf 9. PHYSIC : Solid : Pelle : NO F : Very : Not c : Not a : Insol 10. S n : W	Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMICA ts, slabs PIGMENT faint determined applicable uble TABILITY AND RE table.	rerage AL PRO Evapor Specifi Bulk d Vapor Vapor pH	Respirable dust. Total dust. PERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not TTY	ACGIH OSHA applicable. determined established applicable applicable



MATERIAL SAFETY DATA SHEET

DP-9238-1-1000

Version Number 1.0 Revision Date 08/08/2002

Page 4 of 6 Print Date 11/5/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin			
	12. ECOLOGI	CAL INFORMATION	I			
Persistence and degrada		iodegradable.	·			
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Potent		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: Not applicabl	le				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	g : Recycling is phase the response of the res	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
	14. TRANSPO	RT INFORMATION				
U.S. DOT / CA TDG Classification	: Not regulated	l for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 DECHLAT	ORY INFORMATION	J			

MATERIAL SAFETY DATA SHEET



DP-9238-1-1000

Version Number 1.0 Revision Date 08/08/2002	Page 5 of 6 Print Date 11/5/2011
	Fillit Date 11/3/2011
US Regulations:	
OSHA Status :	Classified as hazardous based on components.
TSCA Status :	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)
Not applicable	
California Proposition : 65	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification :	D2A
WHMIS Ingredient Disclosu	are List
CAS-No. 14807-96-6	
DSL :	Listed.
National Inventories:	
Australia AICS :	Not determined.
China IECS :	Listed.
Europe EINECS :	Not determined.
Japan ENCS :	Not determined.
Korea KECI :	Not determined.
Philippines PICCS :	Listed.
	16. OTHER INFORMATION
	5/6



MATERIAL SAFETY DATA SHEET

DP-9238-1-1000

Version Number 1.0 Revision Date 08/08/2002 Page 6 of 6 Print Date 11/5/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.