

MATERIAL SAFETY DATA SHEET

SFC-600 TC

Version Number 1.0 Revision Date 10/07/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SFC-600 TC
Product code	:	EM10002689
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Graphite	7782-42-5	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

SFC-600 TC

sion Date 10/07/2002	Page 2 Print Date 11/6/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





SFC-600 TC

				Print	Date 11/6
	ar	nd contamination	. Keep in a d	ry, cool place.	
8. E	XPOSURE	CONTROLS / P	PERSONAL	PROTECTION	
Respiratory protection	: No personal respiratory protective equipment normally required.			required.	
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure		Exposure type	List:
Graphite	2 mg/m3	Time Weighte (TWA	A):		ACGIH
Graphite	5 mg/m3 15 mg/m3	PEL PEL		Respirable fraction. Total dust.	
Graphite	15 mg/m3		:	Total dust.	
Graphite	15 mg/m3	PEL CAL AND CHEM	: MICAL PRO	Total dust.	OSHA Z
	15 mg/m3 9. PHYSIC : Solid	PEL CAL AND CHEM	: MICAL PRO Evapor	Total dust. DPERTIES ration rate : Not	OSHA Z
Form Appearance Color	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA	PEL CAL AND CHEM I its, slabs CK	: MICAL PRO Evapor Specifi Bulk d	Total dust. PERTIES ration rate : Not ic Gravity : Not ensity : Not	t determined t established
Form Appearance Color Odor	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very	PEL CAL AND CHEN I ts, slabs CK faint	: MICAL PRO Evapor Specifi Bulk d Vapor	Total dust. OPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not	OSHA Z t applicable. t determined t established t applicable
Form Appearance Color Odor Melting point/range	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very : Not c	PEL CAL AND CHEN I its, slabs CK faint determined	: MICAL PRO Evapor Specifi Bulk d Vapor Vapor Vapor	Total dust. OPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not	OSHA Z t applicable. t determined t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very : Not c : Not a	PEL CAL AND CHEN Its, slabs CK faint determined applicable	: MICAL PRO Evapor Specifi Bulk d Vapor	Total dust. OPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not	OSHA Z t applicable. t determined t established t applicable
Form Appearance Color Odor Melting point/range	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very : Not c	PEL CAL AND CHEN Its, slabs CK faint determined applicable	: MICAL PRO Evapor Specifi Bulk d Vapor Vapor Vapor	Total dust. OPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not	OSHA Z t applicable. t determined t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very : Not c : Not a : Insol	PEL CAL AND CHEN Its, slabs CK faint determined applicable	: MICAL PRO Evapor Specifi Bulk d Vapor Vapor pH	Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not density : Not : Not : Not	OSHA Z t applicable. t determined t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very : Not c : Not a : Insol 10. S	PEL CAL AND CHEN Its, slabs CK faint determined applicable uble	: MICAL PRO Evapor Specifi Bulk d Vapor Vapor pH	Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not density : Not : Not : Not	OSHA Z t applicable. t determined t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very : Not c : Not a : Insol 10. S : St	PEL CAL AND CHEN its, slabs CK faint determined applicable uble	: MICAL PRO Evapor Specifi Bulk d Vapor Vapor pH	Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not density : Not : Not : Not	OSHA Z t applicable. t determined t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	15 mg/m3 9. PHYSIC : Solid : Pelle : BLA : Very : Not c : Not z : Insol 10. S n : W	PEL CAL AND CHEN I sts, slabs CK faint determined applicable uble STABILITY AN table.	: MICAL PRO Evapor Specifi Bulk d Vapor Vapor pH D REACTIV	Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not density : Not : Not : Not	OSHA Z t applicable. t determined t established t applicable t applicable



MATERIAL SAFETY DATA SHEET

SFC-600 TC

Version Number 1.0 Revision Date 10/07/2002

Page 4 of 6 Print Date 11/6/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

7782-42-5	Chemical Name Graphite	E Effect Systemic effects	Target Organ Respiratory system, heart or			
	Chapinto		circulatory system.			
	12. ECOLO	GICAL INFORMATIO	N			
Persistence and degrad	dability · Not readi	ily biodegradable.				
Environmental Toxici	ty : Chemica	: Not readily blodegraduate.: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Pote	ntial : Chemica of the po		as they are bound within the matrix			
Additional advice	: Not appli	icable				
	13. DISPOS	SAL CONSIDERATION	8			
Product	possible, generator classifica	recycling is preferred to d				
Contaminated packagi	has the re and dispo	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANS	SPORT INFORMATION	I			
U.S. DOT Classificati	on : Not regu	lated for transportation.				
ICAO/IATA	: Not regu	lated for transportation.				
IMO / IMDG	: Not regu	lated for transportation.				
	15. REGUL					

MATERIAL SAFETY DATA SHEET



SFC-600 TC Version Number 1.0 Page 5 of 6 Revision Date 10/07/2002 Print Date 11/6/2011 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2A DSL : Listed. National Inventories: Australia AICS Not determined. · China IECS Not determined. ÷ **Europe EINECS** Not determined. Japan ENCS Not determined. : Korea KECI Not determined. : **Philippines PICCS** Not determined. :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

SFC-600 TC

Version Number 1.0 Revision Date 10/07/2002



Page 6 of 6 Print Date 11/6/2011