

MATERIAL SAFETY DATA SHEET

NN-NX 121102

Version Number 1.0 Revision Date 01/16/2003 Page 1 of 6 Print Date 11/7/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	NN-NX 121102
Product code	:	EM10003258
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Graphite	7782-42-5	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

NN-NX 121102

ion Number 1.0 sion Date 01/16/2003	Page 2 Print Date 11/7/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

NN-NX 121102

Respiratory protection Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Va Graphite 5 m 15 n	DSURE : N : S : P : L : S : H W : H au alue ng/m3	Vo personal resp afety glasses wi Protective gloves Long sleeved clo afety shoes. Handle in accorda Vash hands befo	PERSONAL iratory protecti ith side-shields. s. thing. ance with good ore breaks and a s with appropri ust ventilation a re time	PROTECTION ve equipment normally re industrial hygiene and sa at the end of workday. iate exhaust ventilation.	afety practic
Respiratory protection Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Va Graphite 5 m 15 n	: N : S : P : L : S : H W : H aj	Vo personal resp afety glasses wi Protective gloves Long sleeved clo afety shoes. Handle in accord Vash hands befo Heat only in area ppropriate exhat Exposur Time Weight	iratory protecti ith side-shields. s. thing. ance with good ore breaks and a us with appropri- ust ventilation a re time	ve equipment normally r l industrial hygiene and sa at the end of workday. iate exhaust ventilation. at machinery.	afety practic Provide List:
Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Va Graphite 5 m 15 n	: Si : P : L : Si : H W : H aj	Eafety glasses wi Protective gloves Long sleeved clo Eafety shoes. Handle in accorda Vash hands befo Heat only in area ppropriate exhan Exposur Time Weight	th side-shields. thing. ance with good ore breaks and a s with appropri ust ventilation a re time	industrial hygiene and sa at the end of workday. iate exhaust ventilation. at machinery.	afety practic Provide List:
Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Va Graphite 2 m Graphite 5 m 15 n	: P : L : S : H W : H aj	Protective gloves Long sleeved clo Safety shoes. Handle in accords Vash hands befo Heat only in area ppropriate exhau	thing. ance with good ore breaks and a s with appropri- ust ventilation a re time	l industrial hygiene and sa at the end of workday. iate exhaust ventilation. at machinery.	Provide List:
Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Va Graphite 5 m 15 n	: L : S : H W : H aj	Long sleeved clo Gafety shoes. Handle in accord Vash hands befo Heat only in area ppropriate exhan Exposur Time Weight	thing. ance with good ore breaks and a as with appropri- ust ventilation a re time	at the end of workday. iate exhaust ventilation. at machinery.	Provide List:
Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Va Graphite 2 m Image: State of the state	: Si : H W : H aj	afety shoes. Iandle in accord Vash hands befo Ieat only in area ppropriate exhan Exposur Time Weight	ance with good ore breaks and a s with appropri- ust ventilation a re time	at the end of workday. iate exhaust ventilation. at machinery.	Provide List:
Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Va Graphite 2 m Graphite 5 m 15 m	: H W : H aj	Handle in accord Vash hands befo Heat only in area ppropriate exhan Exposur Time Weight	ore breaks and a s with appropri ust ventilation a re time	at the end of workday. iate exhaust ventilation. at machinery.	Provide List:
Considerations Engineering measures Exposure limit(s) Components Va Graphite 2 m Graphite 5 m 15 n	W : H aj alue ng/m3	Vash hands befo Ieat only in area ppropriate exhan Exposu Time Weight	ore breaks and a s with appropri ust ventilation a re time	at the end of workday. iate exhaust ventilation. at machinery.	Provide List:
Exposure limit(s) Components Va Graphite 2 m Graphite 5 m 15 n	aj alue ng/m3	ppropriate exhau Exposu Time Weight	ust ventilation a	at machinery.	List:
ComponentsVaGraphite2 mGraphite5 m15 n	ng/m3	Time Weight		Exposure type	
15 n	1a/m2	(TW			
15 n		PE		Respirable fraction.	OSHA Z
9. F	mg/m3	PEL:		Total dust.	OSHA ZI
	PHYSIC	CAL AND CHI	EMICAL PRO	PERTIES	
Color: NOOdor: VeryMelting point/range: Not		ets, slabsSpecific Gravity:PIGMENTBulk density:v faintVapor pressure:determinedVapor density:applicablepH:		ic Gravity : Not ensity : Not pressure : Not density : Not	applicable. determined established applicable applicable applicable
	10. S	STABILITY A	ND REACTIV	ТТҮ	
Stability	: S	table.			
Hazardous Polymerization	: W	Vill not occur.			
Conditions to avoid	: T	'o avoid thermal	decomposition	n, do not overheat.	
Incompatible Materials	: S	trong acids, oxi	idizing and re-	ducing agents.	



MATERIAL SAFETY DATA SHEET

NN-NX 121102

Version Number 1.0 Revision Date 01/16/2003

Page 4 of 6 Print Date 11/7/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.		al Name	Effect	Target Organ		
7782-42-5	Graphite		Systemic effects	Respiratory system, heart or circulatory system.		
	12.	ECOLOGIC	AL INFORMATION	I		
Persistence and degra	idability : N	Not readily bio	odegradable.			
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Pot		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: 1	: Not applicable				
	13.	DISPOSAL	CONSIDERATIONS			
Product		: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packag	ł	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14.	TRANSPOR	RT INFORMATION			
U.S. DOT Classificat	ion : N	Not regulated	for transportation.			
ICAO/IATA	: 1	Not regulated	for transportation.			
IMO / IMDG	: 1	Not regulated	for transportation.			
	15.]					

MATERIAL SAFETY DATA SHEET



NN-NX 121102 Version Number 1.0 Page 5 of 6 Print Date 11/7/2011 Revision Date 01/16/2003 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the TSCA ÷ Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2A DSL All components of this product are on the Canadian Domestic · Substances List (DSL) or are exempt. National Inventories: Australia AICS Not determined. • China IECS Listed. Europe EINECS Not determined. : Japan ENCS Not determined. : Korea KECI Not determined. · **Philippines PICCS** : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MATERIAL SAFETY DATA SHEET

NN-NX 121102

Version Number 1.0 Revision Date 01/16/2003



Page 6 of 6 Print Date 11/7/2011