MATERIAL SAFETY DATA SHEET GF 600 A 33 HS NATURAL

Version Number 1.0 Revision Date 09/08/2003 Page 1 of 5 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GF 600 A 33 HS NATURAL
Product code	:	EM10004661
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET GF 600 A 33 HS NATURAL

Version Number 1.0 Revision Date 09/08/2003 Page 2 of 5 Print Date 11/12/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not relevant
Suitable extinguishing media	:	water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	None
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/5

PolyOne.

MATERIAL SAFETY DATA SHEET GF 600 A 33 HS NATURAL

Version Number 1.0 Revision Date 09/08/2003 Page 3 of 5 Print Date 11/12/2011

0. EAT	OSURE CONTROLS / I	PERSONAL PROTECTION	
Respiratory protection	: No personal respir	atory protective equipment normally required.	
Eye/Face Protection	: Safety glasses with	n side-shields.	
Hand protection	: Protective gloves.		
Skin and body protection	: Long sleeved cloth	ing.	
Additional Protective Measures	: Safety shoes.		
General Hygiene Considerations		nce with good industrial hygiene and safety pract breaks and at the end of workday.	ice.
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)			
	s components above regul	atory thresholds in this product.	
9. Form Appearance Color Odor	PHYSICAL AND CHE : Solid : Pellets, slabs : NO PIGMENT : Very faint	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapor pressure : Not applicable	1 1
9. Form Appearance Color	PHYSICAL AND CHE : Solid : Pellets, slabs : NO PIGMENT	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established	1
9. Form Appearance Color Odor Melting point/range	PHYSICAL AND CHE : Solid : Pellets, slabs : NO PIGMENT : Very faint : Not determined	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapor pressure : Not applicable Vapor density : Not applicable Vapor density : Not applicable	1
9. Form Appearance Color Odor Melting point/range Boiling Point:	PHYSICAL AND CHE : Solid : Pellets, slabs : NO PIGMENT : Very faint : Not determined : Not applicable	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapor pressure : Not applicable Vapor density : Not applicable pH : Not applicable	1
9. Form Appearance Color Odor Melting point/range Boiling Point:	PHYSICAL AND CHE : Solid : Pellets, slabs : NO PIGMENT : Very faint : Not determined : Not applicable : Insoluble	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapor pressure : Not applicable Vapor density : Not applicable pH : Not applicable	1
9. Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	PHYSICAL AND CHE : Solid : Pellets, slabs : NO PIGMENT : Very faint : Not determined : Not applicable : Insoluble 10. STABILITY AN	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapor pressure : Not applicable Vapor density : Not applicable pH : Not applicable	1
9. Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	PHYSICAL AND CHEI : Solid : Pellets, slabs : NO PIGMENT : Very faint : Not determined : Not applicable : Insoluble 10. STABILITY AN : Stable. : Will not occur.	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapor pressure : Not applicable Vapor density : Not applicable pH : Not applicable	1
9. Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	PHYSICAL AND CHEI : Solid : Pellets, slabs : NO PIGMENT : Very faint : Not determined : Not applicable : Insoluble 10. STABILITY AN : Stable. : Will not occur. : To avoid thermal of	MICAL PROPERTIES Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapor pressure : Not applicable Vapor density : Not applicable pH : Not applicable D REACTIVITY	1

PolyOne

MATERIAL SAFETY DATA SHEET GF 600 A 33 HS NATURAL

Version Number 1.0 Revision Date 09/08/2003 Page 4 of 5 Print Date 11/12/2011

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

PolyOne

MATERIAL SAFETY DATA SHEET GF 600 A 33 HS NATURAL

Version Number 1.0
Revision Date 09/08/2003

Page 5 of 5 Print Date 11/12/2011

California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Extr	rem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Tox	ic (Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Releas	se Iı	nventory (NPRI)
Not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	DSL status has not been determined. Quantity use in Canada may be restricted by regulations.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.
		16 OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.