MATERIAL SAFETY DATA SHEET GF 600 A 44 HS BLACK 13

Version Number 1.1 Revision Date 12/10/2009 Page 1 of 6 Print Date 1/10/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GF 600 A 44 HS BLACK 13
Product code	:	EM10004663
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Glass, oxide	65997-17-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

MATERIAL SAFETY DATA SHEET **GF 600 A 44 HS BLACK 13**

Version Number 1.1 Revision Date 12/10/2009 Page 2 of 6 Print Date 1/10/2012

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion Hazards	 pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET **GF 600 A 44 HS BLACK 13**

Version Number 1.1 Revision Date 12/10/2009 Page 3 of 6 Print Date 1/10/2012

0. E21	POSURE CONTROLS/PERS	ONAL PROTECTION	
Respiratory protection	: No personal respiratory	protective equipment normally required.	
Eye/Face Protection	: Safety glasses with side	e-shields	
Hand protection	: Protective gloves		
Skin and body protection	: Long sleeved clothing		
Additional Protective Measures	: Safety shoes		
General Hygiene Considerations		vith good industrial hygiene and safety before breaks and at the end of workday.	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		
Exposure limit(s)			
	. PHYSICAL AND CHEMIC		
Form Appearance Colour Odour Melting point/range Boiling Point:	 solid pellets, Slabs BLACK very faint Not determined not applicable 	AL PROPERTIESEvaporation rate: Not applicableSpecific Gravity: Not determinedBulk density: Not establishedVapour pressure: not applicableVapour density: not applicablepH: not applicable	
Form Appearance Colour Odour Melting point/range	 solid pellets, Slabs BLACK very faint Not determined 	Evaporation rate: Not applicableSpecific Gravity: Not determinedBulk density: Not establishedVapour pressure: not applicableVapour density: not applicable	
Form Appearance Colour Odour Melting point/range Boiling Point:	 solid pellets, Slabs BLACK very faint Not determined not applicable 	Evaporation rate: Not applicableSpecific Gravity: Not determinedBulk density: Not establishedVapour pressure: not applicableVapour density: not applicablepH: not applicable	
Form Appearance Colour Odour Melting point/range Boiling Point:	 solid pellets, Slabs BLACK very faint Not determined not applicable insoluble 	Evaporation rate: Not applicableSpecific Gravity: Not determinedBulk density: Not establishedVapour pressure: not applicableVapour density: not applicablepH: not applicable	
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets, Slabs BLACK very faint Not determined not applicable insoluble 10. STABILITY AND R	Evaporation rate: Not applicableSpecific Gravity: Not determinedBulk density: Not establishedVapour pressure: not applicableVapour density: not applicablepH: not applicable	
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability	 solid pellets, Slabs BLACK very faint Not determined not applicable insoluble 10. STABILITY AND R Stable Will not occur. 	Evaporation rate: Not applicableSpecific Gravity: Not determinedBulk density: Not establishedVapour pressure: not applicableVapour density: not applicablepH: not applicable	
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	 solid pellets, Slabs BLACK very faint Not determined not applicable insoluble 10. STABILITY AND R Stable Will not occur. 	Evaporation rate : Not applicable Specific Gravity : Not determined Bulk density : Not established Vapour pressure : not applicable Vapour density : not applicable pH : not applicable EACTIVITY	

PolyOne

MATERIAL SAFETY DATA SHEET GF 600 A 44 HS BLACK 13

Version Number 1.1 Revision Date 12/10/2009 Page 4 of 6 Print Date 1/10/2012

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
	12. ECOLOGIC	AL INFORMATI	ON			
Persistence and degradabilit	y : Not readily bio	odegradable.				
Environmental Toxicity	: Chemicals are polymer matrix		le as they are bound within the			
Bioaccumulation Potential	: Chemicals are polymer matrix		le as they are bound within the			
Additional advice	: not applicable	: not applicable				
	13. DISPOSAL	CONSIDERATIO	NS			
Product	possible recycle generator of w classification,	ling is preferred to easte material has the transportation and eastern	he product can be recycled. W disposal or incineration. The e responsibility for proper was disposal in accordance with l and local regulations.			
Contaminated packaging	material has th transportation	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPOR	RT INFORMATIC	N			
U.S. DOT Classification	: Not regulated	for transportation.				
ICAO/IATA	: Refer to specif	ic regulation.				
IMO/IMDG (maritime)	: Refer to specif	ic regulation.				
	15. REGULATO	RY INFORMATI	ON			
US Regulations:						
OSHA Status	: Classified as h	azardous based on	components.			
TSCA Status	: All componen TSCA Invento		re listed on or exempt from the			

PolvOne

MATERIAL SAFETY DATA SHEET **GF 600 A 44 HS BLACK 13**

Version Number 1.1 Revision Date 12/10/2009 Page 5 of 6 Print Date 1/10/2012

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

MATERIAL SAFETY DATA SHEET GF 600 A 44 HS BLACK 13

Version Number 1.1 Revision Date 12/10/2009 Page 6 of 6 Print Date 1/10/2012

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.