# MATERIAL SAFETY DATA SHEET MSDS PC-PBT ALLOY # 108-37 NG1

Version Number 1.0 Revision Date 10/01/2003

Page 1 of 6 Print Date 11/12/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

## POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MSDS PC-PBT ALLOY # 108-37 NG1
Product code	:	EM10004871
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Acrylic acid	79-10-7	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eves.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET MSDS PC-PBT ALLOY # 108-37 NG1

Version Number 1.0 Revision Date 10/01/2003 Page 2 of 6 Print Date 11/12/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not relevant
Suitable extinguishing media	:	water, dry powder, foam, carbon dioxide (CO2)None.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	None
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

# MATERIAL SAFETY DATA SHEET MSDS PC-PBT ALLOY # 108-37 NG1

Version Number 1.0 Revision Date 10/01/2003 Page 3 of 6 Print Date 11/12/2011

	and cor	ntamination. Keep in a di	ry, cool place.	
8. E	XPOSURE CON	TROLS / PERSONAL	PROTECTION	
Respiratory protection	: No pers	sonal respiratory protectiv	ve equipment normally r	equired.
Eye/Face Protection	: Safety	glasses with side-shields.		
Hand protection	: Protect	ive gloves. Refer to equip	oment supplier to ensure	protection.
Skin and body protection	: Long sleeved clothing.			
Additional Protective Measures	: Safety	shoes.		
General Hygiene Considerations		in accordance with good ands before breaks and a		afety practice.
Engineering measures		nly in areas with appropri riate exhaust ventilation a		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Acrylic acid	2 ppm 5.9 Tir mg/m3	me Weighted Average (TWA):	Vapor.	ACGIH
	9. PHYSICAL A	AND CHEMICAL PRO	PERTIES	
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Solid : Pellets, sla : GREEN : Very faint : Not determ : Not applic. : Insoluble	bs Specifi Bulk de Vapor j nined Vapour	c Gravity : Not ensity : Not pressure : Not r density : Not	applicable determined established applicable applicable applicable
	10. STAB	ILITY AND REACTIV	ITY	
Stability	: Stable.			
Hazardous Polymerization	n : Will no	ot occur.		
Conditions to avoid	: To avoi	id thermal decomposition	, do not overheat.	
Incompatible Materials	: Strong	asida avidizing and ma	ducing agents.	
		acids, oxidizing and rec		



# MATERIAL SAFETY DATA SHEET MSDS PC-PBT ALLOY # 108-37 NG1

#### Version Number 1.0 Revision Date 10/01/2003

Page 4 of 6 Print Date 11/12/2011

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
79-10-7	Acrylic acid	Irritant	Eyes, Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
		Highly Toxic	Refer to LC50 / LD50 Data on
			MSDS

## LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
79-10-7	Acrylic acid	LC50	5300 mg/m3	mouse
		Oral LD50	33.50 mg/kg	rat
		Dermal LD50	280 ul/kg	rabbit

## Additional Health Hazard Information:

Acrylic acid 79-10-7 Can cause permanent eye injury. Can cause permanent skin damage.Breathing this material may be harmful.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	:	Not applicable
	1.	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
		Recycling is preferred when possible. The generator of waste material



# MATERIAL SAFETY DATA SHEET MSDS PC-PBT ALLOY # 108-37 NG1

Version Number 1.0 Revision Date 10/01/2003

Page 5 of 6 Print Date 11/12/2011

and disposal in accordance with applicable federal, state/provincial and local regulations.

## 14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

## **15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components	OSHA Status	: Classified as hazardous based on components.
---	-------------	--

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ACRYLIC ACID	79-10-7	1.02

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Acrylic acid	79-10-7	1.02	6

WHMIS Classification : D1A



# MATERIAL SAFETY DATA SHEET MSDS PC-PBT ALLOY # 108-37 NG1

Version Number 1.0 Revision Date 10/01/2003 Page 6 of 6 Print Date *11/12/2011* 

WHMIS Ingredient Disclosure List

CAS-No.	
79-10-7	

DSL

: DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	: Not determined	ł
China IECS	: Not determined	ł
Europe EINECS	: Not determined	ł
Japan ENCS	: Not determined	ł
Korea KECI	: Not determined	ł
Philippines PICCS	: Not determined	ł

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.