## MATERIAL SAFETY DATA SHEET GMF 600 40 UV / 207D CHARCOAL GREY

Version Number 1.0 Revision Date 11/18/2003

Page 1 of 6 Print Date 11/12/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GMF 600 40 UV / 207D CHARCOAL GREY
Product code	:	EM10005183
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET GMF 600 40 UV / 207D CHARCOAL GREY

Version Number 1.0 Revision Date 11/18/2003 Page 2 of 6 Print Date 11/12/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature		Not relevant
Suitable extinguishing media	:	water, dry powder, foam, carbon dioxide (CO2)none.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	None
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6



# MATERIAL SAFETY DATA SHEET GMF 600 40 UV / 207D CHARCOAL GREY

Version Number 1.0 Revision Date 11/18/2003 Page 3 of 6 Print Date 11/12/2011

07 211	POSURE CONTROL	S / PERSONAL PROTECTION
Respiratory protection	: No personal re	espiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses	with side-shields.
Hand protection	: Protective glo	ves. Refer to equipment supplier to ensure protection.
Skin and body protection	: Long sleeved	clothing.
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations		ordance with good industrial hygiene and safety practice. efore breaks and at the end of workday.
Engineering measures		reas with appropriate exhaust ventilation. Provide haust ventilation at machinery.
Exposure limit(s)		
	9 PHYSICAL AND C	regulatory thresholds in this product.
		CHEMICAL PROPERTIES
Form	: Solid	Evaporation rate : Not applicable
Form Appearance		Evaporation rate : Not applicable
Form Appearance Color	: Solid : Pellets, slabs	Evaporation rate       Not applicable         Specific Gravity       Not determined
Form Appearance Color Odor Melting point/range	: Solid : Pellets, slabs : BLACK	Evaporation rate       Not applicable         Specific Gravity       Not determined         Bulk density       Not established
Form Appearance Color Odor Melting point/range Boiling Point:	<ul> <li>Solid</li> <li>Pellets, slabs</li> <li>BLACK</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> </ul>	Evaporation rate       : Not applicable         Specific Gravity       : Not determined         Bulk density       : Not established         Vapor pressure       : Not applicable
Form Appearance Color Odor Melting point/range	: Solid : Pellets, slabs : BLACK : Very faint : Not determined	Evaporation rate       : Not applicable         Specific Gravity       : Not determined         Bulk density       : Not established         Vapor pressure       : Not applicable         Vapour density       : Not applicable
Form Appearance Color Odor Melting point/range Boiling Point:	<ul> <li>Solid</li> <li>Pellets, slabs</li> <li>BLACK</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul>	Evaporation rate       : Not applicable         Specific Gravity       : Not determined         Bulk density       : Not established         Vapor pressure       : Not applicable         Vapour density       : Not applicable
Form Appearance Color Odor Melting point/range Boiling Point:	<ul> <li>Solid</li> <li>Pellets, slabs</li> <li>BLACK</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul>	Evaporation rate       : Not applicable         Specific Gravity       : Not determined         Bulk density       : Not established         Vapor pressure       : Not applicable         Vapour density       : Not applicable         pH       : Not applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>Solid</li> <li>Pellets, slabs</li> <li>BLACK</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul> 10. STABILITY	Evaporation rate       : Not applicable         Specific Gravity       : Not determined         Bulk density       : Not established         Vapor pressure       : Not applicable         Vapour density       : Not applicable         pH       : Not applicable         f       AND REACTIVITY
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	<ul> <li>Solid</li> <li>Pellets, slabs</li> <li>BLACK</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul> <b>10. STABILITY</b> <ul> <li>Stable.</li> <li>Will not occur</li> </ul>	Evaporation rate       : Not applicable         Specific Gravity       : Not determined         Bulk density       : Not established         Vapor pressure       : Not applicable         Vapour density       : Not applicable         pH       : Not applicable         f       AND REACTIVITY
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	<ul> <li>Solid</li> <li>Pellets, slabs</li> <li>BLACK</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul> <b>10. STABILITY</b> <ul> <li>Stable.</li> <li>Will not occurding</li> <li>To avoid thermined</li> </ul>	<b>EXAMPLY INTEGRATION PROPERTIES</b> Evaporation rate       : Not applicable         Specific Gravity       : Not determined         Bulk density       : Not established         Vapor pressure       : Not applicable         Vapour density       : Not applicable         pH       : Not applicable         pH       : Not applicable         Sector       : Not applicable         pH       : Not applicable

PolyOne.

# MATERIAL SAFETY DATA SHEET GMF 600 40 UV / 207D CHARCOAL GREY

Version Number 1.0 Revision Date 11/18/2003 Page 4 of 6 Print Date 11/12/2011

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

## MATERIAL SAFETY DATA SHEET GMF 600 40 UV / 207D CHARCOAL GREY

Version Number 1.0 Revision Date 11/18/2003 Page 5 of 6 Print Date 11/12/2011

California Proposition : This product does not contain a substance listed by California Prop 65. 65

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Copper iodide (CuI)	7681-65-4	0.36	70
Rutile, antimony chromium buff	68186-90-3	0.23	68
Rutile, antimony chromium buff	68186-90-3	0.23	17

WHMIS Classification	:	Not controlled.
DSL	:	DSL status has not been determined. Quantity use in Canada may be restricted by regulations.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.



MATERIAL SAFETY DATA SHEET GMF 600 40 UV / 207D CHARCOAL GREY

Version Number 1.0 Revision Date 11/18/2003 Page 6 of 6 Print Date 11/12/2011