

## MATERIAL SAFETY DATA SHEET

# ONFLEX-V 1045A-S0011 NATURAL

Version Number 1.2 Page 1 of 6
Revision Date 02/20/2007 Print Date 11/26/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

Telephone : Product Stewardship (440) 930-1395

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : ONFLEX-V 1045A-S0011 NATURAL

Product code : EM10005235 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Zinc oxide	1314-13-2	1 - 5
Zinc stearate	557-05-1	1 - 5

## 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Particulates, like other inert materials can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Particulates, like other inert materials can be mechanically irritating.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions** : None known.

**Aggravated by Exposure:** 



## MATERIAL SAFETY DATA SHEET

# ONFLEX-V 1045A-S0011 NATURAL

 Version Number 1.2
 Page 2 of 6

 Revision Date 02/20/2007
 Print Date 11/26/2011

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable
Lower explosion limit : Not applicable
Autoignition temperature : Not applicable

Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foamnone.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption



## MATERIAL SAFETY DATA SHEET

# ONFLEX-V 1045A-S0011 NATURAL

 Version Number 1.2
 Page 3 of 6

 Revision Date 02/20/2007
 Print Date 11/26/2011

and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures

: Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

## Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Zinc oxide	10 mg/m3	Time Weighted Average	Total dust. as Zn	ACGIH
		(TWA):		
	5 mg/m3	PEL:	Respirable dust. as Zn	OSHA Z1
	15 mg/m3	PEL:	Total dust. as Zn	OSHA Z1
	2 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
	10 mg/m3	Short Term Exposure Limit	Respirable fraction.	ACGIH
		(STEL):		
Zinc stearate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as stearates	ACGIH
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid Evaporation rate Not applicable Appearance : Pellets, Slabs Specific Gravity: Not determined Color : NO PIGMENT Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable рH Not applicable

Water solubility : Insoluble



## MATERIAL SAFETY DATA SHEET

# ONFLEX-V 1045A-S0011 NATURAL

Version Number 1.2 Page 4 of 6
Revision Date 02/20/2007 Print Date 11/26/2011

#### 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : To avoid thermal decomposition, do not overheat.

Incompatible Materials : Strong acids, oxidizing and reducing agents

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

11. TOXICOLOGICAL INFORMATION

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1314-13-2	Zinc oxide	Systemic effects	Respiratory system.
557-05-1	Zinc stearate	Systemic effects	Eyes, Skin, Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1314-13-2	Zinc oxide	LC50	2500 mg/m3	mouse
		Oral	7,950	mousemouse
		LD50Oral	mg/kg7,950	
		LD50	mg/kg	
557-05-1	Zinc stearate	Oral LD50	> 10 gm/kg	rat

## 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the

polymer matrix.

Additional advice : Not applicable

### 13. DISPOSAL CONSIDERATIONS



## MATERIAL SAFETY DATA SHEET

# ONFLEX-V 1045A-S0011 NATURAL

Version Number 1.2 Page 5 of 6
Revision Date 02/20/2007 Print Date 11/26/2011

Product : Like most thermoplastic plastics the product can be recycled. Where

possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

### 14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA (air) : Refer to specific regulation.

IMO / IMDG (maritime) : Refer to specific regulation.

### 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : Not applicable

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name CAS-No. Weight %



## MATERIAL SAFETY DATA SHEET

# ONFLEX-V 1045A-S0011 NATURAL

 Version Number 1.2
 Page 6 of 6

 Revision Date 02/20/2007
 Print Date 11/26/2011

Chemical Name	CAS-No.	Weight %
ZINC COMPOUNDS	1314-13-2	1.00 - 5.00
ZINC COMPOUNDS	557-05-1	1.00 - 5.00

#### Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Zinc oxide	1314-13-2	1.00 - 5.00	231
Zinc stearate	557-05-1	1.00 - 5.00	231

WHMIS Classification : Not controlled.

DSL : DSL status has not been determined. Quantity use in Canada may be

restricted by regulations.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

## 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.