

MATERIAL SAFETY DATA SHEET

PEM-50-01-112-L1TS

Version Number 1.0 Revision Date 02/20/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PEM-50-01-112-L1TS
Product code	:	EM10005381
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Tungsten	7440-33-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET PEM-50-01-112-L1TS

Version Number 1.0 Revision Date 02/20/2004 Page 2 of 6 Print Date 11/14/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6



MATERIAL SAFETY DATA SHEET PEM-50-01-112-L1TS

Version Number 1.0 Revision Date 02/20/2004 Page 3 of 6 Print Date 11/14/2011

8. 1		nd contamination. Keep in a		
Respiratory protection		lo personal respiratory protec		required.
Eye/Face Protection	: S	afety glasses with side-shield	S.	-
Hand protection		rotective gloves.		
-		-		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		Iandle in accordance with goo Vash hands before breaks and		afety practice.
Engineering measures		leat only in areas with approp ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Tungsten	5 mg/m3	Time Weighted Average	***	1 GGTT
Tungston	5 mg/m5	• •	as W	ACGIH
	10 mg/m3	(TWA): Short Term Exposure Limit (STEL):		ACGIH
	10 mg/m3	(TWA): Short Term Exposure Limit	as W	
	10 mg/m3 9. PHYSIC	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR	as W OPERTIES	ACGIH
Form	10 mg/m3 9. PHYSIC : Solic	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR	as W OPERTIES oration rate : Not	
Form Appearance	10 mg/m3 9. PHYSIC : Solic : Pelle : NO I	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Speci PIGMENT Bulk	as W OPERTIES oration rate : Not fic Gravity: : Not density : Not	ACGIH applicable determined established
Form Appearance Color Odor	10 mg/m3 9. PHYSIC : Solic : Pelle : NO I : Very	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Speci PIGMENT Bulk v faint Vapo	as W OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not	ACGIH applicable determined established applicable
Form Appearance Color Odor Melting point/range	10 mg/m3 9. PHYSIC : Solic : Pelle : NO I : Very : Not of	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Speci PIGMENT Bulk v faint Vapo determined Vapo	as W OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not	applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 9. PHYSIC : Solic : Pelle : NO I : Very : Not of	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Speci PIGMENT Bulk / faint Vapo determined Vapo applicable pH	as W OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not	ACGIH applicable determined established applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 9. PHYSIC : Solic : Pelle : NO I : Very : Not a : Insol	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Speci PIGMENT Bulk / faint Vapo determined Vapo applicable pH	as W OPERTIES Oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	ACGIH applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 9. PHYSIC 2. Solid 3. Pelle 3. No 1 4. Very 4. Not 6 5. Not 6 5. Insol 10. S	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Special PIGMENT Bulk v faint Vapor determined Vapor applicable pH	as W OPERTIES Oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	ACGIH applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 9. PHYSIO : Solid : Pelle : NO I : Very : Not d : Insol 10. S : S	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Speci PIGMENT Bulk d faint Vapo determined Vapo applicable pH buble STABILITY AND REACTI	as W OPERTIES Oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	ACGIH applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	10 mg/m3 9. PHYSIC : Solic : Pelle : NO I : Very : Not c : Not a : Insol 10. S : S n : W	(TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evap ets, slabs Special PIGMENT Bulk t faint Vapor determined pH luble STABILITY AND REACTI table. Example.	as W OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not VITY	ACGIH applicable determined established applicable applicable



MATERIAL SAFETY DATA SHEET **PEM-50-01-112-L1TS**

Version Number 1.0

Revision Date 02/20/2004

Page 4 of 6 Print Date 11/14/2011

Hazardous decomposition : Ca products (N

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7440-33-7	Tungsten	Systemic effects	Eyes, Skin, Respiratory system, blood and blood forming system.

Additional Health Hazard Information:

Tungsten 7440-33-7 Prolonged or repeated breathing of this material may result in chronic bronchitis. Exposure to freshly formed fumes from heated metal may cause "metal fume fever".

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial
	and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.

4/6



MATERIAL SAFETY DATA SHEET
<i>PEM-50-01-112-L1TS</i>

ion Number 1.0 sion Date 02/20/2004		Page 5 Print Date 11/14/2
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65
SARA Title III Section 302 Ext	rem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Top	xic C	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Relea	se Ir	nventory (NPRI)
Not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Listed
Europe EINECS	:	Listed

PolyOne	
POLYONE CORPORATION	
MATERIAL SAFETY DATA SHEET	
PEM-50-01-112-L1TS	
Version Number 1.0PageRevision Date 02/20/2004Print Date 11/14	
Korea KECI : Not determined	
Philippines PICCS : Not determined	
16. OTHER INFORMATION	
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and at the date of its publication. The information given is designed only as a guidance for safe handling, use processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for su material when used in combination with any other materials and/or in any particular process or processin conditions.	, 1ch