# MATERIAL SAFETY DATA SHEET

# GRV-NP-069-BMX-Nat-3W

Version Number 1.0 Revision Date 03/24/2004 Page 1 of 6 Print Date 11/14/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Elephone Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GRV-NP-069-BMX-Nat-3W
Product code	:	EM10005971
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Barium sulfate	7727-43-7	10 - 30
Tungsten	7440-33-7	60 - 100

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact			
Acute exposure				
Inhalation Ingestion Eyes Skin	<ul> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>			
Chronic exposure Medical Conditions Aggravated by Exposure:	<ul><li>Refer to Section 11 for Toxicological Information.</li><li>None known.</li></ul>			



# MATERIAL SAFETY DATA SHEET GRV-NP-069-BMX-Nat-3W

Version Number 1.0 Revision Date 03/24/2004 Page 2 of 6 Print Date 11/14/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

2/6



# MATERIAL SAFETY DATA SHEET GRV-NP-069-BMX-Nat-3W

Version Number 1.0 Revision Date 03/24/2004 Page 3 of 6 Print Date 11/14/2011

8. E	XPOSURE	CONTROLS / PERSO	NAL I	PROTECTION		
Respiratory protection : No personal respiratory protective equipment normally required.					equired.	
Eye/Face Protection	: 5	afety glasses with side-sl	hields.			
Hand protection	: F	Protective gloves.				
Skin and body protection	: I	long sleeved clothing.				
Additional Protective Measures	: \$	afety shoes.				
General Hygiene Considerations		Handle in accordance with Vash hands before breaks				afety practice
Engineering measures		Heat only in areas with ap ppropriate exhaust ventile			lation.	Provide
Exposure limit(s)						
Components	Value	Exposure time		Exposure ty	pe	List:
Barium sulfate	10 mg/m3	3 Time Weighted Average		Total dust	-	ACGIH
	5 mg/m3	(TWA): PEL:		Respirable frac	ction.	OSHA Z1
	15 mg/m3	PEL:		Total dust		OSHA Z1
Tungsten	5 mg/m3			as W		ACGIH
	10 mg/m3	Short Term Exposure L (STEL):	Limit	as W		ACGIH
		CAL AND CHEMICAL	DDO	DEDUTE		
	9. 11131	CAL AND CHEMICAL	I PRO	PERIIES		
Form	: Soli				: Not	applicable
Appearance				c Gravity:		determined
Color			Bulk de			established
Odor	•			oressure		applicable
Melting point/range			-	density		applicable
Boiling Point: Water solubility	: Not : Inso		ьH		: Not	applicable
water solubility	. 11150	luble				
	10.	STABILITY AND REA	CTIV	ITY		
Stability	: 5	table.				
Hazardous Polymerization	1 : V	Vill not occur.				

3/6



### MATERIAL SAFETY DATA SHEET GRV-NP-069-BMX-Nat-3W

Version Number 1.0 Revision Date 03/24/2004 Page 4 of 6 Print Date 11/14/2011

Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.
7440-33-7	Tungsten	Systemic effects	Eyes, Skin, Respiratory system, blood and blood forming system.

#### Additional Health Hazard Information:

Tungsten 7440-33-7 Prolonged or repeated breathing of this material may result in chronic bronchitis. Exposure to freshly formed fumes from heated metal may cause "metal fume fever".

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



### MATERIAL SAFETY DATA SHEET GRV-NP-069-BMX-Nat-3W

Version Number 1.0 Revision Date 03/24/2004 Page 5 of 6 Print Date 11/14/2011

	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Extr	remely Hazardous Substance
Not applicable	
SARA Title III Section 313 Tox	ic Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Releas	se Inventory (NPRI)
Not applicable	
WHMIS Classification	: Not controlled.
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	



### MATERIAL SAFETY DATA SHEET GRV-NP-069-BMX-Nat-3W

Version Number 1.0 Revision Date 03/24/2004 Page 6 of 6 Print Date 11/14/2011

China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.