

MATERIAL SAFETY DATA SHEET

MC30N

Version Number 1.0 Revision Date 04/20/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone : Emergency telephone : number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MC30N
Product code	:	EM10006125
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Zinc oxide	1314-13-2	1 - 5
Distillates, petroleum, solvent-refined heavy	64741-96-4	1 - 5
naphthenic		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure Medical Conditions Aggravated by Exposure:	Refer to Section 11 for Toxicological Information.None known.
88 ···································	



MATERIAL SAFETY DATA SHEET **MC30N**

Version Number 1.0 Revision Date 04/20/2004 Page 2 of 6 Print Date 11/14/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit	•	Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	÷	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET **MC30N**

Version Number 1.0 Revision Date 04/20/2004 Page 3 of 6 Print Date 11/14/2011

8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection		lo personal respiratory protect		equired.
Eye/Face Protection	: S	afety glasses with side-shields	5.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and		afety practice.
Engineering measures		leat only in areas with approp ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Zinc oxide	10 mg/m3	Time Weighted Average (TWA):	Total dust. as Zn	ACGIH
	5 mg/m3	PEL:	Respirable dust. as Zn	OSHA Z1
	15 mg/m3	PEL:	Total dust. as Zn	OSHA Z1
	2 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
	2 mg/m3	• •		
	10 mg/m3	(TWA): Short Term Exposure Limit	Respirable fraction.	ACGIH
Distillates, petroleum,	10 mg/m3	(TWA):	-	ACGIH OSHA Z1
Distillates, petroleum, solvent-refined heavy		(TWA): Short Term Exposure Limit (STEL):	Respirable fraction. Vapor.	
	10 mg/m3 500 ppm	(TWA): Short Term Exposure Limit (STEL):	-	
solvent-refined heavy	10 mg/m3 500 ppm 2,000 mg/m3	(TWA): Short Term Exposure Limit (STEL):	Vapor.	
solvent-refined heavy naphthenic	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PRO	Vapor. DPERTIES	OSHA Z1
solvent-refined heavy naphthenic	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC : Solid	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PRO	Vapor. OPERTIES oration rate : Not a	
solvent-refined heavy	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC : Solid : Pelle	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PR(L Evapo tts, slabs Specifi	Vapor. OPERTIES oration rate : Not fic Gravity: : Not	OSHA Z1
solvent-refined heavy naphthenic Form Appearance	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC : Solic : Pelle : NO	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PRO tests, slabs PIGMENT Bulk of Specific Specific Bulk of Specific Spe	Vapor. OPERTIES oration rate : Not fic Gravity: : Not density : Not	OSHA Z1 applicable determined
solvent-refined heavy naphthenic Form Appearance Color Odor Melting point/range	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC : Solid : Pelle : NO : Very : Not	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PRO d Evapo ets, slabs Specif PIGMENT Bulk of r faint Vapor determined Vapor	Vapor. OPERTIES Oration rate : Not a fic Gravity: : Not a ensity : Not a or pressure : Not a ir density : Not a	OSHA Z1 applicable determined established applicable applicable
solvent-refined heavy naphthenic Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC : Solid : Pelle : NO I : Very : Not i : Not i	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PRO I Evapor ets, slabs Specif PIGMENT Bulk of r faint Vapor determined Vapor applicable pH	Vapor. OPERTIES Oration rate : Not a fic Gravity: : Not a ensity : Not a or pressure : Not a ir density : Not a	OSHA Z1 applicable determined established applicable
solvent-refined heavy naphthenic Form Appearance Color Odor Melting point/range	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC : Solid : Pelle : NO : Very : Not	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PRO I Evapor ets, slabs Specif PIGMENT Bulk of r faint Vapor determined Vapor applicable pH	Vapor. OPERTIES Oration rate : Not a fic Gravity: : Not a ensity : Not a or pressure : Not a ir density : Not a	OSHA Z1 applicable determined established applicable applicable
solvent-refined heavy naphthenic Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 500 ppm 2,000 mg/m3 9. PHYSIC : Solid : Pelle : NO 1 : Very : Not : Insol	(TWA): Short Term Exposure Limit (STEL): PEL: CAL AND CHEMICAL PRO I Evapor ets, slabs Specif PIGMENT Bulk of r faint Vapor determined Vapor applicable pH	Vapor. OPERTIES oration rate : Not fic Gravity: : Not density : Not pressure : Not ir density : Not : Not : Not	OSHA Z1 applicable determined established applicable applicable



MATERIAL SAFETY DATA SHEET **MC30N**

Version Number 1.0 Revision Date 04/20/2004		Page 4 of 6 Print Date 11/14/2011
Hazardous Polymerization	: Will not occur.	

Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1314-13-2	Zinc oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1314-13-2	Zinc oxide	LC50	2500 mg/m3	mouse
		Oral LD50	7,950 mg/kg	mouse

	COLOGICAL INFOR	RMATION
Persistence and degradability	ot readily biodegradable	
Environmental Toxicity	nemicals are not readily the polymer.	available as they are bound within the matrix
Bioaccumulation Potential	nemicals are not readily the polymer.	available as they are bound within the matrix
Additional advice	ot applicable	
	ISPOSAL CONSIDE	RATIONS
Product	ssible recycling is prefe nerator of waste materia assification, transportation	lastics the product can be recycled. Where pred to disposal or incineration. The al has the responsibility for proper waste on and disposal in accordance with rovincial and local regulations.
Contaminated packaging		en possible. The generator of waste materia proper waste classification, transportation



MATERIAL SAFETY DATA SHEET **MC30N**

Version Number 1.0 Revision Date 04/20/2004

Page 5 of 6 Print Date 11/14/2011

and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified a	s hazardous based on components.
----------------------------	----------------------------------

TSCA Status	:	All components of this product are listed on or exempt from the TSCA
		Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : This product does not contain a substance listed by California Prop 65. 65

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ZINC COMPOUNDS	1314-13-2	1.99
	67762-34-9	0.50

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Zinc oxide	1314-13-2	1.99	241
Fatty acids, C8-18 and C18-unsatd., zinc salts	67762-34-9	0.50	241



MATERIAL SAFETY DATA SHEET **MC30N**

Version Number 1.0 Revision Date 04/20/2004		Print Date	Page 6 of 6 11/14/2011		
WHMIS Classification	:	Not controlled.			
DSL	:	All components of this product are on the Canadian Domes Substances List (DSL) or are exempt.	tic		
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Listed			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			
16. OTHER INFORMATION					

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.