MATERIAL SAFETY DATA SHEET ONFLEX-V EXP 800-254-1

Version Number 1.0 Revision Date 05/19/2005

Page 1 of 6 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ONFLEX-V EXP 800-254-1
Product code	:	EM10008574
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Distillates, petroleum, solvent-refined heavy naphthenic	64741-96-4	5 - 10
Talc	14807-96-6	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET ONFLEX-V EXP 800-254-1

Version Number 1.0 Revision Date 05/19/2005 Page 2 of 6 Print Date 11/18/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET ONFLEX-V EXP 800-254-1

Version Number 1.0 Revision Date 05/19/2005 Page 3 of 6 Print Date 11/18/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Talc 2 mg/m3		Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
	0.1 mg/m3	Time Weighted Average	Respirable.	Z3
		(TWA):		
	0.3 mg/m3	Time Weighted Average	Total dust.	Z3
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Distillates, petroleum,	500 ppm	PEL:	Vapor.	OSHA Z1
solvent-refined heavy	2,000			
naphthenic	mg/m3			

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets, Slabs
 NO PIGMENT
 Very faint
 Not determined
 Not applicable
 Insoluble

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

PolyOne

MATERIAL SAFETY DATA SHEET ONFLEX-V EXP 800-254-1

Version Number 1.0 Revision Date 05/19/2005

_

Page 4 of 6 Print Date 11/18/2011

	1	0. STABILITY AND REACTIVITY
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	0	Themical Name	Effect	Target Organ		
13463-67-7	Titaniu	ım dioxide	Systemic effects	Respiratory system.		
14807-96-6	Talc		Systemic effects	Eyes, Respiratory system, Skin		
		12. ECOLOGIO	CAL INFORMATION	1		
Persistence and degra	adability	: Not readily bi	odegradable.			
Environmental Toxic	city		: Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Potential			Chemicals are not readily available as they are bound within the polymer matrix.			
Additional advice		: Not applicabl	Not applicable			
		13. DISPOSAL	CONSIDERATIONS			
Product		possible recyc generator of v classification,	cling is preferred to dis waste material has the r	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.		
Contaminated packaging		has the respon	nsibility for proper was n accordance with app	e. The generator of waste material te classification, transportation licable federal, state/provincial		

PolyOne.

MATERIAL SAFETY DATA SHEET ONFLEX-V EXP 800-254-1

Version Number 1.0 Revision Date 05/19/2005

Page 5 of 6 Print Date 11/18/2011

	14. TRANSPORT	INFORMATION			
U.S. DOT Classification	: Not regulated for	r transportation.			
ICAO/IATA (air)	: Refer to specific	regulation.			
IMO / IMDG (maritime)	: Refer to specific	regulation.			
	15. REGULATOR	Y INFORMATION			
US Regulations:					
OSHA Status	· Classified as haz	ardous based on com	nonents		
			-		
TSCA Status	: All components Inventory.	of this product are lis	ted on or exemp	pt from the TSCA	
US. EPA CERCLA Hazardo	us Substances (40 CFR 3	02)			
Not applicable					
California Proposition 65	n : Not applicable				
SARA Title III Section 302 Extremely Hazardous Substance Not applicable					
SARA Title III Section 313 Toxic Chemicals:					
Not applicable					
Canadian Regulations:					
National Pollutant Release Inventory (NPRI)					
Chemical Name CAS-No. Weight % NPRI ID#					
Zinc oxide		1314-13-2	0.49	231	
WHMIS Classification : D2A					
WHMIS Ingredient Disclosure List					
CAS-No. 14807-96-6					
	1				

PolyOne

MATERIAL SAFETY DATA SHEET ONFLEX-V EXP 800-254-1

Version Number 1.0 Revision Date 05/19/2005 Page 6 of 6 Print Date 11/18/2011

DSL	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.