## MATERIAL SAFETY DATA SHEET **PP-15CUF-25MN/000 WHITE**

Version Number 1.0 Revision Date 06/27/2005 Page 1 of 7 Print Date 11/18/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PP-15CUF-25MN/000 WHITE
Product code	:	EM10008733
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Copper	7440-50-8	10 - 30
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Eyes, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Avoid skin contact. Product contains unreacted organic peroxides which may cause mild skin irritation.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET PP-15CUF-25MN/000 WHITE

Version Number 1.0 Revision Date 06/27/2005 Page 2 of 7 Print Date 11/18/2011

Aggravated by Exposure:	bronchitis, etc.) may be adversely affected by any airborne contaminan
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne</li> </ul>
Unusual Fire/Explosion Hazards	<ul> <li>contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

**POLYONE CORPORATION** 

PolyOne.

# MATERIAL SAFETY DATA SHEET PP-15CUF-25MN/000 WHITE

Version Number 1.0 Revision Date 06/27/2005 Page 3 of 7 Print Date 11/18/2011

torage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. Keep away from heat. Excessive storage temperature and humidity can degrade product performance. Store below 149 °F (65 °C). Rotate stock. Product shelf life is normally 1 year maximum.
8. EXPOSU	UF	RE CONTROLS / PERSONAL PROTECTION
espiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
ye/Face Protection	:	Safety glasses with side-shields.
and protection	:	Protective gloves.
kin and body protection	:	Long sleeved clothing.
dditional Protective leasures	:	Safety shoes.
eneral Hygiene onsiderations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
ngineering measures	:	Heat only in areas with appropriate exhaust ventilation. During processing and cross-linking, product can give off by-products such as alcohols, acetophenone, alpha-methylstyrene, acetone, methane, and ethane. By-product vapors may be flammable. User must provide necessary precautions such as adequate ventilation to prevent accumulation and ignition of vapors. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
dditional Protective leasures eneral Hygiene onsiderations	: :	Safety shoes. Handle in accordance with good industrial hygiene and safe Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. Do processing and cross-linking, product can give off by-produ alcohols, acetophenone, alpha-methylstyrene, acetone, met ethane. By-product vapors may be flammable. User must p necessary precautions such as adequate ventilation to preve accumulation and ignition of vapors. Adequate ventilation appropriate respiratory protection may also be necessary to

Exposure limit(s)

## MATERIAL SAFETY DATA SHEET PP-15CUF-25MN/000 WHITE

Version Number 1.0 Revision Date 06/27/2005

#### Page 4 of 7 Print Date 11/18/2011

Components	Value	Exposure time	Exposure type	List:
Copper	1 mg/m3	PEL:	Dust and mist. as Cu	OSHA Z1
	0.2 mg/m3	Time Weighted Average (TWA):	Fume. as Cu	ACGIH
	1 mg/m3	Time Weighted Average (TWA):	Dust and mist. as Cu	ACGIH
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Solid : Pellets : WHITE : characteristic : Not determined : Not applicable : Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pН
- Not applicable : Not determined :
- : Not established
- : Not applicable : Not applicable
- : Not applicable

### **10. STABILITY AND REACTIVITY**

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	strong acids, oxidizing agents, reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Traces of alcohols, acetophenone, alpha-methylstyrene, acetone, methane, ethane, or other byproducts may be liberated during processing or decomposition.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7440-50-8	Copper	Irritant	Respiratory system.

PolyOne

MATERIAL SAFETY DATA SHEET PP-15CUF-25MN/000 WHITE

Version Number 1.0

Page 5 of 7 Print Date 11/18/2011

Revision Date 06/27/2005

			Systemic effects	Eyes, Skin, Respiratory syste Liver, Kidney.	
12001-26-2	Mica		Systemic effects	Respiratory system.	
13463-67-7	Titanium	n dioxide	Systemic effects	Respiratory system.	
		12. ECOLOG	ICAL INFORMATION	I	
Persistence and degrad	lability	: Not readily	biodegradable.		
Environmental Toxicit	У	: Chemicals a polymer ma		as they are bound within the	
Bioaccumulation Poter	ntial	: Chemicals a polymer ma		as they are bound within the	
Additional advice		: Not applica	ble		
		13. DISPOSA	L CONSIDERATIONS	5	
Product		possible rec generator o classificatio	cycling is preferred to dis f waste material has the r	product can be recycled. When posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.	
Contaminated packaging		: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
		14. TRANSP	ORT INFORMATION		
U.S. DOT Classificatio	on	: Not regulat	ed for transportation.		
ICAO/IATA (air)		: Refer to spe	ecific regulation.		
IMO / IMDG (maritim	le)	: Refer to spe	ecific regulation.		
		15. REGULAT	FORY INFORMATION	N	
US Regulations:					
OSHA Status		: Classified a	s hazardous based on co	mponents.	
TSCA Status		: All composition Inventory.	nents of this product are l	isted on or exempt from the TSC	
US. EPA CERCLA Ha	azardous Su	ubstances (40 C	CFR 302)		

PolvOne

# MATERIAL SAFETY DATA SHEET **PP-15CUF-25MN/000 WHITE**

Version Number 1.0 Revision Date 06/27/2005 Page 6 of 7 Print Date 11/18/2011

Not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
COPPER	7440-50-8	10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Copper	7440-50-8	10.00 - 30.00	71

WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
~		

China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.

PolyOne.

# MATERIAL SAFETY DATA SHEET PP-15CUF-25MN/000 WHITE

Version Number 1.0 Revision Date 06/27/2005 Page 7 of 7 Print Date 11/18/2011