## MATERIAL SAFETY DATA SHEET **GF 600 A 15 HS UV NATURAL**

Version Number 1.3 Revision Date 03/20/2014 Page 1 of 6 Print Date 3/23/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GF 600 A 15 HS UV NATURAL
Product code	:	EM10010380
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Glass, oxide	65997-17-3	10 - 30
Caprolactam	105-60-2	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET **GF 600 A 15 HS UV NATURAL**

Version Number 1.3 Revision Date 03/20/2014 Page 2 of 6 Print Date 3/23/2014

Medical Conditions Aggravated by Exposure:	: None known.					
	4. FIRST AID MEASURES					
Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.						
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.					
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.					
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.					
	5. FIREFIGHTING MEASURES					
Flash point	: not applicable					
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>					
	6. ACCIDENTAL RELEASE MEASURES					
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.					
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.					
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.					
	7. HANDLING AND STORAGE					
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.					

PolyOne

### **MATERIAL SAFETY DATA SHEET** GF 600 A 15 HS UV NATURAL

Version Number 1.3 Revision Date 03/20/2014

\_

Page 3 of 6 Print Date 3/23/2014

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Caprolactam	5 mg/m3	Time Weighted Average	Inhalable fraction and	ACGIH
		(TWA):	vapor	
	1 mg/m3	Time Weighted Average	Dust.	MX OEL
		(TWA):		
	5 ppm 20	Time Weighted Average	Vapor.	MX OEL
	mg/m3	(TWA):		
	3 mg/m3	Short Term Exposure Limit	Dust.	MX OEL
		(STEL):		
	10 ppm 40	Short Term Exposure Limit	Vapor.	MX OEL
	mg/m3	(STEL):		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range **Boiling Point:** Water solubility
- : solid pellets, Slabs NO PIGMENT very faint Not determined not applicable : insoluble

:

:

:

:

:

- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pН
- Not applicable : Not determined Not established : not applicable : not applicable : not applicable

:

:

#### **10. STABILITY AND REACTIVITY**

Stability

: The product is stable if stored and handled as prescribed.

## MATERIAL SAFETY DATA SHEET **GF 600 A 15 HS UV NATURAL**

Version Number 1.3 Revision Date 03/20/2014 Page 4 of 6 Print Date 3/23/2014

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
105-60-2	Caprolactam	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, Liver, Kidney, central nervous system (CNS), heart or circulatory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
105-60-2	Caprolactam	LC50	300 mg/m3	rat
		Oral LD50	1,210 mg/kg	rat
		Dermal LD50	1410 ul/kg	rabbit

## 12. ECOLOGICAL INFORMATION

Additional advice	:	not applicable
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Persistence and degradability	:	Not readily biodegradable.

#### **13. DISPOSAL CONSIDERATIONS**

Product

: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste

POLYONE CORPORATION

PolyOne.

# MATERIAL SAFETY DATA SHEET **GF 600 A 15 HS UV NATURAL**

sion Number 1.3 vision Date 03/20/2014		Page 5 of 6 Print Date 3/23/2014
		classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Refer to specific regulation.
IMO/IMDG (maritime)	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Sub	stances (40 CFR 302)
not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 Ex	trem	ely Hazardous Substance
Unless specific chemicals are	identi	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic C	Chemicals:
Unless specific chemicals are	identi	fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:		

PolyOne

## MATERIAL SAFETY DATA SHEET **GF 600 A 15 HS UV NATURAL**

Version Number 1.3 Revision Date 03/20/2014 Page 6 of 6 Print Date 3/23/2014

Chemical Name			CAS-No.	Weight	NPRI ID#
				percent	
Zinc stearate			557-05-1	0.10 - 1.00	
WHMIS Classification	n :	D1A			
WHMIS Ingredient Di	sclosı	ire List			
CAS-No.					
105-60-2					
DSL	:			are on the Canadia	n Domestic
		Substances Lis	t (DSL) or are ex	empt.	
tional Inventories:					
Australia AICS	:	Not determined	1		
China IECS	:	Not determined	1		
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined	l		
Korea KECI	:	Not determined	l		
Philippines PICCS	:	Not determined	1		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.