MATERIAL SAFETY DATA SHEET XT-500-BX00-FR NATURAL

Version Number 1.2 Revision Date 05/12/2008 Page 1 of 6 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	XT-500-BX00-FR NATURAL
Product code	:	EM10010990
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET XT-500-BX00-FR NATURAL

Version Number 1.2 Revision Date 05/12/2008 Page 2 of 6 Print Date 1/3/2012

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit	•	Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET XT-500-BX00-FR NATURAL

Version Number 1.2 Revision Date 05/12/2008 Page 3 of 6 Print Date 1/3/2012

8	EXPOSURE	CONTROLS/PEI	RSONAL I	PROTECTION	
Respiratory protection	: N	o personal respirato	ory protecti	ve equipment normal	lly required.
Eye/Face Protection	: S	afety glasses with s	ide-shields		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothin	g		
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations				industrial hygiene a eaks and at the end o	
Engineering measures		eat only in areas wi		ate exhaust ventilation at machinery.	on. Provide
Exposure limit(s)					
Components	Value	Exposure ti	me	Exposure type	List:
Antimony trioxide	0.5 mg/m3	Time Weighted (TWA):		as Sb	MX OEL
	0.5 mg/m3	Time Weighted (TWA):	-	as Sb	ACGIH
	0.5 mg/m3	PEL:		as Sb	OSHA Z1
	0.5 mg/m3				
	Č –	CAL AND CHEMI	ICAL PRO	PERTIES	
Form	9. PHYSIC				Not applicable
	9. PHYSIC : Solid		Evapor	ration rate : 1	Not applicable Not determined
Form Appearance Color	9. PHYSIC : Solid : pelle		Evapor Specifi	ration rate : 1 c Gravity : 1	Not applicable Not determined Not established
Appearance	9. PHYSIC : Solid : pelle : NO I	ts, Slabs PIGMENT	Evapor Specifi Bulk de	ation rate : 1 c Gravity : 1 ensity : 1	Not determined Not established
Appearance Color Odour	9. PHYSIC : Solid : pelle : NO F : Very	ts, Slabs PIGMENT	Evapor Specifi Bulk de Vapour	ation rate : 1 c Gravity : 1 ensity : 1 r pressure : 1	Not determined Not established Not applicable
Appearance Color	9. PHYSIC : Solid : pelle : NO F : Very : Not o	ts, Slabs PIGMENT faint	Evapor Specifi Bulk de Vapour	ration rate : 1 c Gravity : 1 ensity : 1 r pressure : 1 r density : 1	Not determined Not established
Appearance Color Odour Melting point/range	9. PHYSIC : Solid : pelle : NO F : Very : Not o	ts, Slabs PIGMENT faint letermined upplicable	Evapor Specifi Bulk de Vapour Vapour	ration rate : 1 c Gravity : 1 ensity : 1 r pressure : 1 r density : 1	Not determined Not established Not applicable Not applicable
Appearance Color Odour Melting point/range Boiling Point:	9. PHYSIC : Solid : pelle : NO F : Very : Not c : Not a : Insol	ts, Slabs PIGMENT faint letermined upplicable	Evapoi Specifi Bulk de Vapour Vapour pH	ation rate : 1 c Gravity : 1 ensity : 1 r pressure : 1 r density : 1 : 1	Not determined Not established Not applicable Not applicable
Appearance Color Odour Melting point/range Boiling Point:	9. PHYSIC : Solid : pelle : NO F : Very : Not c : Not a : Insol 10. S	ts, Slabs PIGMENT faint letermined applicable uble	Evapoi Specifi Bulk de Vapour Vapour pH	ation rate : 1 c Gravity : 1 ensity : 1 r pressure : 1 r density : 1 : 1	Not determined Not established Not applicable Not applicable
Appearance Color Odour Melting point/range Boiling Point: Water solubility	9. PHYSIC : Solid : pelle : NO H : Very : Not c : Not a : Insol 10. S	ts, Slabs PIGMENT faint letermined upplicable uble TABILITY AND	Evapoi Specifi Bulk de Vapour Vapour pH	ation rate : 1 c Gravity : 1 ensity : 1 r pressure : 1 r density : 1 : 1	Not determined Not established Not applicable Not applicable
Appearance Color Odour Melting point/range Boiling Point: Water solubility Stability	9. PHYSIC : Solid : pelle : NO F : Very : Not c : Not a : Insol 10. S n : W	ts, Slabs PIGMENT faint letermined upplicable uble TABILITY AND table.	Evapor Specifi Bulk d Vapour Vapour pH	ration rate :] c Gravity :] ensity :] r pressure :] r density :] :] ITY	Not determined Not established Not applicable Not applicable

MATERIAL SAFETY DATA SHEET XT-500-BX00-FR NATURAL

Version Number 1.2 Revision Date 05/12/2008 Page 4 of 6 Print Date 1/3/2012

Hazardous decomposition : C products (1

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.

PolyOne.

MATERIAL SAFETY DATA SHEET XT-500-BX00-FR NATURAL

Version Number 1.2 Revision Date 05/12/2008 Page 5 of 6 Print Date 1/3/2012

Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ex	tremely Hazardous Substance
	dentified under this section, this product is Not Applicable under this regula

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET XT-500-BX00-FR NATURAL

Version Number 1.2 Revision Date 05/12/2008		Pag Print Date 1	ge 6 of
			/3/2011
SARA Title III Section 313 T	oxic Chemicals:		
		· · · · · · · · · · · · · · · · · · ·	1
Chemical Name	identified under this section, this	is product is Not Applicable under this re CAS-No. Weight %	gulation
ANTIMONY COMPOUN	DS	1309-64-4 1.00 - 5.00	
Canadian Regulations:			
National Pollutant Rel	ease Inventory (NPRI)		
Not applicable			
WHMIS Classification	n : D2A		
WHMIS Ingredient Di	sclosure List		
CAS-No. 1309-64-4			
DSL	Inventories or are exemp product is on the Canadi	of this product are listed on the Canadian pt. However, at least one component of th ian Non-Domestic Substances List (NDS) is restricted by regulations.	
National Inventories:			
Australia AICS	: Listed		
China IECS	: Not determined		
Europe EINECS	: Not determined		
Japan ENCS	: Not determined		
Korea KECI	: Not determined		
Philippines PICCS	: Not determined		
	16. OTHER INFORM	IATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.