PolyOne

# MATERIAL SAFETY DATA SHEET **143-034**

Version Number 1.2 Revision Date 03/17/2014

Page 1 of 7 Print Date 3/21/2014

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE		
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	143-034		
Product code	:	EM10011094		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

Components	CAS-No.	Weight percent	
Talc	14807-96-6	0.1 - 1	

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Eyes, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Avoid skin contact. Product contains unreacted organic peroxides which may cause mild skin irritation.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET **143-034**

ion Number 1.2 sion Date 03/17/2014	Page 2 Print Date 3/21/2
Medical Conditions Aggravated by Exposure:	: Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>not applicable</li> <li>not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne</li> </ul>
Unusual Fire/Explosion Hazards	<ul> <li>contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat



# MATERIAL SAFETY DATA SHEET **143-034**

/ersion Number 1.2 Revision Date 03/17/2014		Page 3 of 7 Print Date 3/21/2014
Storage	:	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. Keep away from heat. Excessive storage temperature and humidity can degrade product performance. Store below 149 °F (65 °C). Rotate stock. Product shelf life is normally 1 year maximum.
8. EXI	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. During processing and cross-linking, product can give off by-products such as alcohols, acetophenone, alpha-methylstyrene, acetone, methane, and ethane. By-product vapors may be flammable. User must provide necessary precautions such as adequate ventilation to prevent accumulation and ignition of vapors. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
Exposure limit(s)		

PolyOne

### **MATERIAL SAFETY DATA SHEET** 143-034

#### Version Number 1.2 Revision Date 03/17/2014

#### Page 4 of 7 Print Date 3/21/2014

Components	Value	Exposure time	Exposure type	List:
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	2 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	2 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Colour
Odour
Melting point/range
Boiling Point:
Water solubility

#### : pellets : NO PIGMENT : characteristic : Not determined : not applicable : insoluble

: solid

#### Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density

pН

- : Not determined : Not established : not applicable not applicable :
  - not applicable :

: Not applicable

### **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, Oxidizing agents, Reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Traces of alcohols, acetophenone, alpha-methylstyrene, acetone, methane, ethane, or other byproducts may be liberated during processing or decomposition.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.

PolyOne.

# MATERIAL SAFETY DATA SHEET **143-034**

Version Number 1.2 Revision Date 03/17/2014 Page 5 of 7 Print Date 3/21/2014

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14807-96-6	Talc	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	

PolyOne.

# MATERIAL SAFETY DATA SHEET **143-034**

Version Number 1.2 Revision Date 03/17/2014		Page 6 of 7 Print Date 3/21/2014
OCULA Status		Classified as housed an expression of
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	ubs	stances (40 CFR 302)
not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 Extre	em	ely Hazardous Substance
Unless specific chemicals are ide	enti	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 Toxi	c C	Chemicals:
Unless specific chemicals are ide	enti	fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:		
National Pollutant Release	e Ir	nventory (NPRI)
not applicable		
WHMIS Classification	:	D2A
DSL	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined

PolyOne

# MATERIAL SAFETY DATA SHEET **143-034**

Version Number 1.2 Revision Date 03/17/2014

Page 7 of 7 Print Date 3/21/2014

Philippines PICCS

: Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.