MATERIAL SAFETY DATA SHEET AT-0522072 BLACK

Version Number 1.0 Revision Date 06/29/2007

Page 1 of 7 Print Date 11/29/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	AT-0522072 BLACK
Product code	:	EM10013150
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium stearate	1592-23-0	1 - 5
Carbon black	1333-86-4	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	outes of Exposure: : Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Particulates, like other inert materials can be mechanically irritating. If overheated or burnt, the polymer releases formaldehyde.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Particulates, like other inert materials can be mechanically irritating.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET AT-0522072 BLACK

Version Number 1.0 Revision Date 06/29/2007 Page 2 of 7 Print Date 11/29/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May burn with invisible flame.
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Open container only in a well-ventilated area. Heat only in areas with



MATERIAL SAFETY DATA SHEET **AT-0522072 BLACK**

Version Number 1.0		Page 3 of 7
Revision Date 06/29/2007		Print Date 11/29/2011
Storage	:	appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
		and containination. Keep in a dry, coor place.
8. EXPOS	SUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. When temperatures exceed 230°C (446°F) and ventilation is inadequate to maintain concentrations below exposure limits, use a positive air supplied respirator. Air purifying respirators may not provide adequate protection.
Eye/Face Protection	:	Safety glasses with side-shields Wear face-shield and protective suit for abnormal processing problems.
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium stearate	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Carbon black	3.5 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	7 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range
- : Solid
 : pellets, Slabs
 : BLACK
 : formaldehyde
 : Not determined
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicableNot determinedNot establishedNot applicableNot applicable

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET AT-0522072 BLACK

Version Number 1.0 Revision Date 06/29/2007 Page 4 of 7 Print Date 11/29/2011

Water solubility	: Insoluble		
	10. STABILITY ANI	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid			30°C (446°F). Avoid prolonged ocessing temperature.
Incompatible Materials	(decomposes to for resins are incompat (PVC) and any elas processing condition involve rapid degra can cause sudden a Workplace fume w pressurization of econ Thoroughly purges avoid even trace qu	m formaldehyde). A tible with halogenate stomers containing a ons, these materials a adation. Even small a nd spontaneous form ell above threshold I quipment such as ext and mechanically cle antities of halogena	with strong acids and bases at melt temperatures, acetal ed polymers such as vinyl ny halogenated polymers. At are mutually destructive and amounts of such contaminants naldehyde gas formation. evels are a likely result. Unsafe truder or mold can also result. ean processing equipment to ted materials from coming in ination of virgin or rework
Hazardous decomposition products	(NOx), other hazar overheated or burn Decomposition of t exposed to elevated temperature of 210 not be significant u	dous materials, and s t, the polymer releas this material depends d temperatures. At th °C-220°C (410°F-42 ntil after 30 minutes	de (CO), oxides of nitrogen smoke are all possible. If es formaldehyde. s on the lenght of time it is recommended processing 28°F), decomposition should b. Decomposition may be and/or other additives.
	11. TOXICOLOGICAI	L INFORMATION	

health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species

PolvOne.

MATERIAL SAFETY DATA SHEET AT-0522072 BLACK

Version Number 1.0 Revision Date 06/29/2007 Page 5 of 7 Print Date 11/29/2011

1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Like most thermoplastic plastics the product can be recycled. When possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
× ,	

PolyOne.

MATERIAL SAFETY DATA SHEET AT-0522072 BLACK

Version Number 1.0 Revision Date 06/29/2007

Page 6 of 7 Print Date 11/29/2011

	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	bus Substances (40 CFR 302)
Not applicable	
California Propositio 65	on : Not applicable
SARA Title III Section 302	Extremely Hazardous Substance
Unless specific chemicals ar	re identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313	Toxic Chemicals:
Unless specific chemicals ar	re identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Re	elease Inventory (NPRI)
Not applicable	
WHMIS Classificati	on : D2A
WHMIS Ingredient I	Disclosure List
CAS-No. 1333-86-4	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed

PolyOne

MATERIAL SAFETY DATA SHEET AT-0522072 BLACK

Version Number 1.0 Revision Date 06/29/2007 Page 7 of 7 Print Date 11/29/2011

China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.