PolvOne

MATERIAL SAFETY DATA SHEET LC-20NCF/000 V3 RD 4020

Version Number 1.1 Revision Date 09/18/2007 Page 1 of 7 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LC-20NCF/000 V3 RD 4020
Product code	:	EM10013436
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon	7440-44-0	10 - 30
Iron oxide	1309-37-1	5 - 10
Nickel	7440-02-0	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact
 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET LC-20NCF/000 V3 RD 4020

Version Number 1.1 Revision Date 09/18/2007 Page 2 of 7 Print Date 12/1/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

PolvOne

MATERIAL SAFETY DATA SHEET LC-20NCF/000 V3 RD 4020

Version Number 1.1 Revision Date 09/18/2007 Page 3 of 7 Print Date 12/1/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment normally required	d.
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety pr Wash hands before breaks and at the end of workday.	ractice.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provid appropriate exhaust ventilation at machinery.	le

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average	as Fe	MX OEL
		(TWA):		
	10 mg/m3	Short Term Exposure Limit	as Fe	MX OEL
		(STEL):		
Nickel	1.5 mg/m3	Time Weighted Average	Inhalable fraction.	ACGIH
		(TWA):		
	1 mg/m3	PEL:	as Ni	OSHA Z1
	1 mg/m3	Time Weighted Average		MX OEL
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
 pellets, Slabs
 NO PIGMENT
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

hlvUn<u>e</u>

MATERIAL SAFETY DATA SHEET LC-20NCF/000 V3 RD 4020

Version Number 1.1 Revision Date 09/18/2007

Page 4 of 7 Print Date 12/1/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Strong acids, oxidizing and reducing agents
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7440-44-0	Carbon	Systemic effects	Respiratory system, heart or
			circulatory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
7440-02-0	Nickel	Systemic effects	Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
7440-02-0	Nickel	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Nickel 7440-02-0 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney and muscle effects

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

PolyOne.

MATERIAL SAFETY DATA SHEET LC-20NCF/000 V3 RD 4020

sion Number 1.1 ision Date 09/18/2007			Page 5 Print Date 12/1/2
Environmental Toxicity		cals are not readily avai er matrix.	lable as they are bound within the
Bioaccumulation Potential		cals are not readily avai er matrix.	lable as they are bound within the
Additional advice	: Not ap	plicable	
	13. DISP	OSAL CONSIDERAT	IONS
Product	possibl generat classifi	e recycling is preferred tor of waste material has cation, transportation an	cs the product can be recycled. Where to disposal or incineration. The s the responsibility for proper waste ad disposal in accordance with accial and local regulations.
Contaminated packaging	has the and dis	responsibility for prope	ossible. The generator of waste materia er waste classification, transportation h applicable federal, state/provincial
	14. TRA	NSPORT INFORMAT	TION
U.S. DOT Classification	: Not res	gulated for transportatio	n.
ICAO/IATA (air)		o specific regulation.	
IMO / IMDG (maritime)	: Refer t	o specific regulation.	
	15. REGU	LATORY INFORMA	TION
US Regulations:			
OSHA Status	: Classif	ied as hazardous based	on components.
TSCA Status		mponents of this produc	t are listed on or exempt from the TSCA
US. EPA CERCLA Hazard	ous Substances ((40 CFR 302)	
Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product
Nickel	7440-02-0	100 lbs	1,111 LB

PolvOne.

MATERIAL SAFETY DATA SHEET LC-20NCF/000 V3 RD 4020

Version Number 1.1 Revision Date 09/18/2007 Page 6 of 7 Print Date 12/1/2011

65

California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name C	CAS-No.	Weight %
NICKEL 74	7440-02-0	5.00 - 10.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Nickel	7440-02-0	5.00 - 10.00	168

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1309-37-1	
7440-02-0	

DSL

: DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET LC-20NCF/000 V3 RD 4020

Version Number 1.1 Revision Date 09/18/2007 Page 7 of 7 Print Date 12/1/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.