MATERIAL SAFETY DATA SHEET AT-000/000 HI5 NATURAL NA

Version Number 1.1 Revision Date 11/30/2009 Page 1 of 6 Print Date 1/9/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:		Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	AT-000/000 HI5 NATURAL NA
Product code	:	EM10013437
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent	
Calcium stearate	1592-23-0	1 - 5	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. If overheated or burnt, the polymer releases formaldehyde.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **AT-000/000 HI5 NATURAL NA**

Version Number 1.1 Revision Date 11/30/2009 Page 2 of 6 Print Date 1/9/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May burn with invisible flame.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET **AT-000/000 HI5 NATURAL NA**

ion Number 1.1 sion Date 11/30/2009				Pr	Page 3 int Date 1/9/2
Handling	C		ell-ventilat	ild up of electrostatic ed area. Heat only in	
Storage		eep containers dry nd contamination.		closed to avoid moist ry, cool place.	ure absorption
8.]	EXPOSURE	CONTROLS/PE	RSONAL I	PROTECTION	
Respiratory protection	W ir P	When temperatures enadequate to mainta	exceed 230° in concentr respirator.	ve equipment normall °C (446°F) and ventila ations below exposure Air purifying respirate	ition is limits, use a
Eye/Face Protection		afety glasses with s or abnormal process		Wear face-shield and ns.	protective suit
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothin	g		
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations				l industrial hygiene an eaks and at the end of	
Engineering measures		leat only in areas w		iate exhaust ventilation at machinery.	n. Provide
Exposure limit(s)					
Components	Value	Exposure ti	me	Exposure type	List:
Calcium stearate	10 mg/m3	Time Weighted (TWA):	Average		ACGIH
	9. PHYSIC	CAL AND CHEM	ICAL PRO	PERTIES	
Form	1: 4		E	ration rate N	ot applies 1-1-
Form Appearance	: solid	ts, Slabs			ot applicable ot determined
Colour		PIGMENT	Bulk d		ot established
Odour		aldehyde			ot applicable
Melting point/range		determined			ot applicable
Boiling Point:	: not a	pplicable	pH		ot applicable
Water solubility	: insol	uble			
	10. 8	STABILITY AND	REACTIV	TTY	

PolyOne.

MATERIAL SAFETY DATA SHEET AT-000/000 HI5 NATURAL NA

Version Number 1.1 Revision Date 11/30/2009

Page 4 of 6 Print Date 1/9/2012

Stability	•	Stable			
Hazardous Polymerization	ı :	Will not occu	ır.		
Conditions to avoid	:		ymer temperature b posure at or above r		
Incompatible Materials Hazardous decomposition products	:	 Incompatible with strong oxidizers and with strong acids and bases (decomposes to form formaldehyde). At melt temperatures, acetal resins are incompatible with halogenated polymers such as vinyl (PVC) and any elastomers containing any halogenated polymers. At processing conditions, these materials are mutually destructive and involve rapid degradation. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume well above threshold levels are a likely result. Unsafe pressurization of equipment such as extruder or mold can also result. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of halogenated materials from coming in contact with the acetal. Prevent contamination of virgin or rework resin. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. Decomposition of this material depends on the lenght of time it is exposed to elevated temperatures. At the recommended processing temperature of 210°C-220°C (410°F-428°F), decomposition should not be significant until after 30 minutes. Decomposition may be accelerated by contaminants, pigments and/or other additives. 			
	11.	TOXICOLOG	ICAL INFORMA	TION	
This mixture has not been health data for the individ <u>Toxicity Overview</u> This product contains the <u>CAS-No.</u>	ual comp following	onents which co	omprise the mixture	orm have the follo	
LC50 / LD50 This product contains the			which, in their pure	·	owing toxicity data
CAS-No.	Chemical Name		Route	Value	Species
1592-23-0 C	alcium s	tearate	Oral LD50	> 10 gm/kg	rat
	1				
	1	2. ECOLOGIC	CAL INFORMAT	ION	

PolyOne.

MATERIAL SAFETY DATA SHEET **AT-000/000 HI5 NATURAL NA**

sion Number 1.1 rision Date 11/30/2009	Page 5 Print Date 1/9/2
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	is Substances (40 CFR 302)
not applicable	
California Propositior 65	n : Not applicable

MATERIAL SAFETY DATA SHEET AT-000/000 HI5 NATURAL NA

Version Number 1.1 Revision Date 11/30/2009 Page 6 of 6 Print Date 1/9/2012

SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) not applicable WHMIS Classification : Not controlled. DSL DSL status has not been determined. Quantity use in Canada may be : restricted by regulations. National Inventories: Australia AICS Not determined : China IECS Not determined : Europe EINECS : Listed Japan ENCS Not determined : Korea KECI Not determined : **Philippines PICCS** Not determined · **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.