MATERIAL SAFETY DATA SHEET XT-505GF-AU00-FR NATURAL

Version Number 1.0 Revision Date 11/27/2007 Page 1 of 6 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	XT-505GF-AU00-FR NATURAL
Product code :	EM10014145
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET XT-505GF-AU00-FR NATURAL

Version Number 1.0 Revision Date 11/27/2007 Page 2 of 6 Print Date 12/2/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	at
Skin	: Wash off with soap and plenty of water. If skin irritation persists s medical attention.	eeł
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits		
Upper explosion limit	: Not applicable	
Lower explosion limit	: Not applicable	
Autoignition temperature	: Not applicable	
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.	e
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	iot
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	t
Storage	: Keep containers dry and tightly closed to avoid moisture absorptio	n

PolyOne.

MATERIAL SAFETY DATA SHEET XT-505GF-AU00-FR NATURAL

Version Number 1.0 Revision Date 11/27/2007 Page 3 of 6 Print Date 12/2/2011

	o personal respirate	ory protecti	ve equipment normally	no quino d
: S			······································	required.
	afety glasses with s	side-shields		
: P	rotective gloves			
: L	ong sleeved clothin	ıg		
: S	afety shoes			
				afety practice
				Provide
alue	Exposure f	ime	Exposure type	List:
	Time Weighted	Average	as Sb	MX OEL
mg/m3	Time Weighted	Average	as Sb	ACGIH
mg/m3	PEL:		as Sb	OSHA Z1
PHYSIC	CAL AND CHEM	ICAL PRO	PERTIES	
· Solid	1	Evenor	ration rata · Not	applicable
				determined
				established
			2	applicable
2				applicable
		-		applicable
		r		·····
10. 5	STABILITY AND	REACTIV	TTY	
: S	table.			
: W	Vill not occur.			
• т	a avoid thormal day	composition	do not overheat	
	: S : H W : H a] alue mg/m3 mg/m3 mg/m3 mg/m3 mg/m3 PHYSIC : Solic : pelle : No I : Very : Not c : Not c : Insol 10. S : S : W	 Safety shoes Handle in accordanc Wash hands before to Wash hands before to Heat only in areas we appropriate exhaust Heat only in areas we appropriate exhaust Time Weighted (TWA): <li< td=""><td> Handle in accordance with good Wash hands before breaks and a Heat only in areas with appropria appropriate exhaust ventilation a Heat only in areas with appropria appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a It was appropriate exhaust ventilation appropriate exhaust ventilation a It will not occur. </td><td> Safety shoes Handle in accordance with good industrial hygiene and as Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. appropriate exhaust ventilation at machinery. alue Exposure time Exposure type mg/m3 Time Weighted Average as Sb (TWA): mg/m3 Time Weighted Average as Sb (TWA): mg/m3 Time Weighted Average as Sb (TWA): mg/m3 PEL: as Sb PHYSICAL AND CHEMICAL PROPERTIES Solid Evaporation rate : Not is pellets, Slabs Specific Gravity is Not is Not determined Vapour pressure is Not is Not determined Vapour density is Not is Not applicable pH is Not is Insoluble I. Stable.</td></li<>	 Handle in accordance with good Wash hands before breaks and a Heat only in areas with appropria appropriate exhaust ventilation a Heat only in areas with appropria appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a Heat only in areas with appropriation appropriate exhaust ventilation a It was appropriate exhaust ventilation appropriate exhaust ventilation a It will not occur. 	 Safety shoes Handle in accordance with good industrial hygiene and as Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. appropriate exhaust ventilation at machinery. alue Exposure time Exposure type mg/m3 Time Weighted Average as Sb (TWA): mg/m3 Time Weighted Average as Sb (TWA): mg/m3 Time Weighted Average as Sb (TWA): mg/m3 PEL: as Sb PHYSICAL AND CHEMICAL PROPERTIES Solid Evaporation rate : Not is pellets, Slabs Specific Gravity is Not is Not determined Vapour pressure is Not is Not determined Vapour density is Not is Not applicable pH is Not is Insoluble I. Stable.

MATERIAL SAFETY DATA SHEET XT-505GF-AU00-FR NATURAL

Version Number 1.0 Revision Date 11/27/2007 Page 4 of 6 Print Date 12/2/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.

PolyOne.

MATERIAL SAFETY DATA SHEET XT-505GF-AU00-FR NATURAL

Version Number 1.0 Revision Date 11/27/2007 Page 5 of 6 Print Date 12/2/2011

	polymer matrix.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext	remely Hazardous Substance

MATERIAL SAFETY DATA SHEET XT-505GF-AU00-FR NATURAL

Version Number 1.0 Revision Date 11/27/2007 Page 6 of 6 Print Date 12/2/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	1.00 - 5.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)Chemical NameCAS-No.Weight %NPRI ID#Antimony trioxide1309-64-41.00 - 5.0017

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	_
1309-64-4	
14807-96-6	

DSL

DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

:	Not determined
:	Not determined
	· : :

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.