## MATERIAL SAFETY DATA SHEET XXT-500-BU04-FR GREY

Version Number 1.0 Revision Date 05/12/2008

Page 1 of 7 Print Date 1/3/2012

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	XXT-500-BU04-FR GREY
Product code	:	EM10015144
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	0.1 - 1
Antimony trioxide	1309-64-4	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET XXT-500-BU04-FR GREY

Version Number 1.0 Revision Date 05/12/2008 Page 2 of 7 Print Date 1/3/2012

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

# MATERIAL SAFETY DATA SHEET XXT-500-BU04-FR GREY

Version Number 1.0 Revision Date 05/12/2008 Page 3 of 7 Print Date 1/3/2012

8. ]	EXPOSURE	CONTROLS/PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory protect	ive equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shields	;		
Hand protection	: Protective gloves				
Skin and body protection		ong sleeved clothing			
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations		Iandle in accordance with good ractice. Wash hands before by			
Engineering measures		Heat only in areas with appropription		Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Antimony trioxide	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL	
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH	
	0.5 mg/m3	PEL:	as Sb	OSHA Z1	
Titanium dioxide	0.5 mg/m3 10 mg/m3	PEL: Time Weighted Average (TWA):	as Sb	OSHA Z1 ACGIH	
Titanium dioxide		Time Weighted Average	as Sb Total dust.		
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH	
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average	Total dust.	ACGIH OSHA Z1	
Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Total dust. as Ti as Ti	ACGIH OSHA Z1 MX OEL	
Form	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSI0 : Solid	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Total dust. as Ti as Ti DPERTIES ration rate : Not	ACGIH OSHA Z1 MX OEL MX OEL	
Form Appearance	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : Solid : pelle	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Total dust.         as Ti         as Ti         DPERTIES         ration rate       : Not         ic Gravity       : Not	ACGIH OSHA Z1 MX OEL MX OEL	
Form Appearance Color	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : BLA	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO the Evapo ets, Slabs Specific CK Bulk of the State of th	Total dust.         as Ti         as Ti         DPERTIES         oration rate       : Not         Tic Gravity       : Not         lensity       : Not	ACGIH OSHA Z1 MX OEL MX OEL	
Form Appearance Color Odour	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : Solid : pelle : BLA : Very	Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapo         ets, Slabs       Specif         CK       Bulk of Vapor	Total dust.         as Ti         as Ti         DPERTIES         oration rate       : Not         Tic Gravity       : Not         lensity       : Not         ur pressure       : Not	ACGIH OSHA Z1 MX OEL MX OEL	
Form Appearance Color	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIO : Solid : pelle : BLA : Very : Not	Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapo         ets, Slabs       Specif         CK       Bulk of Vapor	Total dust.         as Ti         as Ti         DPERTIES         oration rate       : Not         ic Gravity       : Not         lensity       : Not         ur pressure       : Not         ur density       : Not	ACGIH OSHA Z1 MX OEL MX OEL	

## MATERIAL SAFETY DATA SHEET XXT-500-BU04-FR GREY

Version Number 1.0 Revision Date 05/12/2008 Page 4 of 7 Print Date 1/3/2012

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **Additional Health Hazard Information:**

PolyOne.

# MATERIAL SAFETY DATA SHEET XXT-500-BU04-FR GREY

Version Number 1.0 Revision Date 05/12/2008 Page 5 of 7 Print Date 1/3/2012

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. We possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

# MATERIAL SAFETY DATA SHEET XXT-500-BU04-FR GREY

Version Number 1.0 Revision Date 05/12/2008 Page 6 of 7 Print Date 1/3/2012

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation
Chemical Name
CAS-No.
Weight %

ANTIMONY COMPOUNDS	1309-64-4	1.00 - 5.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1309-64-4	

DSL

DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

:

PolyOne

## MATERIAL SAFETY DATA SHEET XXT-500-BU04-FR GREY

Version Number 1.0 Revision Date 05/12/2008 Page 7 of 7 Print Date 1/3/2012

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.