PolyOne

MATERIAL SAFETY DATA SHEET **XPS-45GF UV BLACK**

Version Number 1.3 Revision Date 03/18/2014 Page 1 of 6 Print Date 3/22/2014

1. POLYONE CORPORAT 33587 Walker Road, Avo	
Telephone Emergency telephone number	 1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name Product code Chemical Name CAS-No.	 XPS-45GF UV BLACK EM10015313 Mixture Mixture
Product Use	: Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Glass, oxide	65997-17-3	30 - 60
Carbon black	1333-86-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **XPS-45GF UV BLACK**

Version Number 1.3 Revision Date 03/18/2014 Page 2 of 6 Print Date 3/22/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne

MATERIAL SAFETY DATA SHEET **XPS-45GF UV BLACK**

Version Number 1.3 Revision Date 03/18/2014 Page 3 of 6 Print Date 3/22/2014

Storage	: Keep containers dry and tightly closed to avoid moisture abso and contamination. Keep in a dry, cool place.	rption
8. EX	SURE CONTROLS/PERSONAL PROTECTION	
Respiratory protection	: No personal respiratory protective equipment normally requir	ed.
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workda	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Prov appropriate exhaust ventilation at machinery.	ide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid
 : pellets, Slabs
 : BLACK
 : very faint
 : Not determined
 : not applicable
 : insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

MATERIAL SAFETY DATA SHEET XPS-45GF UV BLACK

Version Number 1.3 Revision Date 03/18/2014 Page 4 of 6 Print Date 3/22/2014

10. STABILITY AND REACTIVITY	
Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Strong acids, oxidizing and reducing agents
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity

: Chemicals are not readily available as they are bound within the

PolyOne.

MATERIAL SAFETY DATA SHEET **XPS-45GF UV BLACK**

Version Number 1.3 Revision Date 03/18/2014 Page 5 of 6 Print Date 3/22/2014

Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. When possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 Ex	remely Hazardous Substance

hlvUn<u>e</u>

MATERIAL SAFETY DATA SHEET **XPS-45GF UV BLACK**

Version Numb	er 1.3
Revision Date	03/18/2014

Page 6 of 6 Print Date 3/22/2014

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

:

not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1333-86-4

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.