MATERIAL SAFETY DATA SHEET **XEdgetek NT-10GF/10GP Grey**

Version Number 1.0 Revision Date 06/19/2009 Page 1 of 6 Print Date 1/8/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone : Emergency telephone :	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	XEdgetek NT-10GF/10GP Grey
Product code	:	EM10017868
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Glass, oxide	65997-17-3	5 - 10
Graphite	7782-42-5	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 	
Chronic exposure Medical Conditions Aggravated by Exposure:	Refer to Section 11 for Toxicological Information.None known.	
Aggravated by Exposure:		

PolyOne.

MATERIAL SAFETY DATA SHEET **XEdgetek NT-10GF/10GP Grey**

Version Number 1.0 Revision Date 06/19/2009 Page 2 of 6 Print Date 1/8/2012

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	•	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET XEdgetek NT-10GF/10GP Grey

Version Number 1.0 Revision Date 06/19/2009

Water solubility

Page 3 of 6 Print Date 1/8/2012

8.1				
	EXPOSURE	CONTROLS/PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protect	ive equipment normally	required.
Eye/Face Protection	: Sa	afety glasses with side-shields	5	
Hand protection	: P1	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: Sa	afety shoes		
General Hygiene Considerations		andle in accordance with goo actice. Wash hands before b		
Engineering measures		eat only in areas with appropropriate exhaust ventilation		Provide
Components Graphite	Value 2 mg/m3	Exposure time	Exposure type	T
		Time Weighted Average	Respirable fraction	List:
Graphite	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	2.5 mg/m3	• •	Respirable fraction. Respirable.	
		(TWA): Recommended exposure	-	ACGIH NIOSH
	2.5 mg/m3	(TWA): Recommended exposure limit (REL): Time Weighted Average	Respirable.	ACGIH NIOSH
	2.5 mg/m3 2.5 mg/m3	(TWA): Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average	Respirable.	ACGIH NIOSH OSHA Z1A
	2.5 mg/m3 2.5 mg/m3 2 mg/m3	(TWA): Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	Respirable.	ACGIH NIOSH OSHA Z1A MX OEL
	2.5 mg/m3 2.5 mg/m3 2 mg/m3 10 mg/m3	(TWA): Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Respirable dust.	ACGIH NIOSH OSHA Z1A MX OEL MX OEL
	2.5 mg/m3 2.5 mg/m3 2 mg/m3 10 mg/m3 5 mg/m3 15 mg/m3	(TWA): Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	Respirable. Respirable dust. Respirable fraction. Total dust.	ACGIH NIOSH OSHA Z1A MX OEL MX OEL OSHA Z1
	2.5 mg/m3 2.5 mg/m3 2 mg/m3 10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC	(TWA): Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: PEL: PEL:	Respirable dust. Respirable fraction. Total dust.	ACGIH NIOSH OSHA Z1A MX OEL MX OEL OSHA Z1 OSHA Z1
Form	2.5 mg/m3 2.5 mg/m3 2 mg/m3 10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solid	(TWA): Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: PEL: PEL: PEL: PEL:	Respirable. Respirable dust. Respirable fraction. Total dust. OPERTIES oration rate : Not	ACGIH NIOSH OSHA Z1A MX OEL MX OEL OSHA Z1 OSHA Z1
	2.5 mg/m3 2.5 mg/m3 2 mg/m3 10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solid	(TWA): Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: PEL: PEL: CAL AND CHEMICAL PRO	Respirable. Respirable dust. Respirable fraction. Total dust. OPERTIES pration rate : Not fic Gravity : Not	ACGIH NIOSH OSHA Z1A MX OEL MX OEL OSHA Z1 OSHA Z1

10. STABILITY AND REACTIVITY

: Insoluble

3/6

PolyOne

MATERIAL SAFETY DATA SHEET **XEdgetek NT-10GF/10GP Grey**

Version Number 1.0 Revision Date 06/19/2009 Page 4 of 6 Print Date 1/8/2012

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name Graphite		Effect Systemic effects	Target OrganRespiratory system, heart or circulatory system.	
7782-42-5					
		12. ECOLOGIO	CAL INFORMATION	1	
Persistence and degra	adability	: Not readily b	iodegradable.		
Environmental Toxicity		: Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Potential		: Chemicals are not readily available as they are bound within the polymer matrix.			
Additional advice		: Not applicabl	e		
		13. DISPOSAL	CONSIDERATIONS	5	
Product		possible recyc generator of v classification	cling is preferred to dis waste material has the r	product can be recycled. When posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.	
Contaminated packag	ging	material has t transportation	he responsibility for pr	e. The generator of waste oper waste classification, lance with applicable federal, s.	
		14. TRANSPO	RT INFORMATION		

PolyOne.

MATERIAL SAFETY DATA SHEET **XEdgetek NT-10GF/10GP Grey**

sion Date 06/19/2009	Print Date 1/8/201
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	is Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 1	oxic Chemicals:
SARA Title III Section 313	
Unless specific chemicals are	oxic Chemicals: identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are Canadian Regulations:	

PolyOne

MATERIAL SAFETY DATA SHEET **XEdgetek NT-10GF/10GP Grey**

Version Number 1.0 Revision Date 06/19/2009 Page 6 of 6 Print Date 1/8/2012

DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Listed	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	
			_

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.