PolvOne

MATERIAL SAFETY DATA SHEET X GRV-15091-01-2

Version Number 1.3 Revision Date 03/21/2014

Page 1 of 6 Print Date 3/25/2014

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure		
number		or accident).		
Product name	:	X GRV-15091-01-2		
Product code	:	EM10018138		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

ComponentsCAS-No.Weight percentTungsten7440-33-760 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET X GRV-15091-01-2

Version Number 1.3 Revision Date 03/21/2014 Page 2 of 6 Print Date 3/25/2014

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET X GRV-15091-01-2

Version Number 1.3 Revision Date 03/21/2014 Page 3 of 6 Print Date 3/25/2014

8.1	EXPOSURE	CONTROLS/PERSONA	L PROTECTION		
Respiratory protection	: N	lo personal respiratory prote	ctive equipment normally	required.	
Eye/Face Protection	: S	Safety glasses with side-shields			
Hand protection	: P	rotective gloves			
Skin and body protection	: L	Long sleeved clothing			
Additional Protective Measures	: S	Safety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		leat only in areas with appropriate exhaust ventilation		. Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Tungsten	5 mg/m3	Time Weighted Average (TWA):		ACGIH	
	10 mg/m3	Short Term Exposure Lim (STEL):	it as W	ACGIH	
	5 mg/m3	Time Weighted Average (TWA):	as W	MX OEL	
	10 mg/m3	Short Term Exposure Lim (STEL):	it as W	MX OEL	
	9. PHYSI	CAL AND CHEMICAL P	ROPERTIES		
Form	: solid	Eva	pouration rate : No	ot applicable	
Appearance				ot determined	
Colour				ot established	
Odour	: very			t applicable	
Melting point/range		-		t applicable	
Boiling Point:		pplicable pH	: no	t applicable	
Water solubility	: insol	uble			
	10. 8	STABILITY AND REACT	TVITY		
Stability	: Т	he product is stable if stored	l and handled as prescribe	ed.	
Hazardous Polymerization	1 : V	Vill not occur.			
Conditions to avoid	т	o avoid thermal decomposit			

PolyOne.

MATERIAL SAFETY DATA SHEET X GRV-15091-01-2

sion Number 1.3 Page 4 ision Date 03/21/2014 Print Date 3/25/2				
Incompatible Materials	: Strong acids,	, oxidizing and reducing	ng agents	
Hazardous decomposition products			oxide (CO), oxides of nitrogen nd smoke are all possible.	
	11. TOXICOLO	GICAL INFORMATIO	ON	
This mixture has not been er health data for the individua <u>Toxicity Overview</u>			ure effects listed are based on exi	
	llowing components v	which in their pure form	have the following characteristic	
CAS-No. 7440-33-7 Tur	Chemical Name ngsten	Effect Systemic effects	Target OrganEyes, Skin, Respiratorysystem, blood and bloodforming system.	
Tungsten 7440-33-7 Pro Exposure to freshly forme	d fumes from heated	metal may cause "me	tal fume fever''.	
	d fumes from heated		tal fume fever''.	
	d fumes from heated 12. ECOLOGI y : Not readily b : Chemicals ar	metal may cause "me CAL INFORMATION biodegradable. re not readily available a	tal fume fever''.	
Exposure to freshly former Persistence and degradabilit	d fumes from heated 12. ECOLOGI y : Not readily b : Chemicals ar polymer mat : Chemicals ar	metal may cause "me CAL INFORMATION biodegradable. re not readily available a rix. re not readily available a	tal fume fever''.	
Exposure to freshly formed Persistence and degradabilit Environmental Toxicity	d fumes from heated 12. ECOLOGIO y : Not readily b : Chemicals ar polymer mat	metal may cause "me CAL INFORMATION biodegradable. re not readily available a rix. re not readily available a rix.	tal fume fever''.	
Exposure to freshly formed Persistence and degradabilit Environmental Toxicity Bioaccumulation Potential	d fumes from heated 12. ECOLOGIO y : Not readily b : Chemicals ar polymer mat : Chemicals ar polymer mat : not applicabl	metal may cause "me CAL INFORMATION biodegradable. re not readily available a rix. re not readily available a rix.	tal fume fever''.	
Exposure to freshly formed Persistence and degradabilit Environmental Toxicity Bioaccumulation Potential	d fumes from heated 12. ECOLOGIO y : Not readily b : Chemicals ar polymer mat : Chemicals ar polymer mat : not applicabl 13. DISPOSAL : Like most the possible recy generator of classification	metal may cause "me <u>CAL INFORMATION</u> biodegradable. re not readily available a rix. re not readily available a rix. le <u>CONSIDERATIONS</u> ermoplastic plastics the vcling is preferred to dis waste material has the r	tal fume fever''.	
Exposure to freshly former Persistence and degradabilit Environmental Toxicity Bioaccumulation Potential Additional advice	d fumes from heated 12. ECOLOGIO y : Not readily b : Chemicals ar polymer mat : Chemicals ar polymer mat : not applicable 13. DISPOSAL : Like most the possible recy generator of classification applicable fe : Recycling is material has transportation	metal may cause "me <u>CAL INFORMATION</u> biodegradable. re not readily available a rix. re not readily available a rix. re not readily available a rix. le <u>CONSIDERATIONS</u> ermoplastic plastics the vcling is preferred to dis waste material has the r h, transportation and disj deral, state/provincial a preferred when possible the responsibility for pr	tal fume fever''.	

PolyOne.

MATERIAL SAFETY DATA SHEET X GRV-15091-01-2

sion Number 1.3 vision Date 03/21/2014		Page 5 of e Print Date 3/25/2014
U.S. DOT Classification	: N	lot regulated for transportation.
ICAO/IATA		efer to specific regulation.
IMO/IMDG (maritime)		efer to specific regulation.
		REGULATORY INFORMATION
US Regulations:	<u> </u>	
OSHA Status	· C	lassified as hazardous based on components.
TSCA Status		All components of this product are listed on or exempt from the SCA Inventory.
US. EPA CERCLA Hazardo	us Substar	nces (40 CFR 302)
not applicable		
California Proposition 65	n : N	ot applicable
SARA Title III Section 302 I	Extremely	Hazardous Substance
Unless specific chemicals are	e identifie	d under this section, this product is Not Applicable under this regulation
SARA Title III Section 313	Гoxic Che	micals:
Unless specific chemicals are	e identifie	d under this section, this product is Not Applicable under this regulation
Canadian Regulations:		
National Pollutant Rel	lease Inve	entory (NPRI)
not applicable		
WHMIS Classification	on : N	lot controlled.
	: A	All components of this product are on the Canadian Domestic
DSL	S	ubstances List (DSL) or are exempt.
DSL National Inventories:	S	ubstances List (DSL) or are exempt.

PolvOne

MATERIAL SAFETY DATA SHEET X GRV-15091-01-2

Version Number 1.3 Revision Date 03/21/2014

Page 6 of 6 Print Date 3/25/2014

China IECS:ListedEurope EINECS:ListedJapan ENCS:Not determinedKorea KECI:ListedPhilippines PICCS:Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.