PolvOne

MATERIAL SAFETY DATA SHEET X NN-35MG/000 BLACK

Version Number 1.1 Revision Date 03/21/2014

Page 1 of 6 Print Date 3/25/2014

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	X NN-35MG/000 BLACK		
Product code	:	EM10021010		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use		Industrial Applications		

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Quartz	14808-60-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET X NN-35MG/000 BLACK

Version Number 1.1 Revision Date 03/21/2014 Page 2 of 6 Print Date 3/25/2014

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

PolyOne.

MATERIAL SAFETY DATA SHEET X NN-35MG/000 BLACK

Version Number 1.1 Revision Date 03/21/2014 Page 3 of 6 Print Date 3/25/2014

Respiratory protection	: No personal respir		atory protecti	ive equipment normally	required.
Eye/Face Protection	: S	afety glasses with	n side-shields		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved cloth	ing		
Additional Protective Measures	: Safety shoes				
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure	time	Exposure type	List:
*	0.025	Exposure time Time Weighted Average		Respirable fraction.	ACGIH
Quartz	mg/m3	(TWA):		Respirable fraction.	ACOIII
	0.05	Recommended	/	Respirable dust.	NIOSH
	mg/m3	limit (R		Respirable dust.	Mobil
	0.1 mg/m3	Time Weighte (TWA	d Average	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighte (TWA	-	Respirable.	Z3
	0.3 mg/m3	Time Weighte (TWA		Total dust.	Z3
	0.1 mg/m3	Time Weighte (TWA	d Average		MX OEL
	9. PHYSIC	CAL AND CHEN	MICAL PRO	OPERTIES	
Form	: solid		Ever	uration rate : Not	applicable
Appearance		ts, Slabs			determined
Colour	: pene : BLA		abs Specific Gravity Bulk density		established
Odour	: very			•	applicable
Melting point/range	•	determined			applicable
		pplicable	pH		applicable
		uble	L		
Boiling Point: Water solubility	. 111501				

MATERIAL SAFETY DATA SHEET X NN-35MG/000 BLACK

Version Number 1.1 Revision Date 03/21/2014 Page 4 of 6 Print Date 3/25/2014

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the

PolyOne.

MATERIAL SAFETY DATA SHEET X NN-35MG/000 BLACK

Version Number 1.1 Revision Date 03/21/2014 Page 5 of 6 Print Date 3/25/2014

Additional advice	:	not applicable
	13	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Refer to specific regulation.
IMO/IMDG (maritime)	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Subs	stances (40 CFR 302)
not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext	reme	ely Hazardous Substance
Unless specific chemicals are id	lenti	fied under this section, this product is Not Applicable under this regula

MATERIAL SAFETY DATA SHEET X NN-35MG/000 BLACK

Version Number 1.1 Revision Date 03/21/2014 Page 6 of 6 Print Date 3/25/2014

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Maleic anhydride	108-31-6	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
108-31-6	
14808-60-7	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Listed
Korea KECI	: Listed
Philippines PICCS	: Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.