PolvOne

MATERIAL SAFETY DATA SHEET LC 411-157

Version Number 1.2 Revision Date 07/09/2012

Page 1 of 6 Print Date 8/27/2012

POLYONE CORPORATI 33587 Walker Road, Avoi		OH 44012
Telephone E mergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LC 411-157
Product code	:	EM10025069
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	•	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Talc	14807-96-6	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET *LC 411-157*

Version Number 1.2 Revision Date 07/09/2012 Page 2 of 6 Print Date 8/27/2012

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
-		
Flammable Limits		not applicable
Upper explosion limit	:	not applicable
Lower explosion limit	:	not applicable
Autoignition temperature	:	not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
		contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET LC 411-157

Version Number 1.2 Revision Date 07/09/2012

Page 3 of 6 Print Date 8/27/2012

8. EXPOSURE CONTROLS/PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection : Safety glasses with side-shields Hand protection : Long sleeved clothing Additional Protective : Safety shoes Measures : General Hygiene : Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Imme Weighted Average Respirable fraction. ACGIH (TWA): : NIOSH 1mit (REL): : Imme Weighted Average Respirable. IOSH 1 : : : Imme Weighted Average Respirable. Z3 2 mg/m3 Time Weighted Average Respirable. Z3 CfWA): 2 mg/m3 Time Weighted Average Respirable. Z3 Z3 0.1 mg/m3 Time Weighted Average <th></th> <th></th> <th>nd contamination. Keep in a d</th> <th>• •</th> <th>1</th>			nd contamination. Keep in a d	• •	1
Eye/Face Protection ::::::::::::::::::::::::::::::::::::					
Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : General Hygiene General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Mean machinery Components Value Exposure time Exposure type List: Talc 2 mg/m3 Time Weighted Average Respirable fraction. ACGIH (TWA): 2 mg/m3 Recommended exposure Respirable dust. OSHA Z1A 0.1 mg/m3 Time Weighted Average Respirable dust. OSHA Z1A (TWA): : Cotal dust. Z3 (TWA): : Iotal dust. Z3 (TWA): : Not applicable Appearance : pellets, Slabs Specific Gravity : Not applicable Appearance : pellets, Slabs Specific Gravity : Not applicable Odour : NOt determined	Respiratory protection	: N	o personal respiratory protecti	ive equipment normally i	required.
Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Karping in the exposure time interventilation is the end of workday. Components Value Exposure time interventilation at machinery. Exposure limit(s) : Components Value interventilation at machinery. Exposure limit(s) : : NIOSH 1 : : : 2 mg/m3 Recommended exposure interventilation. ACGIH (TWA): NIOSH 2 mg/m3 Time Weighted Average interventile dust. OSHA ZIA (TWA): 0.1 : : : : 0.1 : : : : • : : : : • : : : : : • : : :	Eye/Face Protection	: Sa	afety glasses with side-shields		
Additional Protective Measures :: Safety shoes General Hygien Considerations :: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures :: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Exposure time Exposure type List: Talc 2 mg/m3 Time Weighted Average (TWA); Respirable fraction. ACGIH 2 mg/m3 Recommended exposure limit (REL); NIOSH NIOSH 0.1 mg/m3 Time Weighted Average (TWA); Respirable dust. OSHA ZIA 0.1 mg/m3 Time Weighted Average (TWA); Total dust. Z3 0.3 mg/m3 Time Weighted Average (TWA); Not applicable PHYSICAL AND CHEMICAL PROPERTIES Not applicable Form :: solid Evaporation rate Not determined Not established Qour : very faint Vapour pressure Not established Not applicable Melting point/range : Not determined Vapour density : not applicable Huttret : : not applicable	Hand protection	: P1	: Protective gloves		
Measures	Skin and body protection	: Le	ong sleeved clothing		
Considerations practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s)		: Sa	afety shoes		
appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Exposure time Exposure type List: Talc 2 mg/m3 Time Weighted Average Respirable fraction. ACGIH (TWA): 2 mg/m3 Recommended exposure Respirable. NIOSH imit (REL): 1 1 OSHA Z1A (TWA): 0.1 mg/m3 Time Weighted Average Respirable dust. OSHA Z1A (TWA): 0.1 mg/m3 Time Weighted Average Respirable. Z3 (TWA): 0.3 mg/m3 Time Weighted Average Total dust. Z3 (TWA): 0.3 mg/m3 Time Weighted Average Total dust. Z3 (TWA): 0.3 mg/m3 Time Weighted Average Total dust. Z3 (TWA): 0.3 mg/m3 Time Weighted Average Total dust. Z3 (TWA): 0.3 mg/m3 Time Weighted Average Total dust. Z3 (TWA): Vapour average Not determined Vapour average Not determined Appearance : pellets, Slabs Specific Gravity : Not established <td></td> <td></td> <td></td> <td></td> <td></td>					
Components Value Exposure time Exposure type List: Tale 2 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACGIH 2 mg/m3 Recommended exposure limit (REL): Respirable. NIOSH 2 mg/m3 Time Weighted Average (TWA): Respirable. OSHA Z1A 0.1 mg/m3 Time Weighted Average (TWA): Respirable. Z3 0.3 mg/m3 Time Weighted Average (TWA): Total dust. Z3 OR PHYSICAL AND CHEMICAL PROPERTIES Performance : pellets, Slabs Specific Gravity : Not applicable Appearance : pellets, Slabs Specific Gravity : Not determined Odour : NO PIGMENT Bulk density : Not established Odour : very faint Vapour pressure : not applicable Melting point/range : Not determined Vapour density : not applicable Boiling Point: : not applicable pH : not applicable Water solubility : insoluble INO REACTIVITY	Engineering measures				Provide
Talc 2 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACGIH 2 mg/m3 Recommended exposure limit (REL): Respirable. NIOSH 2 mg/m3 Time Weighted Average (TWA): Respirable. OSHA Z1A 0.1 mg/m3 Time Weighted Average (TWA): Respirable dust. OSHA Z1A 0.1 mg/m3 Time Weighted Average (TWA): Respirable. Z3 0.3 mg/m3 Time Weighted Average (TWA): Total dust. Z3 0.3 mg/m3 Time Weighted Average (TWA): Total dust. Z3 9. PHYSICAL AND CHEMICAL PROPERTIES Form : solid Evaporation rate : Not applicable Appearance : pellets, Slabs Specific Gravity : Not determined Colour : NO PIGMENT Bulk density : Not applicable Melting point/range : Not determined Vapour density : not applicable Boiling Point: : not applicable pH : not applicable IO. STABILITY AND REACTIVITY	Exposure limit(s)				
Image: Constraint of the second se	Components	Value	Exposure time	Exposure type	List:
2 mg/m3 Recommended exposure limit (REL): Respirable. NIOSH 2 mg/m3 Time Weighted Average (TWA): Respirable dust. OSHA Z1A 0.1 mg/m3 Time Weighted Average (TWA): Respirable. Z3 0.1 mg/m3 Time Weighted Average (TWA): Total dust. Z3 0.3 mg/m3 Time Weighted Average (TWA): Total dust. Z3 9. PHYSICAL AND CHEMICAL PROPERTIES Form : solid Evaporation rate : Not applicable Appearance : pellets, Slabs Specific Gravity : Not determined Colour : NO PIGMENT Bulk density : Not established Odour : very faint Vapour pressure : not applicable Melting point/range : Not determined Vapour density : not applicable Boiling Point: : not applicable pH : not applicable Water solubility : insoluble Image: Not REACTIVITY	Talc	2 mg/m3	• •	Respirable fraction.	ACGIH
Image: Constraint of the second system of		2 mg/m3	Recommended exposure	Respirable.	NIOSH
Image: constraint of the state of the s		2 mg/m3		Respirable dust.	OSHA Z1A
0.3 mg/m3 Time Weighted Average (TWA): Total dust. Z3 9. PHYSICAL AND CHEMICAL PROPERTIES Form : solid Evaporation rate : Not applicable Appearance : pellets, Slabs Specific Gravity : Not determined Colour : NO PIGMENT Bulk density : Not established Odour : very faint Vapour pressure : not applicable Melting point/range : Not determined Vapour density : not applicable Boiling Point: : not applicable pH : not applicable IO. STABILITY AND REACTIVITY		0.1 mg/m3		Respirable.	Z3
Form: solidEvaporation rate: Not applicableAppearance: pellets, SlabsSpecific Gravity: Not determinedColour: NO PIGMENTBulk density: Not establishedOdour: very faintVapour pressure: not applicableMelting point/range: Not determinedVapour density: not applicableBoiling Point:: not applicablepH: not applicableWater solubility: insolubleInsolubleInsolubleIO. STABILITY AND REACTIVITY		0.3 mg/m3	Time Weighted Average	Total dust.	Z3
Appearance : pellets, Slabs Specific Gravity : Not determined Colour : NO PIGMENT Bulk density : Not established Odour : very faint Vapour pressure : not applicable Melting point/range : Not determined Vapour density : not applicable Boiling Point: : not applicable pH : not applicable Water solubility : insoluble Insoluble Insoluble		9. PHYSIC	CAL AND CHEMICAL PRO	OPERTIES	
	Appearance Colour Odour Melting point/range Boiling Point:	: pellet : NO F : very : Not d : not a	ts, Slabs Specif PIGMENT Bulk d faint Vapou letermined Vapou pplicable pH	ic Gravity: Notlensity: Notrr pressure: notrr density: not	determined established applicable applicable
Stability : Stable		10. S	TABILITY AND REACTIV	/ITY	
	Stability	: St	able		
3/6					

MATERIAL SAFETY DATA SHEET LC 411-157

Version Number 1.2 Revision Date 07/09/2012 Page 4 of 6 Print Date 8/27/2012

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system,
			Skin.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14807-96-6	Talc	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	not applicable

13. DISPOSAL CONSIDERATIONS



MATERIAL SAFETY DATA SHEET LC 411-157

Version Number 1.2 Revision Date 07/09/2012	Page 5 of 6 Print Date <i>8/27/2012</i>
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	as Substances (40 CFR 302)
not applicable	
not approable	
California Propositior 65	i : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation



MATERIAL SAFETY DATA SHEET LC 411-157

Version Number 1.2 Revision Date 07/09/2012

Page 6 of 6 Print Date 8/27/2012

National Pollutant Release	se Iı	nventory (NPRI)
not applicable		
WHMIS Classification	:	D2A
DSL	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.