PolyOne

MATERIAL SAFETY DATA SHEET X ST-1052-001-2

Version Number 1.0 Revision Date 08/24/2012 Page 1 of 6 Print Date 8/29/2012

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION			
33587 Walker Road, Avon Lake, OH 44012			
Telephone E mergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	X ST-1052-001-2	
Product code	:	EM10026426	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Carbon	7440-44-0	1 - 5
Talc	14807-96-6	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET X ST-1052-001-2

Version Number 1.0 Revision Date 08/24/2012 Page 2 of 6 Print Date 8/29/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET X ST-1052-001-2

Version Number 1.0 Revision Date 08/24/2012 Page 3 of 6 Print Date 8/29/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	2 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	2 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility solid
pellets, Slabs
NO PIGMENT
very faint
Not determined
not applicable
insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

10. STABILITY AND REACTIVITY

olvOn<u>e</u>

MATERIAL SAFETY DATA SHEET X ST-1052-001-2

Version Number 1.0 Revision Date 08/24/2012

Page 4 of 6 Print Date 8/29/2012

Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7440-44-0	Carbon	Systemic effects	Respiratory system, heart or
			circulatory system.
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system,
			Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7440-44-0	Carbon	Oral LD50	10,000 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14807-96-6	Talc	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET X ST-1052-001-2

ion Number 1.0 sion Date 08/24/2012	Page 5 Print Date 8/29/2
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable

MATERIAL SAFETY DATA SHEET X ST-1052-001-2

Version Number 1.0 Revision Date 08/24/2012 Page 6 of 6 Print Date 8/29/2012

SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) not applicable WHMIS Classification : D2A DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Not determined : China IECS Not determined : Europe EINECS : Listed Japan ENCS Not determined : Korea KECI Not determined : **Philippines PICCS** Not determined · **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.