MATERIAL SAFETY DATA SHEET X GT0100-0030 SS Black

Version Number 1.1 Revision Date 11/01/2012

Page 1 of 7 Print Date 11/1/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	X GT0100-0030 SS Black
Product code :	EM10026712
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Carbon black	1333-86-4	1 - 5
Chromium	7440-47-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET X GT0100-0030 SS Black

Version Number 1.1 Revision Date 11/01/2012 Page 2 of 7 Print Date 11/1/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne.

MATERIAL SAFETY DATA SHEET X GT0100-0030 SS Black

Version Number 1.1 Revision Date 11/01/2012 Page 3 of 7 Print Date 11/1/2012

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.		
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION		
Respiratory protection	:	No personal respiratory protective equipment normally required.		
Eye/Face Protection	:	Safety glasses with side-shields		
Hand protection	:	Protective gloves		
Skin and body protection	:	Long sleeved clothing		
Additional Protective Measures	:	Safety shoes		
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		
Exposure limit(s)				

PolyOne

MATERIAL SAFETY DATA SHEET X GT0100-0030 SS Black

Version Number 1.1 Revision Date 11/01/2012 Page 4 of 7 Print Date 11/1/2012

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Chromium	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	1 mg/m3	PEL:	as Cr	OSHA Z1
	1 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid : pellets, Slabs : BLACK : very faint Not determined : not applicable : insoluble

:

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

Not applicable : Not determined : Not established : not applicable not applicable not applicable

:

:

:

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET X GT0100-0030 SS Black

Version Number 1.1 Revision Date 11/01/2012 Page 5 of 7 Print Date 11/1/2012

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
7440-47-3	Chromium	Systemic effects	Eyes, Skin, Respiratory
			system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Chromium 7440-47-3 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	not applicable

13. DISPOSAL CONSIDERATIONS

PolyOne.

MATERIAL SAFETY DATA SHEET X GT0100-0030 SS Black

sion Number 1.1 ision Date 11/01/2012	Page 6 o Print Date 11/1/20
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	Substances (40 CFR 302)
not applicable	
California Propositior 65	: Not applicable
SARA Title III Section 302 E	remely Hazardous Substance
Unless specific chemicals are	lentified under this section, this product is Not Applicable under this regulati
SARA Title III Section 313 T	xic Chemicals:
Unless specific chemicals are	lentified under this section, this product is Not Applicable under this regulati
	CAS-No. Weight percent
Chemical Name CHROMIUM	7440-47-3 10.00 - 30.00

PolyOne

MATERIAL SAFETY DATA SHEET X GT0100-0030 SS Black

Version Number 1.1 Revision Date 11/01/2012 Page 7 of 7 Print Date 11/1/2012

Canadian Regulations:

Canadian Regulations:					
National Pollutant Release	e Iı	nventory (NPRI)			1
Chemical Name			CAS-No.	Weight percent	NPRI ID#
Chromium			7440-47-3	10.00 - 30.00	
Manganese			7439-96-5	0.10 - 1.00	
WHMIS Classification	:	D2A			
WHMIS Ingredient Discl	osu	re List			
CAS-No. 1333-86-4					
7440-47-3					
					a
DSL	:	DSL status has restricted by reg	not been determine	ed. Quantity use i	n Canada may be
National Inventories:					
Australia AICS	:	Not determined			
China IECS		Not determined			
Chinia IECS	•	Not determined			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			
		16. OTHER IN	FORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.