PolvOne

MATERIAL SAFETY DATA SHEET X SR-01439-2 Bright Glitter

Version Number 1.0 Revision Date 02/25/2013

Page 1 of 7 Print Date 2/25/2013

1.	PROD	UCT AND COMPANY IDENTIFICATION
POLYONE CORPORATI		011 44910
33587 Walker Road, Avoi	n Lake,	OH 44012
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	X SR-01439-2 Bright Glitter
Product code	:	EM10028193
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use		Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Aluminum	7429-90-5	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

MATERIAL SAFETY DATA SHEET X SR-01439-2 Bright Glitter

Version Number 1.0 Revision Date 02/25/2013 Page 2 of 7 Print Date 2/25/2013

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

PolyOne.

MATERIAL SAFETY DATA SHEET X SR-01439-2 Bright Glitter

Version Number 1.0 Revision Date 02/25/2013 Page 3 of 7 Print Date 2/25/2013

Respiratory protection	: No personal respiratory protective equipment normally required
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne

MATERIAL SAFETY DATA SHEET X SR-01439-2 Bright Glitter

Version Number 1.0 Revision Date 02/25/2013 Page 4 of 7 Print Date 2/25/2013

Components	Value	Exposure time	Exposure type	List:
Aluminum	1 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Welding fume or pyrophoric powder. as Al	NIOSH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	15 mg/m3	Time Weighted Average (TWA):	Total dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Respirable dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Fume. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Welding fume.	MX OEL
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form:Appearance:Colour:Odour:Melting point/range:Boiling Point::Water solubility:
 - solid
 pellets, Slabs
 GREY
 very faint
 Not determined
 not applicable
 insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable
- **10. STABILITY AND REACTIVITY** The product is stable if stored and handled as prescribed. Stability : Hazardous Polymerization Will not occur. : Conditions to avoid To avoid thermal decomposition, do not overheat. : **Incompatible Materials** Strong acids, oxidizing and reducing agents : Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products (NOx), other hazardous materials, and smoke are all possible.

PolyOne

MATERIAL SAFETY DATA SHEET X SR-01439-2 Bright Glitter

Version Number 1.0 Revision Date 02/25/2013

Page 5 of 7 Print Date 2/25/2013

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory
			system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	

PolyOne.

MATERIAL SAFETY DATA SHEET X SR-01439-2 Bright Glitter

Version Number 1.0 Revision Date 02/25/2013 Page 6 of 7 Print Date 2/25/2013

OSHA Status	: Classified as ha	azardous based on	components.		
TSCA Status	TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardou	s Substances (40 CFR	. 302)			
not applicable					
California Proposition 65	n : Not applicable				
SARA Title III Section 302 E	Extremely Hazardous S	ubstance			
Unless specific chemicals are	identified under this s	ection, this produc	et is Not Applicabl	le under this regu	Ilation
-		-		-	
SARA Title III Section 313 T	oxic Chemicals:				
Unless specific chemicals are		ection this produc	rt is Not Applicabl	le under this regu	lation
Canadian Regulations:		·····, ···· [·····			
National Pollutant Rel	ansa Invantary (NDDI)				
Chemical Name	ease inventory (INFRI)	CAS-No.	Weight	NPRI ID#	
Aluminum		7429-90-5	0.10 - 1.00		
WHMIS Classification	n · D2P				
WHMIS Ingredient Di	sclosure List				
CAS-No. 7429-90-5					
DSL	-	ts of this product a t (DSL) or are exe		n Domestic	
National Inventories:					
Australia AICS	: Not determined	1			
China IECS	: Not determined	d			

PolyOne.

MATERIAL SAFETY DATA SHEET X SR-01439-2 Bright Glitter

Version Number 1.0 Revision Date 02/25/2013 Page 7 of 7 Print Date 2/25/2013

Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.