

MATERIAL SAFETY DATA SHEET

X 2866-002-01

 Version Number 1.0
 Page 1 of 6

 Revision Date 05/21/2013
 Print Date 5/21/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : X 2866-002-01
Product code : EM10029226
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Benzenepropanoic acid, 3,5-bis(1,1-	32687-78-8	1 - 5
dimethylethyl)-4-hydroxy-,2-[3-[3,5-bis(1,1-		
dimethylethyl)-4-hydroxyphenyl]-1-		
oxopropyl]hydrazide		
Glass, oxide	65997-17-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Eyes, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically

irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eyes.

Skin : Avoid skin contact. Product contains unreacted organic peroxides



MATERIAL SAFETY DATA SHEET

X 2866-002-01

Version Number 1.0 Page 2 of 6 Print Date 5/21/2013 Revision Date 05/21/2013

which may cause mild skin irritation.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Move to fresh air in case of accidental inhalation of fumes from Inhalation

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

: Rinse immediately with plenty of water, also under the eyelids, for at Eyes

least 15 minutes. If eye irritation persists, seek medical attention.

Wash off with soap and plenty of water. If skin irritation persists Skin

seek medical attention.

5. FIREFIGHTING MEASURES

Flash point : not applicable

Flammable Limits

Upper explosion limit not applicable not applicable Lower explosion limit Auto-ignition temperature Not relevant

Suitable extinguishing media Water, Dry powder, Foam, Carbon dioxide (CO2).

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal.



MATERIAL SAFETY DATA SHEET

X 2866-002-01

 Version Number 1.0
 Page 3 of 6

 Revision Date 05/21/2013
 Print Date 5/21/2013

7. HANDLING AND STORAGE

Handling : Traces of methanol may be present when first opening package. Heat

only in areas with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Take measures to prevent the

build up of electrostatic charge.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place. Keep away from heat. Excessive storage temperature and humidity can degrade product

performance.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required when

handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this

material.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective

Measures

: Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Adequate

ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors. During processing and cross-linking, product can give off byproducts such as methanol. By-product vapors may be flammable. User must provide necessary precautions such as adequate ventilation

to prevent accumulation and ignition of vapors.

Exposure limit(s)

9. PHYSICAL AND CHEMICAL PROPERTIES

: solid Evapouration rate : Not applicable Form : pellets Specific Gravity Not determined Appearance : NO PIGMENT Bulk density Not established Colour Odour : characteristic Vapour pressure : not applicable



MATERIAL SAFETY DATA SHEET

X 2866-002-01

Version Number 1.0 Page 4 of 6
Revision Date 05/21/2013 Print Date 5/21/2013

Melting point/range : 115°C - 135°C (240°F - Vapour density : not applicable

275°F)

Boiling Point: : not applicable pH : not applicable

Water solubility : insoluble

10. STABILITY AND REACTIVITY

Stability : The product is stable if stored and handled as prescribed.

Hazardous Polymerization : Will not occur.

Conditions to avoid : To avoid thermal decomposition, do not overheat. Prolonged heating

may result in product degradation.

Incompatible Materials : Strong acids, oxidizing and reducing agents

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Traces of alcohols, acetophenone, alpha-methylstyrene, acetone, methane, ethane, or other byproducts may be liberated during processing or

decomposition.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
32687-78-8	Benzenepropanoic acid,	Chronic effects	Liver.
	3,5-bis(1,1-		
	dimethylethyl)-4-hydroxy-		
	,2-[3-[3,5-bis(1,1-		
	dimethylethyl)-4-		
	hydroxyphenyl]-1-		
	oxopropyl]hydrazide		

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
32687-78-8	Benzenepropanoic acid,	Oral LD50	> 7,000 mg/kg	rat
	3,5-bis(1,1-			
	dimethylethyl)-4-hydroxy-			
	,2-[3-[3,5-bis(1,1-			
	dimethylethyl)-4-			
	hydroxyphenyl]-1-			
	oxopropyl]hydrazide			



MATERIAL SAFETY DATA SHEET

X 2866-002-01

 Version Number 1.0
 Page 5 of 6

 Revision Date 05/21/2013
 Print Date 5/21/2013

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the

polymer matrix.

Additional advice : not applicable

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

IMO/IMDG (maritime) : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable



MATERIAL SAFETY DATA SHEET

X 2866-002-01

 Version Number 1.0
 Page 6 of 6

 Revision Date 05/21/2013
 Print Date 5/21/2013

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D2B

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.