MATERIAL SAFETY DATA SHEET X-HC-052113-0

Version Number 1.0 Revision Date 06/19/2013

Page 1 of 6 Print Date 6/19/2013

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	X-HC-052113-0		
Product code	:	EM10029587		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

CACN 337. 1. 1.

Components	CAS-No.	Weight percent
Barium sulfate	7727-43-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET X-HC-052113-0

Version Number 1.0 Revision Date 06/19/2013 Page 2 of 6 Print Date 6/19/2013

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIREFIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits		
Upper explosion limit		not applicable
Lower explosion limit	:	not applicable
Auto-ignition temperature	:	not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET X-HC-052113-0

Version Number 1.0 Revision Date 06/19/2013

Page 3 of 6 Print Date 6/19/2013

	EXPOSURE	CONTROLS/PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protect	ive equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: Long sleeved clothing			
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		andle in accordance with good ractice. Wash hands before br		
Engineering measures		eat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Components Barium sulfate	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type	List: ACGIH
		Time Weighted Average	Exposure type Respirable.	
	10 mg/m3	Time Weighted Average (TWA): Recommended exposure		ACGIH
	10 mg/m3 5 mg/m3	Time Weighted Average (TWA): Recommended exposure limit (REL): Recommended exposure	Respirable.	ACGIH NIOSH
	10 mg/m3 5 mg/m3 10 mg/m3	Time Weighted Average (TWA): Recommended exposure limit (REL): Recommended exposure limit (REL):	Respirable. Total Respirable fraction. Total dust.	ACGIH NIOSH NIOSH
	10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3	Time Weighted Average (TWA): Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: PEL: Time Weighted Average (TWA):	Respirable. Total Respirable fraction. Total dust. Respirable fraction.	ACGIH NIOSH NIOSH OSHA Z1
	10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 15 mg/m3	Time Weighted Average (TWA): Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: PEL: Time Weighted Average	Respirable. Total Respirable fraction. Total dust.	ACGIH NIOSH NIOSH OSHA Z1 OSHA Z1
	10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3	Time Weighted Average (TWA): Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average	Respirable. Total Respirable fraction. Total dust. Respirable fraction. Total dust.	ACGIH NIOSH NIOSH OSHA Z1 OSHA Z1
	10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIC : solid : pelle	Time Weighted Average (TWA): Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Evapo ts, Slabs Specif PIGMENT Bulk of	Respirable. Total Respirable fraction. Total dust. Respirable fraction. Total dust. OPERTIES ouration rate : Not Construction rate : Not It Gravity : Not It of an it is in the second secon	ACGIH NIOSH NIOSH OSHA Z1 OSHA Z1

10. STABILITY AND REACTIVITY

Stability

: The product is stable if stored and handled as prescribed.

PolyOne

MATERIAL SAFETY DATA SHEET X-HC-052113-0

Version Number 1.0 Revision Date 06/19/2013 Page 4 of 6 Print Date 6/19/2013

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.

PolyOne.

MATERIAL SAFETY DATA SHEET X-HC-052113-0

/ersion Number 1.0 Revision Date 06/19/2013		Page 5 of 6 Print Date <i>6/19/2013</i>
		1 11 1 Dato 0, 10,2010
ICAO/IATA	:	Refer to specific regulation.
IMO/IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
-		Classified as beendaus based on companyouts
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Sub	stances (40 CFR 302)
not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 Ex	trem	ely Hazardous Substance
Unless specific chemicals are	identi	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic (Themicals:
		fied under this section, this product is Not Applicable under this regulation
-	uenti	ince under tins section, tins product is Not Applicable under tins regulation
Canadian Regulations:	T	
National Pollutant Rele	ase n	nventory (INPRI)
not applicable		
WHMIS Classification	ı :	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed

PolyOne

MATERIAL SAFETY DATA SHEET X-HC-052113-0

Version Number 1.0 Revision Date 06/19/2013

Page 6 of 6 Print Date 6/19/2013

Europe EINECS:ListedJapan ENCS:Not determinedKorea KECI:ListedPhilippines PICCS:Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.