PolvOne

MATERIAL SAFETY DATA SHEET **NEUView UR75D20-1003 Natural**

Version Number 1.2 Revision Date 04/03/2014 Page 1 of 6 Print Date 4/10/2014

1. POLYONE CORPORATI		UCT AND COMPANY IDENTIFICATION
33587 Walker Road, Avon	n Lake,	OH 44012
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	NEUView UR75D20-1003 Natural
Product code	:	EM10031651
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use		Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Barium sulfate	7727-43-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

MATERIAL SAFETY DATA SHEET **NEUView UR75D20-1003 Natural**

Version Number 1.2 Revision Date 04/03/2014 Page 2 of 6 Print Date 4/10/2014

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIREFIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	: : :	not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

PolyOne.

MATERIAL SAFETY DATA SHEET NEUView UR75D20-1003 Natural

Version Number 1.2 Revision Date 04/03/2014 Page 3 of 6 Print Date 4/10/2014

Considerations practice. Wash hands before by Engineering measures : Heat only in areas with appropriappropriate exhaust ventilation Exposure limit(s) : Components Value Exposure time Barium sulfate 10 mg/m3 Time Weighted Average (TWA): 5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 15 mg/m3 PEL: 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 PEL: 9 PHYSICAL AND CHEMICAL PRE Form : solid	PROTECTION			
Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Handle in accordance with goo General Hygiene : Handle in accordance with goo Considerations : Heat only in areas with appropriate exhaust ventilation Engineering measures : Heat only in areas with appropriate exhaust ventilation Exposure limit(s) : Exposure time Barium sulfate 10 mg/m3 Time Weighted Average limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 5 mg/m3 PEL: 5 mg/m3 PEL: 15 mg/m3 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 9. PHYSICAL AND CHEMICAL PRO Form : solid Evapo	ive equipment normally r	required.		
Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Safety shoes General Hygiene : Handle in accordance with goo practice. Wash hands before be practice. Wash hands				
Additional Protective Measures : Safety shoes General Hygiene Considerations : Handle in accordance with goo practice. Wash hands before be presented as the properties of the prope				
Measures General Hygiene Considerations : Handle in accordance with goo practice. Wash hands before be engineering measures Engineering measures : Heat only in areas with appropriappropriate exhaust ventilation Exposure limit(s) Components Value Exposure limit(s) Components Value Exposure time Barium sulfate 10 mg/m3 Time Weighted Average (TWA): 5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 PEL: 5 mg/m3 PEL: 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid				
Considerations practice. Wash hands before by Engineering measures : Heat only in areas with appropriappropriate exhaust ventilation Exposure limit(s) : Components Value Exposure time Barium sulfate 10 mg/m3 Time Weighted Average (TWA): 5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 15 mg/m3 PEL: 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 PEL: 9 PHYSICAL AND CHEMICAL PRE Form : solid	: Safety shoes			
Components Value Exposure time Barium sulfate 10 mg/m3 Time Weighted Average (TWA): 5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 15 mg/m3 PEL: 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 PEL: 5 mg/m3 PEL: 9. PHYSICAL AND CHEMICAL PRO Form : solid	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Components Value Exposure time Barium sulfate 10 mg/m3 Time Weighted Average (TWA): 5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 5 mg/m3 PEL: 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Barium sulfate 10 mg/m3 Time Weighted Average (TWA): 5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 15 mg/m3 PEL: 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid				
Barium sulfate 10 mg/m3 Time Weighted Average (TWA): 5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 15 mg/m3 PEL: 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid	Exposure type	List:		
5 mg/m3 Recommended exposure limit (REL): 10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 15 mg/m3 PEL: 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid		ACGIH		
10 mg/m3 Recommended exposure limit (REL): 5 mg/m3 PEL: 15 mg/m3 PEL: 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid	Respirable.	NIOSH		
5 mg/m3 PEL: 15 mg/m3 PEL: 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PROPERTY Form : solid	Total	NIOSH		
5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid	Respirable fraction.	OSHA Z1		
(TWA): 10 mg/m3 Time Weighted Average (TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid Evapo	Total dust.	OSHA Z1		
(TWA): 9. PHYSICAL AND CHEMICAL PRO Form : solid	Respirable fraction.	OSHA Z1A		
Form : solid Evapo	Total dust.	OSHA Z1A		
1	DPERTIES			
1		1		
		applicable determined		
	2			
	2	established		
		applicable applicable		
Boiling Point: : not applicable pH		applicable		

10. STABILITY AND REACTIVITY

: not applicable

: insoluble

Stability

Water solubility

: The product is stable if stored and handled as prescribed.

pН

: not applicable

PolyOne

MATERIAL SAFETY DATA SHEET **NEUView UR75D20-1003 Natural**

Version Number 1.2 Revision Date 04/03/2014 Page 4 of 6 Print Date *4/10/2014*

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Strong acids, oxidizing and reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.

PolyOne.

MATERIAL SAFETY DATA SHEET **NEUView UR75D20-1003 Natural**

Version Number 1.2 Revision Date 04/03/2014	Page 5 of 6 Print Date 4/10/2014			
	1 mit Date 4/10/2014			
ICAO/IATA :	Refer to specific regulation.			
IMO/IMDG (maritime) :	Refer to specific regulation.			
15	. REGULATORY INFORMATION			
US Regulations:				
OSHA Status :	Classified as hazardous based on components.			
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous Subs	stances (40 CFR 302)			
not applicable				
California Proposition : 65	Not applicable			
SARA Title III Section 302 Extremely Hazardous Substance				
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
SARA Title III Section 313 Toxic C	Chemicals:			
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
Canadian Regulations:				
National Pollutant Release Inventory (NPRI)				
not applicable				
WHMIS Classification :	Not controlled.			
DSL :	All components of this product are on the Canadian Domestic			
	Substances List (DSL) or are exempt.			
National Inventories:				
Australia AICS :	Not determined			
China IECS :	Not determined			

PolyOne

MATERIAL SAFETY DATA SHEET **NEUView UR75D20-1003 Natural**

Version Number 1.2 Revision Date 04/03/2014 Page 6 of 6 Print Date 4/10/2014

Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.