

MATERIAL SAFETY DATA SHEET

3062 106 FLESH

Version Number 1.0 Revision Date 05/05/2003 Page 1 of 6 Print Date *11/11/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	3062 106 FLESH
Product code	:	FO0000213
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product has not been evaluated as a whole for health effects. Information provided on the health effects of this product is based on individual components. In addition, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Skin contact, Inhalation, Ingestion			
Acute exposure				
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.			
Ingestion	: May be harmful if swallowed.			
Eyes	: May cause eye/skin irritation.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			
Medical Conditions Aggravated by Exposure:	: None known.			



MATERIAL SAFETY DATA SHEET

3062 106 FLESH

Version Number 1.0 Revision Date 05/05/2003 Page 2 of 6 Print Date 11/11/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Seek medical attention if necessary.
Eyes	:	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	: : :	No data available. No data available. No data available. carbon dioxide (CO2), water, foam, dry chemical.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray Do not allow run-off from fire fighting to enter drains or water courses
Unusual Fire/Explosion Hazards	:	Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes.
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	:	The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.
		7. HANDLING AND STORAGE





3062 106 FLESH Version Number 1.0 Page 3 of 6 Revision Date 05/05/2003 Print Date 11/11/2011 Handling : Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may be necessary before use. Containers which are opened must be carefully resealed and kept Storage : upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION : A respirator is normally not required for routine handling of product in Respiratory protection areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. Airborne contaminant levels should be maintained below the occupational exposure guidelines. **Eye/Face Protection** Safety glasses with side-shields. Wear goggles or face shield during : operations that present a splash potential. : Impervious gloves such as rubber or PVC Hand protection Skin and body protection Long sleeved shirts and long pants are adequate for normal handling. : Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection. Additional Protective Safety shoes : Measures General Hygiene Wash hands before breaks and immediately after handling the product. : Considerations Handle in accordance with good industrial hygiene and safety practices. Engineering measures : Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

	9. PHYSICAL AND C	HEMICAL PROPERTIES		
Form	: Liquid	Evaporation rate	:	Slower than Butyl Acetate
Appearance	: Liquid	Specific Gravity	:	Not determined



MATERIAL SAFETY DATA SHEET

3062 106 FLESH

Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymeriza Conditions to avoid Incompatible Materials	: Stable.	ble pH	essure : Not established nsity : Heavier than air. : Not determined
Hazardous Polymeriza Conditions to avoid	: Stable.	LITY AND REACTIVIT	Y
Hazardous Polymeriza Conditions to avoid	ation : Will not		
Conditions to avoid			
	. .	occur.	
Incompatible Material	: Extremes	s of temperature and direct	t sunlight. Keep from freezing.
	s : Acids, m	etal salts, and solvents	
Hazardous decomposit products			noxide (CO), oxides of nitrogen and smoke are all possible.
		LOGICAL INFORMATI	ΙΟΝ
This product contains CAS-No.	the following component		m have the following characteristics:
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
Carcinogenicity: This product contains to data: CAS-No. IARC Carcinogen Class	Chemical Nan		m have the following carcinogenicity
1 - The component is c 2A - The component is	carcinogenic to humans, s probably carcinogenic s possibly carcinogenic	to humans.	
	known to be a human ca	arcinogen. o be a human carcinogen.	
	12. ECOLO	OGICAL INFORMATIO	N
Persistence and degrad	lability : No data	available.	
- ersistenee und degrad			



MATERIAL SAFETY DATA SHEET

3062 106 FLESH

ion Number 1.0 sion Date 05/05/2003			Pri	Page 5 int Date 11/11/2	
Bioaccumulation Potential	: No data availa	ıble.			
Additional advice	: No data availa	ıble.			
	13. DISPOSAL	CONSIDERATION	S		
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	has the respon	preferred when possib asibility for proper wa n accordance with applations.	ste classification	n, transportation	
	14. TRANSPOL	RT INFORMATION	Ň		
U.S. DOT Classification	: Refer to speci	fic regulation.			
ICAO/IATA : Refer to specific regulation.					
IMO / IMDG	: Refer to speci	fic regulation.			
	15. REGULATO	RY INFORMATIO	N		
US Regulations:					
OSHA Status	: Classified as h	nazardous based on co	omponents.		
TSCA Status	: All componer Inventory.	nts of this product are	listed on or exen	npt from the TSC	
US. EPA CERCLA Hazardou	s Substances (40 CFI	R 302)			
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Proc	
Ziram	137-30-4	0.0006	001 lbs	166,667 LB	
California Proposition 65	: WARNING! California to c	This product contains cause cancer.	s a chemical kno	wn to the State o	
SARA Title III Section 302 E	xtremely Hazardous !	Substance			

MATERIAL SAFETY DATA SHEET



PolyOne.

Version Number 1.0 Revision Date 05/05/2003		P Print Date 1	age 6 of 6 1/11/2011
Not applicable			
SARA Title III Section 313 Tox	ic C	Chemicals:	
Not applicable			
Canadian Regulations:			
WHMIS Classification	:	D2B	
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed.	
China IECS	:	Listed.	
Europe EINECS	:	Not determined.	
Japan ENCS	:	Not determined.	
Korea KECI	:	Not determined.	
Philippines PICCS	:	Listed.	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.