## MATERIAL SAFETY DATA SHEET

## 10-S-4680 CARPET LATEX

Version Number 1.3 Revision Date 10/21/2004 Page 1 of 6 Print Date 11/16/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	10-S-4680 CARPET LATEX
Product code :	F00000324
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This product is a water based mixture with an ammonia odor. The mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. The product is not combustible, but it will burn if involved in a fire, releasing hydrocarbon products of combustion. Inhalation of the ammonia from this product may cause respiratory irritation, coughing, sore throat, and labored breathing.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Skin contact, Inhalation, Ingestion
Acute exposure	
Inhalation	: Symptoms of breathing ammonia vapor concentrated from this product may include laryngitis, tracheitis, pulmonary edema, dyspnea, bronchospasms, and chest pains or pneumonitis. Symptoms are typically reversible.
Ingestion	: May be harmful if swallowed.
Eyes	: Liquid, aerosol, or vapors of this product are irritating and may cause tearing, reddening, and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.
Skin	: Skin contact may cause redness, irritation, and burns.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

## MATERIAL SAFETY DATA SHEET 10-S-4680 CARPET LATEX

Version Number 1.3 Revision Date 10/21/2004 Page 2 of 6 Print Date 11/16/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>No data available</li> <li>No data available</li> <li>No data available</li> <li>No data available</li> <li>carbon dioxide (CO2), water, foam, dry chemicalnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray Do not allow run-off from fire fighting to enter drains or water courses</li> </ul>
Unusual Fire/Explosion Hazards	: Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder



## MATERIAL SAFETY DATA SHEET 10-S-4680 CARPET LATEX

Version Number 1.3 Revision Date 10/21/2004 Page 3 of 6 Print Date 11/16/2011

	7. HANDLING AND STORAGE	
Handling	: Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material ma settle during storage. Careful mixing without introduction of air n be necessary before use.	
Storage	: Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.	
8. EXP	DSURE CONTROLS / PERSONAL PROTECTION	
Respiratory protection	: A respirator is normally not required for routine handling of product areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. If using a cartridg respirator, an ammonia cartridge is required to filter out potential excess ammonia vapors.	
Eye/Face Protection	: Safety glasses with side-shields. Wear goggles or face shield durin operations that present a splash potential.	ng
Hand protection	: Impervious gloves such as rubber or PVC	
Skin and body protection	: Long sleeved shirts and long pants are adequate for normal handlin Where operations present a splash or spill potential, employees sho wear chemically resistant clothing, boots, apron, gloves, and eye/fa protection.	bul
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Wash hands before breaks and immediately after handling the prod Handle in accordance with good industrial hygiene and safety practices.	uc
Engineering measures	: Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.	/
Exposure limit(s)		

<u>olyOne</u>

MATERIAL SAFETY DATA SHEET 10-S-4680 CARPET LATEX

Version Number 1.3

Revision Date 10/21/2004

Page 4 of 6 Print Date 11/16/2011

Components	Value	Exposure time	Exposur	e type	List:
Calcium carbonate 5 mg/m3		PEL:	Respirable	Respirable fraction.	
	15 mg/m3	PEL:	Total d	lust.	OSHA Z1
	9. PHYSICA	L AND CHEMICAL	PROPERTIES		
Form	: liquid	E	vaporation rate	: Slov Acet	ver than Buty tate
Appearance	: liquid	S	pecific Gravity:	: Not	determined
Color	: NO PIG		ulk density	: Not	applicable
Odor			apor pressure		established
Melting point/range	: Not app		apour density		vier than air.
Boiling Point:	: Not esta	P P	H	: Not	determined
Water solubility	: Completely miscible				
	<b>10. ST</b> A	ABILITY AND REA	CTIVITY		
Stability	: Stab	le.			
Hazardous Polymerization	on : Will not occur.				
Conditions to avoid : Extremes of temperature and direct sunlight. Keep from freezing.					
Incompatible Materials	npatible Materials : Acids, metal salts, and solvents				
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.				

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	No data available
Environmental Toxicity	:	No data available
<b>Bioaccumulation Potential</b>	:	No data available
Additional advice	:	No data available

PolyOne.

# MATERIAL SAFETY DATA SHEET 10-S-4680 CARPET LATEX

Version Number 1.3 Revision Date 10/21/2004 Page 5 of 6 Print Date 11/16/2011

Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State o California to cause cancer.
SARA Title III Section 302 E	xtremely Hazardous Substance
Not applicable	
SARA Title III Section 313 T	oxic Chemicals:
Not applicable Canadian Regulations:	

PolyOne

# MATERIAL SAFETY DATA SHEET 10-S-4680 CARPET LATEX

Version Number 1.3 Revision Date 10/21/2004

\_

Page 6 of 6 Print Date 11/16/2011

National Pollutant Release Inventory (NPRI)				
Not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.